


Description

- Surface mount Voltage Controlled Temperature Compensated Crystal Oscillator (VCTCXO) in a miniature 1.6 x 1.2mm surface mount package.
- Model IQXT-351
- Model Issue number 1

Frequency Parameters

- Frequency 52.0MHz
- Frequency Tolerance ±1.50ppm
- Tolerance Condition @ 25°C ±2°C
- Frequency Stability ±0.50ppm
- Operating Temperature Range -30.00 to 85.00°C
- Ageing ±1ppm max per year @ 25°C
±3°C
- Developed Frequencies: 26.0MHz and 52.0MHz
- Supply Voltage Variation (±5% change @ 25°C): ±0.1ppm max
- Load Variation (±10% change @ 25°C): ±0.1ppm max
- IR Reflow Resistance (referred to frequency before reflow): ±1ppm max

Electrical Parameters

- Supply Voltage 1.8V ±5%
- Current Draw 2.000mA
- Absolute Maximum Supply Voltage: -0.6V to 4.6V

Frequency Adjustment

- Pulling ±8ppm to ±13ppm
- Control Voltage 0.9V ±0.8V
- Absolute Maximum Control Voltage: -0.6V to Vs+0.6V
- Slope: Positive

Output Details

- Output Compatibility Clipped Sine
- Drive Capability 10kΩ//10pF
- Output Voltage Level: 0.8V pk-pk min
- Output: DC coupled
- Start Up Time (Vout ≥ 90%Vpk-pk): 2ms max

Noise Parameters




- Harmonic distortion: -5.0dBc max
- Phase Noise @ 25°C: -135dBc/Hz @ 1kHz typ

Environmental Parameters


- Storage Temperature Range: -40 to 85°C

Manufacturing Details

- Reflow Process
Preheating: 170°C±10°C for 1 to 2 minutes.
Maximum reflow: 250°C±10°C for 10secs.
- A DC-cut capacitor is not built in to the oscillator; a 1000pF DC-cut capacitor is therefore required in the output line.
- RoHS Terminations AuNi
- RoHS Reflow Temp Maximum reflow: 250°C±10°C for

Outline (mm)


- Pad Connections
1. Voltage Control
 2. GND
 3. Output
 4. +Vs

Solder Pad Layout

Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com

Compliance

- RoHS Status (2011/65/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

Packaging Details

- Pack Style: Reel Tape and reel in accordance with
Pack Size: 3,000 EIA-481-D
- *Alternative packing option available*

Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com