


## Accessories - FL 3-H - 1760310

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB terminal block, pitch: 2.5 mm, number of positions: 3, connection method: Slip-on connection, mounting: Wave soldering, color: green

### Why buy this product

- ✓ Space-saving, standardized slip-on connection allows worldwide use
- ✓ Two solder pins reduce the mechanical strain on the soldering spots
- ✓ The latching on the side enables various numbers of positions to be combined
- ✓ Well-known mounting principle allows worldwide use



### Key Commercial Data

Packing unit	1
GTIN	 4 017918 030858
GTIN	4017918030858
Custom tariff number	85369010

### Technical data

#### Dimensions

Pitch	2.5 mm
Constructional height	13.3 mm
Height [ h ]	18.3 mm
Pin dimensions	0,8 x 1,0 mm
Pin spacing	5.00 mm
Hole diameter	1.3 mm

#### General

Range of articles	FL
Nominal cross section	0 mm <sup>2</sup>
Insulating material	PA 6.6
Solder pin surface	Sn
Flammability rating according to UL 94	V2

## Accessories - FL 3-H - 1760310

### Technical data

#### General

Number of positions	3
---------------------	---

#### Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	V2

#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440490
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

#### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002498
ETIM 5.0	EC002637
ETIM 6.0	EC002637

#### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

### Approvals

#### Approvals

# Accessories - FL 3-H - 1760310

## Approvals

Approvals

CSA / EAC / cULus Recognized

Ex Approvals

## Approval details

CSA		<a href="http://www.csagroup.org/services/testing-and-certification/certified-product-listing/">http://www.csagroup.org/services/testing-and-certification/certified-product-listing/</a>	13631
Nominal current IN		10 A	
Nominal voltage UN		300 V	

EAC			B.01742
-----	--	--	---------

cULus Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	E60425-19770427
Nominal current IN		10 A	
Nominal voltage UN		300 V	

## Accessories

Accessories

Insulating sleeve

Insulating sleeve - PT/FS 6,3 - 0604707



Insulating sleeve, as touch protection, slide onto the conductor before for 6.3 slip-on sleeves

Labeled terminal marker

## Accessories - FL 3-H - 1760310

### Accessories

Marker pin Zack strip - BNB-ZB 5,LGS:FORTL.ZAHLEN - 1400201



Marker pin Zack strip, Strip, white, labeled, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 491 - 500, Mounting type: Plug in, for terminal block width: 5 mm, Lettering field: 4 x 4 mm

---

### Marker pen

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

---

### Terminal marking

Marker pin Zack strip - BN-ZB 5/WH:UNBEDRUCKT - 1400078



Marker pin Zack strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, Mounting type: Plug in, for terminal block width: 5 mm, Lettering field: 4 x 4 mm