This Dual Wall Heat Shrink Sleeving from Remington Industries is comprised of a thin-wall polyolefin tubing lined with a fine thermoplastic adhesive; it has a shrink ratio of 3 to 1, and it bonds with many plastics, rubbers, and metals. It is flexible, permanent, and water-resistant, which makes it perfect for protecting wire connections in any kind of automotive or marine applications that will have to withstand an outdoor environment. It is available in black or red to keep your project organized. Additionally, we offer this sleeving in several lengths (see below) for your convenience.

- Type: Dual Wall, Adhesive-Lined Heat Shrink Tubing
- Specifications Met: UL 224 & SAE-AMS-DTL-23053/4 Class 3
 Temperature Rating: -55°C (-67°F) to 110°C (230°F)

- Sleeving Material: Thin-Wall Polyolefin
- Shrink Ratio: 3:1
- Inner Diameter: 0.500" (12.70 mm)

- Colors Available: Black or Red
- Lengths Available: 1 ft, 2 ft, 4 ft, 8 ft

Heat Shrink Sleeving UL224 Data Sheet

Remington Industries is proud to offer our Custom Wire Services

Our exclusive inventory of in-stock wire and ability to procure wire of all kinds makes us the perfect partner for wire purchasing and custom wire services. We are proud to provide essential, high quality wire for engineering projects, educational science projects, coil winding, and electronics applications.

Some of our many wire services include the following:

- Wire Re-Packaging
- Bifilar & Trifilar Windings
- Wire Processing
- Coil Winding
- Wire Procurement Services

If you have any questions or need any information about our Wire Services, feel free to contact us! It only takes one call to get experienced assistance.

Contact us by phone: (815) 385-1987

Contact us by email: sales@remingtonindustries.com

PART NUMBER	SHRINK Ratio	INNER DIAMETER	COLORS AVAILABLE	
1/2UL224	3 to 1	½" (12.70 mm)	Black, Red	DATE ISS. REVISION BY Drawn by: AG 2/3/20 Drawing rev.: Remington Industries 3521 N. Chapel Hill Rd Johnsburg, IL 60051 USA remingtonindustries.com