

Title of Change:	LQFN 5X5 DRMOS NCP81295MNTXG, NCP81296MNTXG, NCP81292MNTXG Change in Bond Wire from 1.3mil Gold to 1.3mil Palladium-Coated Copper Wire		
Proposed First Ship date:	31 Aug 2021 or earlier if approved by customer		
Contact Information:	Contact your local ON Semiconductor Sales Office or <u>Wayne.Cheng@onsemi.com</u>		
PCN Samples Contact:	Contact your local ON Semiconductor Sales Office or < <u>PCN.samples@onsemi.com</u> >. Sample requests are to be submitted no later than 30 days from the date of first notification, Initial PCN or Final PCN, for this change. Samples delivery timing will be subject to request date, sample quantity and special customer packing/label requirements.		
Additional Reliability Data:	Contact your local ON Semiconductor Sales Office or MohdAzizi.Azman@onsemi.com		
Type of Notification:	This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change. ON Semiconductor will consider this change accepted, unless an inquiry is made in writing within 30 days of delivery of this notice. To do so, contact <u>PCN.Support@onsemi.com</u>		
Marking of Parts/ Traceability of Change:	The affected products will be identified with data code		
Change Category:	Assembly Change		
Change Sub-Category(s):	Material Change		
Sites Affected:			
ON Semiconductor Sites		External Foundry/Subcon Sites	
ON Semiconductor Seremban, Malaysia		None	

Description and Purpose:

LQFN 5X5 DRMOS NCP81295MNTXG, NCP81296MNTXG, NCP81292MNTXG Change in Bond Wire from 1.3mil Gold to 1.3mil Palladium-Coated Copper Wire.

Before Chang		Before Change Description	After Change Description
	Bond Wire	1.3mil Gold Wire	1.3mil Pd-Coated Copper Wire
		(Part # B50607A083)	(Part # N40363E016)

There is no product marking change as a result of this change.



Reliability Data Summary:

QV DEVICE NAME: <u>NCP81295MNTXG</u> RMS: <u>072277</u>

PACKAGE: QFN 5x5 32L

Specification	Condition	Interval	Results		
JESD22-A103	Ta= 150°C	1008 hrs	0/336		
JESD22-A104	Ta= -65°C to +150°C	1000 cyc	0/400		
JESD22-A110	130°C, 85% RH, 18.8psig, bias	192 hrs	0/392		
JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs	0/336		
J-STD-020 JESD-A113	MSL 3 @ 260 °C		All Pass		
	Compare for Delamination before and after PC		0/88		
JSTD002	Ta = 245C, 5 sec		0/60		
	Specification JESD22-A103 JESD22-A104 JESD22-A110 JESD22-A118 J-STD-020 JESD-A113	Specification Condition JESD22-A103 Ta= 150°C JESD22-A104 Ta= -65°C to +150°C JESD22-A110 130°C, 85% RH, 18.8psig, bias JESD22-A118 130°C, 85% RH, 18.8psig, unbiased J-STD-020 JESD-A113 MSL 3 @ 260 °C Compare for Delamination before and after PC Compare for Delamination before and after PC	Specification Condition Interval JESD22-A103 Ta= 150°C 1008 hrs JESD22-A104 Ta= -65°C to +150°C 1000 cyc JESD22-A110 130°C, 85% RH, 18.8psig, bias 192 hrs JESD22-A118 130°C, 85% RH, 18.8psig, unbiased 96 hrs J-STD-020 JESD-A113 MSL 3 @ 260 °C Compare for Delamination before and after PC		

Electrical Characteristics Summary:

Electrical characteristics are not impacted.

List of Affected Parts:

Note: Only the standard (off the shelf) part numbers are listed in the parts list. Any custom parts affected by this PCN are shown in the customer specific PCN addendum in the PCN email notification, or on the **PCN Customized Portal**.

Part Number	Qualification Vehicle		
NCP81292MNTXG	NCP81295MNTXG		
NCP81296MNTXG	NCP81295MNTXG		
NCP81295MNTXG	NCP81295MNTXG		



Appendix A: Changed Products

Product	Customer Part Number	Qualification Vehicle	New Part Number	Replacement Supplier
NCP81295MNTXG		NCP81295MNTXG	NA	