Title: Datasheet for TPS65911 Customer Contact: PCN Manager Dept: Quality Services Assembly Site Design Wafer Bump Site Assembly Process Data Sheet Wafer Bump Material Assembly Materials Part number change Wafer Bump Material Massembly Materials Part number change Wafer Fab Site Packing/Shipping/Labeling Test Site Wafer Sub Materials Change back for Manager Change Packing/Shipping/Labeling Test Site Change backs formuments incorporated is announcing an information only notification. Test Site Packet Change backs formuments incorporated is announcing an information only notification. Test Site Packet Change backs formumon back to a single row reflecting all orderable devices 2 Packet Packet Change	PC	N Number:	20180530002	PCN Date:	June 7,	2018		
Change Type: Design Wafer Bump Site Assembly Site Data Sheet Wafer Bump Material Assembly Process Data Sheet Wafer Fab Material Assembly Materials Part number change Wafer Fab Site Mechanical Specification Test Site Wafer Fab Materials Packing/Shipping/Labeling Test Site Wafer Fab Materials Description of Change: Wafer Fab Materials Wafer Fab Materials Peaking/Shipping/Labeling Test Site Wafer Fab Materials Description of Change: Texas Instruments Incorporated is announcing an information only notification. The product datasheet(s) is being updated as summarized below. The following change history provides further details. TPS65911 Changed Device Information table to a single row reflecting all orderable devices 2 Changed Device Information block Degram. 2 Changed the Volonize from 2 to 0 to 0 2 V to 2 5 V. 2 Changed The Volonize from 2 to 0 to 0 2 V to 2 5 V. 2 Changed The Volonize from 2 to 0 to 0 2 V to 2 5 V. 2 Changed the Volonize from 2 to 0 to 0 2 V to 2 5 V. 2 Changed the Volonize from 2 to 0 2 V to 2 5 V. 2 Changed the Vo	Title: Datasheet for		r TPS65911					
Assembly Site Design Wafer Bump Site Assembly Process Data Sheet Wafer Bump Material Assembly Materials Part number change Wafer Bump Process Mechanical Specification Test Site Wafer Fab Materials Packing/Shipping/Labeling Test Site Wafer Fab Materials Packing/Shipping/Labeling Test Process Wafer Fab Process Notification Details Description of Change: Texas Instruments Incorporated is announcing an information only notification. The product datasheet() is being updated as summarized below. The following change history provides further details. TPs66911 SWCS049R_JUNE 2010_REVISED MAY 2010 Changed be/ functional faile to a single row reflecting all orderable devices Changed be/ functional Biock Diagram Changed the Functional Biock Diagram Changed bevice Information table to a single row reflecting all orderable devices Conceded the SEL bits for 1 V to 2 to 1 to 2 to 2 to 2 to 2 to 2 to 2	Customer Contact:		PCN Manager		Dept:	Quality Services		
Assembly Process Data Sheet Wafer Bump Material Assembly Materials Part number change Wafer Fab Materials Mechanical Specification Test Stree Wafer Fab Materials Machanical Specification Test Stree Wafer Fab Materials Machanical Specification Test Stree Wafer Fab Materials Description of Change: Wafer Fab Materials Wafer Fab Materials Texas Instruments Incorporated is announcing an information only notification. The product datasheet(s) is being updated as summarized below. The following change history provides further details. TPs65911 Image from Revision Q (March 2016) to Revision R Page • Changed Device Information table to a single row reflecting all orderable devices 2 • Changed the Functional Block Diagram. 30 • Contraded the Color Diagram. 30 • Contraded the Color Diagram. 30 • Contraded the Color Diagram. 30 • Con	Cha	ange Type:						
Assembly Materials Part number change Wafer Bump Process Mechanical Specification Test Site Wafer Fab Materials Packing/Shipping/Labeling Test Process Wafer Fab Materials Description of Change: Wafer Fab Process Wafer Fab Materials Texas Instruments Incorporated is announcing an information only notification. The product datasheet(s) is being updated as summarized below. The product datasheet(s) is being updated as summarized below. The following change history provides further details. TPS65911 Change from Revision Q (March 2016) to Revision R Page Changed below Information table to a single row reflecting all orderable devices 2 Changed the functionable to a single row reflecting all orderable devices 2 2 Changed the functionable foot Diagram 30 4dded the Overwew section 30 Corrected two odge from 2.2 V to 2.5 V 30 30 4dded the Overwew section 30 Added the Applications, Implementation, and Layout section 30 30 30 30 Added specification of the OL 2.5 V options, Added the SEL bits for 0.5 V options, Added the SEL bits for 0.8 V options, Added tayout diagrams whitch show the routing around the device . <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
Mechanical Specification Test Site Wafer Fab Site Packing/Shipping/Labeling Test Process Wafer Fab Materials Description of Change: Test Process Test Site Texas Instruments Incorporated is announcing an information only notification. The following change history provides further details. Texas Instruments Incorporated is announcing an information only notification. The following change history provides further details. Texas Instruments Texas Instruments Incorporated is announcing an information only notification. The following change history provides further details. Texas Instruments Texas Instruments Texas Instruments Incorporated is announcing an information only notification. Texas Instruments Texas Instruments Texas Instruments Instruction and Biock Digram SwcSo49R -JUNE 2010-REVISED MAY 2015 Changed Device Information table to a single row reflecting all orderable devices 2 Changed Inte / Uncload a form 2.2 V to 2.5 V 2 Changed Inte / Uncload a form 2.2 V to 2.5 V 2 Added the Optication, implementation, and Layout description 2.2 V to 2.5 V 2 Changed Inte Application, implementation, and Layout description 2 Added the Optication, implementation, and Layout description 2								
□ Packing/Shipping/Labeling □ Test Process □ Wafer Fab Materials □ Wafer Fab Process □ Wafer Fab Process Description of Change: □ Wafer Fab Process Texas Instruments Incorporated is announcing an information only notification. The product datasheet(s) is being updated as summarized below. The product datasheet(s) is being updated as summarized below. Tess5911 WSTRUMENTS Swcso49R -JUAE 2010-REVISED MAY 2018 Changed Device Information table to a single row reflecting all orderable devices 2 • Changed the Aunotonal Block Diagram. 23 • Changed the VDCH's Bew rate from the Recommended Operating Conditions table 20 • Changed the VDCH's Bew rate from the Recommended Operating Conditions table 21 • Changed the VDCH's Bew rate from 100 mV20s to 5 mVijs for danty 26 • Changed the VDCH's Bew rate from 100 mV20s to 5 mVijs for danty 26 • Corrected Wo section of UO1 PLEG and LDO2_REG 37 • Corrected the SEL bits for 0 Volus volus escion 30 • Added specific tayout recommendations, and added layout diagrams which show the routing around the device . 129								
Wotification Details Wotification Details Texas Instruments Incorporated is announcing an information only notification. The product datasheet(s) is being updated as summarized below. The following change history provides further details. TPS65911 With the following change history provides further details. TPS65911 With the following change history provides further details. TPS65911 Changed the Functional Blook Diagram 2 Changed the Functional Blook Diagram 2 Changed the Functional Blook Diagram 2 Changed the Vince from 2 to 10 mV/20 to 5 mV/us for darity 20 Consected WO output voltage from 2.2 V to 2.5 V 20 Consected WO voltage from 2.2 V to 2.5 V 20 Consected mesclustor of LDO1 REG and LDO2, REG 20 Consected WO voltage from 2.2 V to 2.5 V 20 Consected mesclustor of LDO1 REG and LDO2, REG 20 Consected mesclustor of LDO1 REG and LDO2, REG 20 Consected WSEL bits for 0.8 V to 0.9 V polions. Added the SEL bits for 0.8 V to 0.9 V colspan <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td></td<>								
Notification Details Description of Change: Texas Instruments Incorporated is announcing an information only notification. The product datasheet(s) is being updated as summarized below. The following change history provides further details. TPS65911 The State of Change Device Information table to a single row reflecting all orderable devices 2 Changed the Functional Block Diagram. 20 Changed the Functional Block Diagram. 20 Changed the Functional Block Diagram. 20 Changed the Function 100 mV/20µs to 5 mV/µs for clarity 20 Added the ODC reflex set bits for 10 set on 20 to 25 v. 20 Changed to Punct Viol Set must be on 20 to 20 v. 20 <td colspane="" cot="" of="" td="" to="" val<="" value=""><td></td><td>Facking/Shipping/i</td><td></td><td>FIUCESS</td><td></td><td></td></td>	<td></td> <td>Facking/Shipping/i</td> <td></td> <td>FIUCESS</td> <td></td> <td></td>		Facking/Shipping/i		FIUCESS			
Description of Change: Texas Instruments Incorporated is announcing an information only notification. The product datasheet(s) is being updated as summarized below. The following change history provides further details. Texas Texas INSTRUMENTS SWC5048R_JUNE 2010 - REVISED MAY 2019 Changed Device Information table to a single row reflecting all orderable devices Changed Device Information table to a single row reflecting all orderable devices Changed the VDDCH severature from the Recommended Operating Conditions table Changed the VDDCH severature from the Recommended Operating Conditions table Changed the Overview section Added SEL options for V _{SUT} < 1V								
Texas Instruments Incorporated is announcing an information only notification. The product datasheet(s) is being updated as summarized below. The following change history provides further details. TPS65911 STRUMENTS SWC5049R-JUNE 2010-REVISED MAY 2018 Changes from Revision Q (March 2016) to Revision R Changed Device Information table to a single row reflecting all orderable devices Changed the <i>Functional Block Diagram</i> Deteked lead temperature from the <i>Recommended Operating Conditions</i> table Changed the <i>Functional Block Diagram</i> Deteked VID Output voltage from 2 V to 2.5 V Changed the <i>Functional Block Diagram</i> Deteked VID Output voltage from 2 V to 2.5 V Changed the <i>Functional Block Diagram</i> Deteked VID Output voltage from 2 V to 2.5 V Changed the State from 100 mV/20 to 5 mV/1 to for darity Corrected VID Output alter tom 2 V to 2.5 V Corrected the SEL bits for 1 V selection for LDO1 REG and LDO2 REG Corrected the SEL bits for 1 V selection for LDO1 REG and LDO2 REG Corrected the SEL bits for 1 V selection for LDO1 REG and LDO2 REG Corrected the SEL bits for 0.8 V to 9.4 Voltas Added the SEL bits for 0.9 V voltas Corrected the SEL bits for 0.9 V options. Device Family Change From: Change Tro: TPS65911 SWCS049Q SWCS049R These changes may be reviewed at the datasheet links provided. http://www.ti.com/product/TPS65911 Reason for Change: Coarceted the SEL bits a specification change announcement only. There are no changes to the actual device. Changes to product identification resulting from this PCN: No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. TPS6591102A22RCR TPS6591104A22RCR TPS6591104A	Des	scription of Chang						
The product datasheet(s) is being updated as summarized below. The following change history provides further details. TPS65911 Texas Changes from Revision Q (March 2016) to Revision R Page Changed Device Information table to a single row reflecting all orderable devices Changed Device Information table to a single row reflecting all orderable devices Changed the VDC/to sev rate Recommended Operating Conditions table Corrected VIO output voltage from 2.2 V to 2.5 V Corrected VIO output voltage from 100 mV/20 to 5 mV/1s for clarity Corrected VIO output voltage from 100 mV/20 to 5 mV/1s for clarity Corrected VIO voltage from 2.2 V to 2.5 V Corrected VIO voltage from 2.2 V to 2.5 V Corrected VIO voltage from 2.2 V to 2.5 V Corrected the SEL bits for 1 V section for DOI PREG and LDO2 REG Corrected the SEL bits for 1 V section for DOI PREG and LDO2 REG Corrected the SEL bits for 1 V section for DOI PREG and LDO2 REG Corrected the SEL bits for 1 V section for DOI PREG and LDO2 REG Corrected the SEL bits for 1 V section for LDOI PREG and LDO2 REG Corrected the SEL bits for 1 V section for LDOI PREG and LDO2 REG Corrected the SEL bits for 1 V section for LDOI PREG and LDO2 REG Corrected the SEL bits for 1 V section for LDOI PREG and LDO2 REG Corrected the SEL bits for 1 V section for LDOI PREG and LDO2 REG Corrected the SEL bits for 1 V section for LDOI PREG and LDO2 REG Corrected the SEL bits for 1 V section for LDOI PREG and LDO2 REG Corrected the SEL bits for 1 V section for LDOI PREG and LDO2 REG Corrected the Application, Implementation, and Layout section Corrected the SEL bits for 1 Section for LDOI PREG Corrected VEC PREG Corrected the Application, Implementation, and Layout section Corrected the SEL bits for 1 Section for LDOI PREG Corrected VEC PREG Corrected the Application, Implementation, and Layout section Corrected the Application for the datasheet links provided. Corrected the SEL bits for 1 Section for LDOI PREG Corrected VEC PREG Corrected VEC PREGESSII Contant vector Predet device characteristics.				ing an information of	only notifi	cation.		
TPS65911 Image: Note of the service of the ser			•	-				
EXAMPLE SWCSD49R - JUNE 2010 - REVISED MAY 2018 Changes from Revision Q (March 2016) to Revision R Page Changed Device Information table to a single row reflecting all orderable devices Changed the <i>Functional Block Diagram</i> Corrected VIO output voltage from 2.2 V to 2.5 V Changed the VDDCht siew rate from 100 mV/20µs to 5 mV/µs for darity Corrected VIO output voltage from 2.2 V to 2.5 V Corrected VIO output voltage from 2.2 V to 2.5 V Corrected the SEL bits for 1.9 V to 9.9 V options. Added the SEL bits for 0.95 V Corrected the SEL bits for 0.8 V to 9.9 V options. Added the SEL bits for 0.95 V Corrected the SEL bits for 0.8 V to 9.9 V options. Added the SEL bits for 0.95 V Added specific layout recommendations, and added layout diagrams which show the routing around the device. The datasheet number will be changing. Device Family Change From: Change To: TPS65911 SWCS049Q SWCS049R These changes may be reviewed at the datasheet links provided. http://www.ti.com/product/TPS659113 Reason for Change: To accurately reflect device characteristics. Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative): None. Product Affected: TPS6591102A22RCR TP	The	following change h	istory provides furthe	er details.		TROOPALA		
SWC3049K-JUNE 2010-REVISED MAY 2019 Changed Information table to a single row reflecting all orderable devices 2 Changed the Functional Block Diagram	1 IEXAS							
Changed Device Information table to a single row reflecting all orderable devices		INSTRUMENTS			SWCS	049R-JUNE 2010-REVISED MAY 2018		
 Changed the Functional Block Diagram Deleted lead temperature from the Recommended Operating Conditions table Corrected VIO output voltage from 2.2 V to 2.5 V Added the VDDCht silew rate from 100 mV/20 to 5 mV/us for darity Added SEL options for V_{Out} < 1 V Added the Voerview section Corrected VIO voltage from 2.2 V to 2.5 V Added the Overview section Corrected the SEL bits for 1 V selection for LDO1_REG and LDO2_REG Corrected the SEL bits for 1.0 V to 0.9 V options. Added the SEL bits for 0.95 V Corrected the SEL bits for 0.8 V to 0.9 V options. Added the SEL bits for 0.95 V Added the Applications, implementation, and Layout section Pevice Family Change From: Change To: TPS65911 SWCS049Q SWCS049R These changes may be reviewed at the datasheet links provided. http://www.ti.com/product/TPS65911 Reason for Change: To accurately reflect device characteristics. Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative): No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. Product Affected: TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS659114A2ZRCT TPS6591102A2ZRCR TPS6591104A2ZRCR TPS659113A2ZRC TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRC TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR	Cha	anges from Revision Q (I	March 2016) to Revision R	ł		Page		
 Changed the Functional Block Diagram Deleted lead temperature from the Recommended Operating Conditions table Corrected VIO output voltage from 2.2 V to 2.5 V Added the VDDCht silew rate from 100 mV/20 to 5 mV/us for darity Added SEL options for V_{Out} < 1 V Added the Voerview section Corrected VIO voltage from 2.2 V to 2.5 V Added the Overview section Corrected the SEL bits for 1 V selection for LDO1_REG and LDO2_REG Corrected the SEL bits for 1.0 V to 0.9 V options. Added the SEL bits for 0.95 V Corrected the SEL bits for 0.8 V to 0.9 V options. Added the SEL bits for 0.95 V Added the Applications, implementation, and Layout section Pevice Family Change From: Change To: TPS65911 SWCS049Q SWCS049R These changes may be reviewed at the datasheet links provided. http://www.ti.com/product/TPS65911 Reason for Change: To accurately reflect device characteristics. Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative): No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. Product Affected: TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS659114A2ZRCT TPS6591102A2ZRCR TPS6591104A2ZRCR TPS659113A2ZRC TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRC TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR		Changed Device Infor	mation table to a single row	reflecting all orderable de	evices			
 Corrected VIO output voltage from 2.2 V to 2.5 V Changed the VDDCttt slew rate from 100 mV/20µs to 5 mV/µs for darity Added SEL options for V_{0UT} < 1 V Added the <i>Overview</i> section Corrected VIO outgae from 2.2 V to 2.5 V Added the <i>Overview</i> section Corrected VIO outgae from 2.2 V to 2.5 V Corrected VIO outgae from 2.2 V to 2.5 V Corrected VIO outgae from 2.2 V to 2.5 V Corrected VIO outgae from 2.2 V to 2.5 V Corrected VIO outgae from 2.2 V to 2.5 V Corrected VIO outgae from 2.2 V to 2.5 V Corrected VIO outgae from 2.2 V to 2.5 V Corrected VIO outgae from 2.2 V to 2.5 V Corrected VIO outgae from 2.2 V to 2.5 V Corrected VIO outgae from 2.2 V to 2.5 V Corrected VIO outgae from 2.2 V to 2.5 V Added the <i>SEL</i> bits for 1.9 selection for LDO1_REG and LDO2_REG Corrected VIO outgae from 2.2 V to 2.5 V Added the <i>Applications, Implementation, and Layout</i> section Corrected VIO outgae from 2.2 V to 2.5 V Added the <i>Applications, Implementation, and Layout</i> section Change To: TPS65911 SWCS049Q SWCS049R These changes may be reviewed at the datasheet links provided. http://www.ti.com/product/TPS65911 Reason for Change: To accurately reflect device characteristics. Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative): No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. Changes to product identification resulting from this PCN: None. Product Affected: TPS6591102A22RCR TPS6591102A22RCR TPS6591102A22RCR TPS6591102A22RCR TPS6591102A22RCR TPS6591103A22R		 Changed the Function 	al Block Diagram	_		2		
 Changed the VDDCttt slew rate from 100 mV/20µs to 5 mV/µs for clarity Added SEL options for V_{0UT} < 1 V Added the Overview section Corrected VIO voltage from 2.2 V to 2.5 V Corrected the SEL bits for 1 V selection for LDO1. REG and LDO2. REG Corrected the SEL bits for 0.8 V to 0.9 V options. Added the SEL bits for 0.95 V Added the Applications, Implementation, and Layout section Added specific layout recommendations, and added layout diagrams which show the routing around the device. Added specific layout recommendations, and added layout diagrams which show the routing around the device. The datasheet number will be changing. Device Family Change From: Change To: TPS65911 SWCS049Q SWCS049R These changes may be reviewed at the datasheet links provided. http://www.ti.com/product/TPS65911 Reason for Change: To accurately reflect device characteristics. Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative): No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. Changes to product identification resulting from this PCN: None. Product Affected: TPS6591102A2ZRCR TPS6591102A2ZRCR TPS6591102A2ZRCR TPS6591102A2ZRCR TPS6591103A2ZRCR TPS6591103A2ZRCR TPS6591103A2ZRCR TPS6591104A2ZRCR TPS6591104A2ZRCR								
 Added the Overview section		 Changed the VDDCtrl 	slew rate from 100 mV/20µ	is to 5 mV/µs for clarity .				
 Corrected VIO voltage from 2.2 V to 2.5 V								
 Corrected the SEL Dits for 1 V selection for LDO1_REG and LDO2_REG		 Added the Overview's Corrected VIO voltage 	ection from 2.2 V to 2.5 V					
 Added the Applications, Implementation, and Layout section		 Corrected the SEL bits 	s for 1 V selection for LDO1	_REG and LDO2_REG .				
 Added specific layout recommendations, and added layout diagrams which show the routing around the device 129 The datasheet number will be changing. Device Family Change From: Change To: TPS65911 SWCS049Q SWCS049R These changes may be reviewed at the datasheet links provided. http://www.ti.com/product/TPS65911 Reason for Change: To accurately reflect device characteristics. Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative): No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. Changes to product identification resulting from this PCN: None. Product Affected: TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS659114A2ZRCT TPS6591102A2ZRCR TPS6591106A2ZRCR TPS659113A2ZRCR TPS659118A2ZRCR TPS6591103A2ZRCR TPS6591100A2ZRCR TPS659113A2ZRCR TPS659118A2ZRCR TPS6591104A2ZRCR TPS6591100A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS6591100A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS6591100AZZRC TPS659113A2ZRCR TPS6591104A2ZRCR TPS6591100AZZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS6591100AZZRCR TPS659113A2ZRCR 								
The datasheet number will be changing. Device Family Change From: Change To: TPS65911 SWCS049Q SWCS049R These changes may be reviewed at the datasheet links provided. http://www.ti.com/product/TPS65911 Reason for Change: To accurately reflect device characteristics. Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative): No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. Changes to product identification resulting from this PCN: None. Product Affected: TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS6591103A2ZRCR TPS6591109A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS6591104A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS6591104A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS6591104A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRC TPS659110A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR								
Device FamilyChange From:Change To:TPS65911SWCS049QSWCS049RThese changes may be reviewed at the datasheet links provided. http://www.ti.com/product/TPS65911SWCS049RReason for Change:To accurately reflect device characteristics.Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative):No anticipated impact. This is a specification change announcement only. There are no changes to the actual device.Changes to product identification resulting from this PCN:None.Product Affected:TPS6591102A2ZRCRTPS6591104EA2ZRCRTPS659112A2ZRCRTPS659114A2ZRCTTPS6591102A2ZRCRTPS6591106A2ZRCRTPS659113A2ZRCTPS659118A2ZRCRTPS6591103A2ZRCRTPS6591109A2ZRCRTPS659113A2ZRCTPS659113A2ZRCRTPS6591104A2ZRCRTPS659110A2ZRCRTPS659113A2ZRCRTPS659113A2ZRCTPS6591104A2ZRCRTPS659110A2ZRCRTPS659113A2ZRCRTPS659113A2ZRCR								
TPS65911SWCS049QSWCS049RThese changes may be reviewed at the datasheet links provided. http://www.ti.com/product/TPS65911SWCS049RReason for Change: To accurately reflect device characteristics.Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative): No anticipated impact. This is a specification change announcement only. There are no changes to the actual device.Changes to product identification resulting from this PCN: None.None.Product Affected:TPS6591102A2ZRCRTPS6591104EA2ZRCRTPS659112A2ZRCRTPS659114A2ZRCTTPS6591102A2ZRCRTPS6591106A2ZRCRTPS659113A2ZRCTPS659118A2ZRCRTPS6591103A2ZRCRTPS659110A2ZRCRTPS659113A2ZRCRTPS659113A2ZRCRTPS6591104A2ZRCRTPS659110A2ZRCRTPS659113A2ZRCRTPS659113A2ZRCRTPS6591104A2ZRCRTPS659110A2ZRCRTPS659113A2ZRCRTPS659113A2ZRCRTPS6591104A2ZRCRTPS659110A2ZRCRTPS659113A2ZRCRTPS659113A2ZRCR				Change From:	Ch	ange To:		
These changes may be reviewed at the datasheet links provided. http://www.ti.com/product/TPS65911 Reason for Change: To accurately reflect device characteristics. Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative): No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. Changes to product identification resulting from this PCN: None. Product Affected: TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS6591104A2ZRCR TPS6591102A2ZRCR TPS6591106A2ZRCR TPS659113A2ZRCR TPS659113A2ZRCR TPS6591103A2ZRCR TPS6591109A2ZRCR TPS659113A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRC TPS659113A2ZRC	,							
http://www.ti.com/product/TPS65911Reason for Change:To accurately reflect device characteristics.Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative):No anticipated impact. This is a specification change announcement only. There are no changes to the actual device.Changes to product identification resulting from this PCN:None.Product Affected:TPS6591102A22RCRTPS6591104EA2ZRCRTPS659112A2ZRCRTPS659114A2ZRCTTPS6591102A2ZRCRTPS6591106A2ZRCRTPS659113A2ZRCTPS659118A2ZRCRTPS6591103A2ZRCRTPS6591109A2ZRCRTPS659113A2ZRCRTPS659118A2ZRCTTPS6591104A2ZRCTPS659110A2ZRCRTPS659113A2ZRCRTPS659118A2ZRCTTPS6591104A2ZRCTPS659110A2ZRCRTPS659113A2ZRCTPS659118A2ZRCT	IPS65911 SWC5049Q SWC5049K							
Reason for Change:To accurately reflect device characteristics.Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative):No anticipated impact. This is a specification change announcement only. There are no changes to the actual device.Changes to product identification resulting from this PCN:None.Product Affected:TPS6591102A2ZRCRTPS6591104EA2ZRCRTPS659112A2ZRCRTPS659114A2ZRCTTPS6591102A2ZRCRTPS6591106A2ZRCRTPS659113A2ZRCTPS659118A2ZRCRTPS6591103A2ZRCRTPS6591109A2ZRCRTPS659113A2ZRCRTPS659118A2ZRCTTPS6591104A2ZRCTPS659110A2ZRCRTPS659113A2ZRCRTPS659118A2ZRCTTPS6591104A2ZRCRTPS659110A2ZRCRTPS659113A2ZRCRTPS659118A2ZRCTTPS6591104A2ZRCRTPS659110A2ZRCRTPS659113A2ZRCRTPS659113A2ZRC	These changes may be reviewed at the datasheet links provided.							
To accurately reflect device characteristics. Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative): No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. Changes to product identification resulting from this PCN: None. Product Affected: TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS659114A2ZRCT TPS6591102A2ZRCR TPS6591106A2ZRCR TPS659113A2ZRC TPS659118A2ZRCR TPS6591103A2ZRCR TPS6591109A2ZRCR TPS6591133A2ZRC TPS659118A2ZRCT TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC	http://www.ti.com/product/TPS65911							
To accurately reflect device characteristics. Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative): No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. Changes to product identification resulting from this PCN: None. Product Affected: TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS659114A2ZRCT TPS6591102A2ZRCR TPS6591106A2ZRCR TPS659113A2ZRC TPS659118A2ZRCR TPS6591103A2ZRCR TPS6591109A2ZRCR TPS6591133A2ZRC TPS659118A2ZRCT TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC	Rea	ason for Change:						
No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. Changes to product identification resulting from this PCN: None. Product Affected: TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS659114A2ZRCT TPS6591102A2ZRCR TPS6591106A2ZRCR TPS6591133A2ZRC TPS659118A2ZRCR TPS6591103A2ZRCR TPS6591109A2ZRCR TPS6591133A2ZRCR TPS659118A2ZRCT TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC								
No anticipated impact. This is a specification change announcement only. There are no changes to the actual device. Changes to product identification resulting from this PCN: None. Product Affected: TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS659114A2ZRCT TPS6591102A2ZRCR TPS6591106A2ZRCR TPS6591133A2ZRC TPS659118A2ZRCR TPS6591103A2ZRCR TPS6591109A2ZRCR TPS6591133A2ZRCR TPS659118A2ZRCT TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC								
Changes to product identification resulting from this PCN:None.Product Affected:TPS6591102A2ZRCRTPS6591104EA2ZRCRTPS659112A2ZRCRTPS659114A2ZRCTTPS6591102AA2ZRCRTPS6591106A2ZRCRTPS6591133A2ZRCTPS659118A2ZRCRTPS6591103A2ZRCRTPS6591109A2ZRCRTPS6591133A2ZRCRTPS659118A2ZRCTTPS6591104A2ZRCTPS659110A2ZRCTPS659113A2ZRCRTPS659118A2ZRCTTPS6591104A2ZRCTPS659110A2ZRCTPS659113A2ZRCTPS659113A2ZRC								
None. Product Affected: TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS659114A2ZRCT TPS6591102AA2ZRCR TPS6591106A2ZRCR TPS6591133A2ZRC TPS659118A2ZRCR TPS6591103A2ZRCR TPS6591109A2ZRCR TPS6591133A2ZRCR TPS659118A2ZRCR TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR TPS659118A2ZRCT TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC TPS6591104A2ZRC TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR								
Product Affected: TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS659114A2ZRCT TPS6591102AA2ZRCR TPS6591106A2ZRCR TPS6591133A2ZRC TPS659118A2ZRCR TPS6591103A2ZRCR TPS6591109A2ZRCR TPS6591133A2ZRCR TPS659118A2ZRCR TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR TPS659118A2ZRCT TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC TPS6591104A2ZRC TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR Image: TPS659110A2ZRCR	Changes to product identification resulting from this PCN:							
TPS6591102A2ZRCR TPS6591104EA2ZRCR TPS659112A2ZRCR TPS659114A2ZRCT TPS6591102AA2ZRCR TPS6591106A2ZRCR TPS6591133A2ZRC TPS659118A2ZRCR TPS6591103A2ZRCR TPS6591109A2ZRCR TPS6591133A2ZRCR TPS659118A2ZRCR TPS6591104A2ZRCR TPS6591109A2ZRCR TPS659113A2ZRCR TPS659118A2ZRCT TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC TPS6591104A2ZRC TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR	None.							
TPS6591102AA2ZRCR TPS6591106A2ZRCR TPS6591133A2ZRC TPS659118A2ZRCR TPS6591103A2ZRCR TPS6591109A2ZRCR TPS6591133A2ZRCR TPS659118A2ZRCT TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC TPS6591104A2ZRC TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRC TPS6591104A2ZRC	Product Affected:							
TPS6591103A2ZRCR TPS6591109A2ZRCR TPS6591133A2ZRCR TPS659118A2ZRCT TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC TPS6591104A2ZRC TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR	TP	S6591102A2ZRCR	TPS6591104EA2Z	RCR TPS659112A	2ZRCR	TPS659114A2ZRCT		
TPS6591103A2ZRCR TPS6591109A2ZRCR TPS6591133A2ZRCR TPS659118A2ZRCT TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC TPS6591104A2ZRC TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR TPS6591104A2ZRCR	TP	S6591102AA2ZRCR	TPS6591106A2ZR	CR TPS6591133	A2ZRC	TPS659118A2ZRCR		
TPS6591104A2ZRC TPS659110A2ZRC TPS659113A2ZRC TPS6591104A2ZRCR TPS659110A2ZRCR TPS659113A2ZRCR	TP	S6591103A2ZRCR	TPS6591109A2ZR					
	TP	S6591104A2ZRC			2ZRC			
TPS6591104DA2ZRC TPS659112A2ZRC TPS659114A2ZRCR	ΤР	S6591104A2ZRCR	TPS659110A2ZRC	CR TPS659113A	2ZRCR			
	TP	S6591104DA2ZRC	TPS659112A2ZRC	C TPS659114A	2ZRCR			

For questions regarding this notice, e-mails can be sent to the regional contacts shown below or your local Field Sales Representative.

Location	E-Mail
USA	PCNAmericasContact@list.ti.com
Europe	PCNEuropeContact@list.ti.com
Asia Pacific	PCNAsiaContact@list.ti.com
Japan	PCNJapanContact@list.ti.com