Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions

 $\label{eq:max-Eyth-Straße} \begin{array}{l} \text{Max-Eyth-Straße 1} \cdot \text{74638 Waldenburg} \cdot \text{Germany} \\ \text{Tel.} + 49 (0) \, 79 \, 42 \, 945 \cdot 0 \cdot \text{Fax} + 49 (0) \, 79 \, 42 \, 945 \cdot 400 \\ \text{eiSos@we-online.de} \cdot \text{www.we-online.de} \end{array}$



Product / Process Change Notification (PCN) ☐ Major change ☐ Minor change		
PCN #:	PCN_IndGFH_20220118	Change Category:
Affected Series:	WE-GFH; 7447669xxx	☐ Equipment / Location
Allected Selles.	WE-GITI, 7447009XXX	⊠ General Data
DON D	D 1 04 0004	☐ Material
PCN Date:	December 21, 2021	☐ Process
Effective Date:	January 18, 2022	☐ Product Design☐ Shipping / Packaging
		☐ Supplier
		☐ Software
Contact:	Product Management	Data Sheet Change:
Phone:	+49 (0) 7942 - 945 5001	⊠ Yes □ No
Fax:	+49 (0) 7942 - 945 5179	Attachment:
E-Mail:	pcn.eisos@we-online.com	□ Yes ⊠ No
DESCRIPTION AND PURPOSE OF CHANGE:		
Because of a database mismatch, Würth Elektronik will correct the packaging unit in the data sheet.		
This is a datasheet correction only. There will be no change in form, fit, function, quality or reliability of the		
product.		
DETAIL OF CHANGE:		
The corrected packaging specs are marked with red before and green after change.		
packaging is reffered to the in	nternational standard IEC 60286-3:2013 W T T1 T2 K0 P0 P1 P2 D0 D1	E1 E2 F Tape Type 2a VPE / packaging unit
tolerance typ. typ. value 3,70 4,90	+0.3/-0.1 max. max. typ. typ. ±0.1 ±0.1 ±0.05 +0.1/-0.0 min.	±0.1 min. ±0.05 pcs. 1,75 10,25 5,50 Polystyrene 2000
packaging is refrered to the in	nternational standard IEC 60286-3:2013 W	E1 E2 F Tape Type 2a VPE / packaging unit
tolerance typ. typ. value 3,70 4,90	+0.3/-0.1 max. max. typ. typ. ±0.1 ±0.1 ±0.05 +0.1/-0.0 min. 12,00 0,60 0,10 4,20 3,50 4,00 8,00 2,00 1,50 1,50	±0.1 min. ±0.05 pcs. 1,75 10,25 5,50 Polystyrene 500
RELIABILITY / QUALIFICATION SUMMARY:		
There will be no change of the product, therefore no additional reliability or qualification testing will be		
performed.		