

Press Release Quick Tips

New long-body LED indicator fits thick panels, Prominent bezel style for increased visibility - IP67 rated

Distribution Date: November 2019 **Product Name: CDLB Series**

Product Description: Ø0.236" (6.0mm) Prominent LED Indicator, Long Body, IP67 sealed and Vandal Resistant

Key Markets/Applications:

Main Power Indication

Machine Tools

Civil Engineering Vehicles

Maritime, Oil and Gas Industry

Automation and Control

· Status indication

Professional Electrical Appliance

Instrumentation

Aircraft/Military Instrumentation

Key Benefits

Indicator

Fits panel thickness up to .256" (6.5mm)

Panel Hole Diameter

Ø 0.236" (6.0mm)

Terminal

6" Wire Leads or Bi-pins

Colors

Red, Yellow, Green, Blue, White

Voltage

5V to 48VDC; 120VAC

IP76 rated (wire leads) Sealed against moisture and dust

Compliance

RoHS and REACH

Product Specifications

- For panel hole diameter: 0.236" (6.0mm)
- Prominent bezel style LED indicator for increased visibility (3mm LED T-1)
- Long-body indicator (longer threads) which fit thicker panels up to .256" (6.5mm)
- Available in nickel-plated brass housing
- Available with ultra bright daylight viewing LEDs.
- · Designed for the extreme, harsh and outdoor environment
- Sealed against moisture and dust (IP67)
- Optional resistor for 5V-28VDC and 120VAC
- Offered with 6" 24 AWG wire leads or bi-pins
- · Available in five single illumination colors: red, green, yellow, blue, and white
- Viewing angle: 25°-60° (depending on model)
- Mounting hardware provided: lock washer, hex nut and gasket seal
- Thread size: M6*0.75mm
- · Resistant to vandal, shock and vibration
- Life Expectancy: 50,000 Average
- RoHS and REACH Compliant

For additional information about VCC, please visit vcclite.com







