

GENERAL SPECIFICATIONS:

RATING: 10A / 125V AC

CABLE TYPE / SIZE: SPT-2. # 2 x 18 AWG **TEMPERATURE RATING:** 60° C MINIMUM

CONDUCTOR COLORS: PANTONE WARM GRAY 4C

1880 ± 50 mm OVERALL LENGTH (L): CABLE OUTER DIAMETER: $3.5 \times 7.0 + 0.2 \text{ mm}$

END 'A' PLUG; **NEMA 1-15P POLARIZED** END 'B' SEE TERMINATION TABLE

APPROVALS PLUG: UL, CSA OR cUL APPROVALS CABLE: UL, CSA OR cUL

ble UL,CSA or EN Standards for proper

installation instruction.

PACKING:

BULK PACK

NOTES:

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



DATE:

09/15/18

SCALE: NONE



REV

Α



REVISION

APPROVED

09/15/18

DESCRIPTION

INITIAL RELEASE

2. CABLE AND MOLDED PLUG ARE MATCHED GRAY COLOR.

PART NO:

451P1116F00BB1(R)

CONDUCTOR TERMINATION TABLE:

out prior notice

Wire	Color	ROJ <u>+</u> 5 mm	RIJ <u>+</u> 1mm	Terminal
NEUTRAL	GRAY	25	10	STRIP
LINE	GRAY	25	10	STRIP

approval from the CEO of Globtek Inc.

PROPRIETARY INFORMATION:

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR

USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY

RELEASED By N.Frost at 8:11 am, Sep 18, 2018

NOTES

REV.

Α

SHEET 1/1

DASH REV. DESCRIPTION PART NO TABULATION BLOCK TOLERANCES: REV. ANGULAR DECIMALS GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647 $xx + /_{-} 0.1$ Tel. 201-784-1000 Fax 201.784.0111 SHEET www.globtek.com .xxx +/- .005 MILLIMETERS ANGULAR DATE: DWG TITLE: NORTH AMERICAN NON-DETACHABLE CORDSET INIT.BY: BS .xx +/- 0.3 Globtek product are not authorized for use as Globtek Inc. will not be liable for the 09/15/18 xxx +/= 013 mission critical components in life support, hazsafety and performance of these power DATE: FSCN No.: SIZE Contents of this document ardous environment, nuclear or product if unauthorized access and repair DRAWN: NF G, CC, YL are subject to change withaircraft applications without prior written occurs. End user should consult the applica-09/15/18

APRVD:BS