, PCB terminals, insulated, 2-pole, Audio Plug/Sockets, 6.3 mm



See below:

Approvals and Compliances

Description

- PCB : Screw-on mounting, rear-side
- Audio entrances and exits
- Data and Signal transfer
- Audio Plug: 2-pole , insulated , straight

References

Alternative: Housing shielded 4833.2220

Weblinks

pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product

Technical Data

Diameter	6.3 mm	
Number of Poles	2-pole	
Ratings DC	1 A / 30 VDC	
Ratings AC	1 A / 30 VAC	
Dielectric Strength	500 VDC	
Insulation Resistance	> 50 MΩ @ 500 VDC	

Allowable Operation Tempe-	-20°C to 70°C	
rature		
Terminal	PCB terminals tin-plated	
Mounting	Screw-on mounting	
	wall thickness max. 3.6mm	
Housing	insulated	
Style	straight	
Lifetime	5000 Insertions	

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals


SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Compliances


The product complies with following Guide Lines

Identification	Details	Initiator	Description
ROHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
50	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimensions [mm]



Diagrams



All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Audio Plug/Sockets	6.3	2-pole	PCB terminals	4833.2230

A vailability for all products can be searched real-time: https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit 100 Pcs

Mating Inlets/Plugs

Category / Description

Audio Plug/Sockets Overview complete



, solder terminal, screened, 2-pole, Audio Plug/Sockets, 6.3 mm	4833.1200
, solder terminal, insulated, 2-pole, Audio Plug/Sockets, 6.3 mm	4833.1210
, solder terminal, insulated, 2-pole, Audio Plug/Sockets, 6.3 mm	4833.1220

product selected for their own applications.

information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each