


| ITEM NO. | PART NUMBER | DESCRIPTION  | QTY. | COMPONENT NOTES |
|----------|-------------|--|------|-----------------|
| 1        | 50-00129    | Connector, dc plug, 5.5x2.5xL18.5 mm, molding style, spring contacts | 2    |                 |
| 2        | 30-00338    | Wire, 1C TS, 20 AWG, UL1185, 300V, 80C, 2.95 mm, shielded, VW-1, PVC | 1    |                 |
| 3        | 24-00357    | Overmold, dc plug, 5.5 mm  | 2    | PVC, black      |



**Notes:**  
Functionally equivalent components may be substituted  
Cable rated for 48 V, 7.0 A

| Wiring Diagram |            |          |
|----------------|------------|----------|
| 50-00129       | wire color | 50-00129 |
| center         | white      | center   |
| sleeve         | shield     | sleeve   |

|           |           |                 |  |  |  |
|-----------|-----------|-----------------|--|--|--|
| Revision: | Date:     | Description:    | Prepared:  | Notes:<br>RoHS compliant<br>Function test: no open, no short circuit, no intermittent          | <h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118<br/>fax 1.541.323.4202 web tensility.com</p> |
| A         | 4/19/2021 | Initial release | Verified:  |  |  |
|           |           |                 | Dimensions are in millimeters.<br>Tolerances:<br>X: ± 0.5 mm<br>X.X: ± 0.3 mm<br>X.XX: ± 0.05 mm | Description:<br>Cable, 1830 mm, 5.5x2.5x9.5 mm 50-00129 dc plug to same, 20 AWG, 30-00338 wire | Size:<br>A   |
|           |           |                 |  |  | Part number:<br>10-03923   |
|           |           |                 |  |  | Scale: 1:1   |
|           |           |                 |  |  | Sheet 1 of 1   |

5

4

3

2

1