

ECBT2.E224053 - Connectors for Use in Data, Signal, Control and Power Applications - Component

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Connectors for Use in Data, Signal, Control and Power Applications - Component

ADAM TECH

909 RAHWAY AVE
UNION, NJ 07083 United States

E224053

Marking: Company name and model designation.

Note: For additional marking information, refer to the [Guide Information Page](#).

Connector, Model(s): CDR-05-TR-SMT, CDR-08-TS, DMX-02-S-P-S-V0, DMX-02-S-P-V0, DMX-03-S-P-S-V0, DMX-04-S-P-S-V0, DMX-06-A-V-T-A, DMX-08-S-P-S-V0, DMX-09-S-SQ-V0, DMX-10-S-P-V0, DMX-14-S-P-V0, DMX-14-V0, DMX-18-S-P-V0, DMX-F-05-R/A-E-V0

Connectors, Model(s): 2PH, ADP f/b numerical digits, may be f/b SR, BB, BH f/b 01 thru 41, f/b 1, 2, 3, 4 or 5, BS f/b 1 thru 6, f/b 1 or 2, CDH f/b 02 thru 16, CDN f/b 02 thru 16, CDR f/b 02 thru 16, f/b GS, GR, TS or TR, DD f/b H, F, S or R, f/b 02, 03 or 04, DP or DS f/b 003 thru 008, HFH, HSH, LH, LHX-02-TS-V0, LHX-04-TS-V0, MDP or MDS f/b 003 thru 009, MMI Followed by alpha numerical digits., MPCl f/b 124, f/b 1, 2 or 3 f/b SMT, MTE f/b 02 thru 40, PHX-06-T-.125/.455, PHX-06-T-.125/.455-HT, RF, SC f/b R, S, TD or CC.

Connectors, Model(s): 08, 1, 125, 15, 2 or 25, f/b SH or SHD f/b dashed Alpha numeric digits, f/b 01 thru 80, maybe f/b dashed alpha numerical digits, maybe f/b SMT, PP, T/R or V0

Connectors, Model(s): 08, 1, 125, 15, 2, or 25 f/b CH or CHD f/b dashed Alpha numeric digits, f/b 01 thru 80, maybe f/b by dashed alpha numerical digits.

Connectors, Model(s): 2BHR Followed by dashed alpha numerical digits.

Connectors, Model(s): 2BHR f/b 08, 10, 14, 16, 20, 24, 26, 30, 34, 40, 44, 50, 60 or 64, f/b V or H, f/b U, T or SG, f/b A, B or SMT, may be f/b 30, GY or HT

Connectors, Model(s): 2BHRE Followed by dashed alpha numerical digits.

Connectors, Model(s): 2FCS Followed by up to 3 alpha digits, Followed by dashed alpha numerical digits.

Connectors, Model(s): 2FCS f/b 06, 08, 10, 12, 14, 16, 18, 20, 22, 24, 26, 34, 36, 40, 44, 50, 60 or 68, may be f/b 30 or PB

Connectors, Model(s): 2FDP Followed by dashed alpha numerical digits.

Connectors, Model(s): 2FSR Followed by up to 3 alpha digits, Followed by dashed alpha numerical digits.

Connectors, Model(s): 2FTR Followed by dashed alpha numerical digits.

Connectors. Model(s): 2FTR f/b 08, 10, 12, 14, 16, 20, 22, 24, 26, 30, 34, 40, 44, 50 or 68, f/b SG, may be f/b 30 or PB

Connectors, Model(s): 2MBHR Followed by dashed alpha numerical digits.

Connectors, Model(s): 2MHR Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH1 Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH1H Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH1R Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH1RA Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH1RB Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH1RW Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH1W Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH1Y Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH2 Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH2H Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH2R Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH2RA Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH2RB Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH2RW Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH2W Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH2Y Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH3 Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH3RA Followed by dashed alpha numerical digits.

Connectors, Model(s): 2PH4 Followed by dashed alpha numerical digits.

Connectors, Model(s): 2RS Followed by dashed alpha numerical digits.

Connectors, Model(s): 2RS1K Followed by dashed alpha numerical digits.

Connectors, Model(s): 2RS2K Followed by dashed alpha numerical digits.

Connectors, Model(s): 396 Followed by RS or PH, followed by dashed alpha numerical digits.

Connectors, Model(s): ADC f/b 01 thru 42, f/b 1 thru 8, may be f/b RT, HT, N or ADCH

Connectors, Model(s): ADT f/b alphanumeric digits, maybe f/b letter A w/ 5 numerical digits

Connectors, Model(s): ASJ f/b 1, 5, 6, 7, 12, 15, 18, 37, 38, 40, 41, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112 or 113, f/b contact forms, may be f/b E. M. HT or TR

Connectors, Model(s): BHR Followed by dashed alpha numerical digits.

Connectors, Model(s): BHR f/b 08, 10, 14, 16, 20, 24, 26, 30, 34, 40, 44, 50, 60 or 64, f/b V or H, f/b U, T or SG, f/b A, B or SMT, may be f/b LL, SL, 30, GY or HT

Connectors, Model(s): BHRE Followed by dashed alpha numerical digits.

Connectors, Model(s): CE may be f/b RA, f/b 4, 6, 8, 12, 16, 20, 24, 26, 28, 30, 32, 34, 36, 38, 40, 44, 48, 50, 60, 62, 64, 70, 72, 80, 86, 98, 100, 108 or 120, f/b U, may be f/b 30, HT or BR

Connectors, Model(s): CE Followed by dashed alpha numerical digits.

Connectors, Model(s): CERA Followed by dashed alpha numerical digits.

Connectors, Model(s): CF f/b A, R, S or 1R, f/b 50 or 68, f/b A, may be f/b SG, f/b SM or SMT, may be f/b A, B, C or D, may be f/b 1 or 2

Connectors, Model(s): D f/b 50 f/b PF or SF, f/b M or P, f/b 1 or 2

Connectors, Model(s): D f/b 50, f/b PF or SF f/b M or P, f/b 1 or 2

Connectors, Model(s): D f/b 50, f/b PH or SH f/b C, G or F, f/b 1, 2 or 3, f/b A, B AM, BM, C, D or E, may be f/b 15, 30, BK or HT

Connectors, Model(s): D f/b D50 f/b HD, f/b PY, PB, PN or AL, f/b SS or TS

Connectors, Model(s): D f/b D50 f/b PR or SR f/b SL or JS may be f/b 15 or 30

Connectors, Model(s): D f/b D50, f/b PD or SD f/b SL or JS, may be f/b 15, 30, EMI or WT

Connectors, Model(s): D f/b D50, f/b PT, ST, PE or SE f/b 1 or 2, f/b SL, JS, BL, R or JSL, may be f/b 15, 30, EMI or HT

Connectors, Model(s): D f/b E09, A15, B25, C37 or D50 f/b PT, ST, PE or SE f/b 1 or 2, f/b SL, JS, BL, R or JSL, f/b SL, JS, BL, R or JSL, may be f/b 15, 30, EMI, HT, or NS f/b HT

Connectors, Model(s): D f/b E09, A15, B25, or C37, f/b PR or SR, f/b SL or JS may be f/b 15 or 30

Connectors, Model(s): D f/b E09, A15, B25, or C37 f/b PL or SL, f/b 1, 2, 3 or 4, f/b 3, 4, 5 or 6, may be f/b 15, 30, EMI, LPJ, F, HT, R or PF

Connectors, Model(s): D f/b E09, A15, B25, or C37, f/b HD f/b PY, PB, PN or AL, f/b SS or TS

Connectors, Model(s): D f/b E09, A15, B25, or C37, f/b PA or SA f/b M1, M2, M1-R3, M2-R-BI, M2-JS, M2-BI or M2-BI-JS, may be f/b 15, 30, PF or HT

Connectors, Model(s): D f/b E09, A15, B25, or C37, f/b PD or SD f/b SL or JS, may be f/b 15, 30, EMI or WT

Connectors, Model(s): D f/b E09, A15, B25, or C37, f/b PF or SF f/b M or P, f/b 1 or 2

Connectors, Model(s): D f/b E09, A15, B25, or C37, f/b PH or SH f/b C, G or F, f/b 1, 2 or 3, f/b A, B AM, BM, C, D or E, may be f/b 15, 30, BK or HT

Connectors, Model(s): D f/b E09, A15, B25, or C37, f/b PL or SL D f/b E09, A15, B25, or C37, f/b PL or SL

Connectors, Model(s): D f/b E09, A15, B25, or C37, f/b PQ or SQ f/b SA, SB, SC, SD, F or R, f/b 3, 4, 5 or 6, may be f/b 15, 30, EMI, LPJ, F, HT or R

Connectors, Model(s): D f/b E09, A15, B25, or C37, f/b PR or SR f/b SL or JS may be f/b 15 or 30

Connectors, Model(s): D f/b E09, A15, B25, or C37, f/b PT, ST, PE or SE f/b 1 or 2, f/b SL, JS, BL, R or JSL, may be f/b 15, 30, EMI, HT, or NS

Connectors, Model(s): D1PH Followed by dashed alpha numerical digits

Connectors, Model(s): D2PH Followed by dashed alpha numerical digits.

Connectors, Model(s): D2Ph1 Followed by dashed alpha numerical digits.

Connectors, Model(s): D2PH1R Followed by dashed alpha numerical digits.

Connectors, Model(s): D2PH2 Followed by dashed alpha numerical digits

Connectors, Model(s): D2PH2R Followed by dashed alpha numerical digits.

Connectors, Model(s): DFW may be f/b –B or –C, f/b 02, 03 or 04

Connectors, Model(s): DPH Followed by dashed alpha numerical digits.

Connectors, Model(s): DIMM, SOD or DDR f/b 144, 168, 184, 200 or 240, f/b V, R or S, f/b 1, 2, 3, 4 or 5, may be f/b 30, HT, YW or PU

Connectors, Model(s): DIN f/b 08, 16, 24, 32, 64 or 96 f/b M or F, f/b S or R, f/b S22, S32, L22, L32, L33 or L44, f/b A or B, f/b 1 or 2, may be f/b PF, HT, BL, CI or CII

Connectors, Model(s): DIN f/b 120 f/b M or F, f/b S or R, f/b S22, S32, L22, L32, L33 or L44, f/b A or B, f/b 1 or 2, may be f/b PF, HT, BL, CI or CII

Connectors, Model(s): DJ f/b N or P, f /b 3P thru 13P, f/b A or B

Connectors, Model(s): DM f/b one alphanumeric digit, f/b alphanumeric digits, may be f/b SMT, may be f/b B or R, may be f/b P, may be f/b V0

Connectors, Model(s): DPA Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DPD Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DPD f/b 09, 15, 25, 37, 50 or X/X, f/b 10, 11, 01, or 00, f/b A, B or C, f/b 1, 2 or 3, may be f/b 15, 30, JS, R or F

Connectors, Model(s): DPE Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DPF Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DPH Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DPH f/b 1, 2 or 3, f/b 1 through 40, f/b U, T or SG, may be f/b C Dim, D Dim, E Dim or SMT

Connectors, Model(s): DPL Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DPN Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DPQ Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DPR Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DPS Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DPT Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DSA Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DSC Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DSD Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DSE Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DSF Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DSH Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DSL Followed by dashed alpha numerical digits.

Connectors, Model(s): DSN Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DSR Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DSS Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DST Followed by 09, 15, 25, 37, or 50 Followed by dashed alpha numerical digits.

Connectors, Model(s): DVI /b SL , ST, PL or PT f/b 24, f/b 1 or 2, may be f/b BK, JS or HT

Connectors, Model(s): EB f/b A thru V, V2 or W, f/b 02 thru 24, f/b A, B, C, E, F, G, H, J or K, may be f/b C or E

Connectors, Model(s): FCE Followed by up to 3 alpha digits, Followed by dashed alpha numerical digits.

Connectors, Model(s): FCE may be f/b K, f/b 10, 14, 16, 20, 26, 34,40 or 50, f/b SG, may be f/b 30, GY or E

Connectors, Model(s): FCP Followed by up to 3 alpha digits, Followed by dashed alpha numerical digits.

Connectors, Model(s): FCS Followed by up to 3 alpha digits, Followed by dashed alpha numerical digits.

Connectors, Model(s): FCS may be f/b D2 or K, f/b 06, 08, 10, 12, 14, 16, 20, 24, 26, 30, 34, 40,44 or 50, f/b SG, may be f/b 30, GY or N

Connectors, Model(s): FCS-D2 Followed by up to 3 alpha digits, Followed by dashed alpha numerical digits.

Connectors, Model(s): FDP Followed by dashed alpha numerical digits.

Connectors, Model(s): FDP f/b 08, 10, 14, 16, 18, 20, 24, 28, 32 or 40, f/b T or G, may be f/b 30, GY or RT

Connectors, Model(s): FSR Followed by up to 3 alpha digits, Followed by dashed alpha numerical digits.

Connectors, Model(s): FTR Followed by dashed alpha numerical digits.

Connectors, Model(s): FTR f/b 08, 10, 14, 16, 20, 24, 26, 28, 30, 34, 40, 50 or 60, 64, f/b T or G, may be f/b 30, GY or RT

Connectors, Model(s): HBHR f/b 06, 08, 10, 12, 14, 16, 20, 24, 26, 30, 34, 40, 44, 50, 56, 60 or 64, f/b V or H, f/b G, SG or T, may be f/b 30, SMT or HT

Connectors, Model(s): HBHRE Followed by dashed alpha numerical digits.

Connectors, Model(s): HCDE Followed by dashed alpha numerical digits.

Connectors, Model(s): HD15 or D f/b E09, or DB25, f/b SN or PN, f/b 24 or 25, may be f/b 15, 30, LPJ, HT or R

Connectors, Model(s): HDCE f/b 188, f/b G, may be f/b 30, BK or HT

Connectors, Model(s): HDL Followed by 15, 26, 44, 62 or 78, Followed by dashed alpha numerical digits.

Connectors, Model(s): HDL or HDVG f/b 15, 26, 44 or 62, f/b PL or SL, f/b A, B, C or D, may be f/b 15, 30, EMI F, HT or R

Connectors, Model(s): HDL15 or D f/b E09 or B25, f/b PS or SS, f/b 24 or 25, may be f/b 15, 30 or R

Connectors, Model(s): HDMI f/b S, f/b R, f/b 1, SMT or TSMT, may be f/b 15, MF or R

Connectors, Model(s): HDT Followed by 15, 26, 44, 62 or 78, Followed by dashed alpha numerical digits.

Connectors, Model(s): HDT f/b 15, 26, 44, 62, f/b PD, PR, PT, SD, SR or ST, may be f/b WT, HT, SL, JS, BL, 15, 30 or EMI

Connectors, Model(s): HFCS Followed by up to 3 alpha digits, Followed by dashed alpha numerical digits.

Connectors, Model(s): HFCS f/b 10, 20, 30, 40, 50, 60, 70, 80, 90 or 100, f/b SG or T, may be f/b N

Connectors, Model(s): HFDP Followed by dashed alpha numerical digits.

Connectors, Model(s): HFDP f/b 30, 50, 68, 72, 80 or 100, f/b SG or T, may be f/b N

Connectors, Model(s): HFH Followed by dashed alpha numerical digits.

Connectors, Model(s): HFTR Followed by dashed alpha numerical digits.

Connectors, Model(s): HFTR f/b 10, 12, 14, 16, 20, 22, 26, 30, 34, 40, 44 or 50, f/b SG or T, may be f/b N

Connectors, Model(s): HMCA f/b A or B, f/b 112, 120, 132, 182, 184 or 194, f/b G, may be f/b 30 or HT

Connectors, Model(s): HMCA Followed by dashed alpha numerical digits.

Connectors, Model(s): HMHR Followed by dashed alpha numerical digits.

Connectors, Model(s): HMSX Where X can be A through Z, Followed by dashed alpha numerical digits.

Connectors, Model(s): HPH f/b 2 f/b A or B, f/b 2 thru 80, f/b SG, U or T, f/b A or B may be f/b HT, SMT, SMT-A, SMT-B or P

Connectors, Model(s): HPH1 Followed by dashed alpha numerical digits.

Connectors, Model(s): HPH2 Followed by dashed alpha numerical digits.

Connectors, Model(s): HRS Followed by dashed alpha numerical digits.

Connectors, Model(s): HRS2BR Followed by dashed alpha numerical digits.

Connectors, Model(s): HSH Followed by dashed alpha numerical digits.

Connectors, Model(s): ICM or TMC f/b 3, 4, 6 or 9, f/b 06 thru 52, f/b 1 or 2, f/b GT or TT, may be f/b SMT, SMT-A, SMT-B or HT

Connectors, Model(s): ICS f/b 3 or 6, f/b 06 thru 48, f/b T, may be f/b OF or HT

Connectors, Model(s): IDC f/b T, G, S, A, B, C or D, f/b 24, 28, 32, 36 or 40

Connectors, Model(s): LH f/b A or S f/b 2 thru 20, f/b TS, TRA or TRB

Connectors, Model(s): LH f/b B or F f/b 2 thru 20, f/b S, f/b A or B, f/b 1 or 2

Connectors, Model(s): LH f/b C or D may be f/b A, f/b 2 thru 20, f/b MTS, TS, TRA or TRB

Connectors, Model(s): MC f/b alphanumeric digits, f/b A, B, C, D or E, f/b SG or G

Connectors, Model(s): MCT, 1MCT, HMCT or 2MCT f/b 1, 1R, 2 or 2R 01 thru 40 or 2 thru 80, f/b 1 or 2, f/b G or T, may be f/b SMT, SMT-A, SMT-B or HT

Connectors, Model(s): MDE f/b 3P thru 6P, f/b W or WS, may be f/b RT, PG, PG4 or TGBP

Connectors, Model(s): MDJ may be f/b D, f/b 3P thru 9P, f/b S or FS, may be f/b RT, PG, PG4 or TGBP

Connectors, Model(s): MDV f/b 3P thru 8P. f/b B or E may be f/b RT, PG, PG4 or TGBP

Connectors, Model(s): MHR f/b 10, 14, 16, 20, 24, 26, 30, 34, 40, 50, 60 or 64, f/b V or H, f/b U, SG or T, f/b A or B, f/b S, L or N, may be f/b U, SG or T

Connectors, Model(s): MHR Followed by dashed alpha numerical digits.

Connectors, Model(s): MPCl Followed by dashed alpha numerical digits.

Connectors, Model(s): MPCIE f/b 001 thru 110, f/b alphanumeric digits

Connectors, Model(s): MPE f/b 001 thru 125, f/b R, f/b SMT, f/b 2 thru 10, f/b TR

Connectors, Model(s): MPE Followed by dashed alpha numerical digits.

Connectors, Model(s): MPH Followed by dashed alpha numerical digits.

Connectors, Model(s): MPH f/b 4, 6, 8, 10, 12, 14, 16, 18, 20, 24 or 26, f/b F, V H or SMT, f/b SG or T may be f/b 15, 30 or L

Connectors, Model(s): MPH, MPF or MPC f/b 4, 6, 8, 10, 12, 14, 16, 18, 20, 24 or 26, f/b F, V, H or SMT, f/b SG or T, may be f/b 15, 30 or L

Connectors, Model(s): MPH2 f/b 04 thru 80, f/b U, SH or T, f/b Blank or SMT

Connectors, Model(s): MR Followed by 14, 24, 36 or 50, Followed by PA, PC, PD, PE, PF, PG, SA, SC, SD, SE, SF or SG, Followed by dashed alpha numerical digits.

Connectors, Model(s): MR f/b 14, 24, 36 or 50 f/b P or S, f/b A, B, C, D, E, F or G, f/b 1, 14, 2, 3 or 34, may be f/b 30, BK, F, HT or LI

Connectors, Model(s): MS f/b alphanumeric digits, f/b A, B, C, D or E, f/b SG, G, T or MT, may be f/b A

Connectors, Model(s): MS f/b A, B, C, DA, DB, BH, SA, SB, SC, SE, ST or BG, f/b G or T, may be f/b 30, may be f/b R, B, W, Y or G

Connectors, Model(s): MS2X X can be A through Z, Followed by dashed alpha numerical digits.

Connectors, Model(s): MSBX Where X can be A through Z, Followed by dashed alpha numerical digits.

Connectors, Model(s): MSDX Where X can be A through Z, Followed by dashed alpha numerical digits.

Connectors, Model(s): MSX Where X can be A through Z, Followed by dashed alpha numerical digits.

Connectors, Model(s): MTB maybe f/b alphanumeric digits , f/b 02 thru 20, maybe f/b alphanumeric digits, maybe followed by V0

Connectors, Model(s): MTD Followed by dashed alpha numerical digits.

Connectors, Model(s): MTS followed by dashed alpha numerical digits

Connectors, Model(s): PCA f/b 1, 2, 2B, 3, 4, 5, 6, 6A, 6B, 6C or 7 f/b 03 thru 30, f/b v, HL or HU, f/b 3, f/b 20 or Blank, may be f/b TR

Connectors, Model(s): PCA f/b alphanumeric digits f/b 03 thru 30, f/b V, HD, HL or HU, f/b 3, maybe f/b 20, G, KT or Blank, may be f/b TR.

Connectors, Model(s): PCB f/b A, B, C, D, E, G, H or K followed by 02 THRU 40, followed by T, SA or SB, f/b 20, 25 or SMT, maybe f/b alphanumeric digits

Connectors, Model(s): PCIE f/b 36, 64, 98 or 164, f/b 1 or SM, may be f/b 30, WT or HT

Connectors, Model(s): PCIE Followed by dashed alpha numerical digits.

Connectors, Model(s): PCMCIA f/b one alphanumeric digit, f/b 68, f/b one alphanumeric digit, f/b one alphanumeric digit, f/b 1 thru 9, f/b 1 or 2, f/b one alphanumeric digit, f/b one alphanumeric digit.

Connectors, Model(s): PH /b 1, 1RA, 1RB, 2, 2RA, 3 or 3RA, f/b 1 through 40, f/b U, V, W, T or SG, f/b A or B, may be f/b SMT, SMT-A, SMT-B, HT or L

Connectors, Model(s): PH f/b 1, 1RA, 1RB, 2, 2RA, 3, 3RA, f/b 1 thru 40 f/b U, V, W, T or SG, f/b A or B, may be f/b SMT, SMT-A, SMT-B, HT or L

Connectors, Model(s): PH f/b 1, 1RA, 1RB, 2, 2RA, 3, 3RA, f/b 2 thru 80 f/b U, V, W, T or SG, f/b A or B, may be f/b SMT, SMT-A, SMT-B, HT or L

Connectors, Model(s): PH1 Followed by dashed alpha numerical digits.

Connectors, Model(s): PH2 Followed by dashed alpha numerical digits.

Connectors, Model(s): PLCC f/b 20, 28, 32, 44, 52, 68 or 84, f/b At or Ag, may be f/b SMT, may be f/b P or TR

Connectors, Model(s): RCA f/b 1 thru 11, f/b 1 thru 4, f/b B, R, W, Y, Ganged: X/X = Left / Right Color X/X/X = Left / Center / Right Color

Connectors, Model(s): RS Followed by dashed alpha numerical digits.

Connectors, Model(s): RS, 2RS or HRS f/b 1, 1R, E1 or M1 f/b 2 thru 40, f/b G, T or SG, may be f/b SMT-A, SMT-B, 30, P or HT

Connectors, Model(s): RS, 2RS or HRS f/b 2, 2R, B, BR, E2 or M2 f/b 4 thru 80, f/b SMT, 30, P or HT

Connectors, Model(s): RS1 Followed by dashed alpha numerical digits

Connectors, Model(s): RS1B Followed by dashed alpha numerical digits.

Connectors, Model(s): RS1BR Followed by dashed alpha numerical digits.

Connectors, Model(s): RS1H Followed by dashed alpha numerical digits.

Connectors, Model(s): RS1L Followed by dashed alpha numerical digits.

Connectors, Model(s): RS1R Followed by up to 3 alpha digits, Followed by dashed alpha numerical digits.

Connectors, Model(s): RS1T Followed by dashed alpha numerical digits.

Connectors, Model(s): RS2 Followed by dashed alpha numerical digits.

Connectors, Model(s): RS2B Followed by dashed alpha numerical digits.

Connectors, Model(s): RS2BR Followed by dashed alpha numerical digits.

Connectors, Model(s): RS2H Followed by dashed alpha numerical digits.

Connectors, Model(s): RS2L Followed by dashed alpha numerical digits.

Connectors, Model(s): RS2R Followed by dashed alpha numerical digits.

Connectors, Model(s): RS2T Followed by dashed alpha numerical digits.

Connectors, Model(s): RS3 Followed by dashed alpha numerical digits.

Connectors, Model(s): RSB Followed by dashed alpha numerical digits.

Connectors, Model(s): RSEX Followed by dashed alpha numerical digits.

Connectors, Model(s): RSM1 - Followed by dashed alpha numerical digits.

Connectors, Model(s): RSM2 Followed by dashed alpha numerical digits.

Connectors, Model(s): RSVL Followed by dashed alpha numerical digits.

Connectors, Model(s): S2A f/b SR or SV, f/b 20, 26, 28, 40, 50, 60, 68, 80, 100 or 120, f/b 2 or 3, f/b TFA, TF/B, TFC, TFD or BL, f/b 1, 2 or 3

Connectors, Model(s): SATA SATA f/b A thru M, f/b PL, PR or PM, f/b VT, RT, SM or SMT, may be f/b H, S, 30 or P

Connectors, Model(s): SBHR Followed by dashed alpha numerical digits.

Connectors, Model(s): SD f/b alphanumeric digits, f/b A, B, C, D or E, f/b SG or G

Connectors, Model(s): SFC 1 thru 8, may be f/b LP, LP1, LP2, LP3 or EMI

Connectors, Model(s): SFCJ f/b 2, 4, 8 or 12, may be f/b LP, LP1, LP2, LP3 or EMI

Connectors, Model(s): SFF f/b 20, f/b SG, may be f/b LP, LP1, LP2, LP3 or EMI

Connectors, Model(s): SMC, 1SMC, HSMC or 2SMC f/b 1, 1R, 2 or 2R, f/b 1, f/b GT or TT, may be f/b SMT, SMT-A, SMT-B or HT


Connectors, Model(s): SPDIF f/b RA or ST, f/b one or more alphanumeric digits.

Connectors, Model(s): SPH Followed by dashed alpha numerical digits.

Connectors, Model(s): SPH2 f/b 04 thru 80, f/b U, SH or T, f/b Blank or SMT

Connectors, Model(s): USB, MUSB, MCR, FWC or MFW f/b A, A3, B, B3, AB, B4, B5, C, D, P, AP, BP or AB1, f/b S, D, T or Q, f/b RA, RU, VT or S, may be f/b SMT, TSMT, 30, WT, HT or T/R

Last Updated on 2023-01-19



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."