

# HK

# 1/4" x 1 1/4" Panel-mount indicating fuse holder



### **Product features**

- For 1/4" x 1 1/4" fuses
- For panels up to 3/16" (4.8 mm) thick
- Vibration resistant
- · Light comes on when fuse opens
- Steel nut 9351
- Neoprene washer 6276
- Line connection is the back terminal
- Do not put tension on line (rear) terminal.


#### **Environmental Data:**

Temperature Rating (RTI): +130 °C


# **Agency information**

- \*UL Recognized, Guide IZLT2, File E14853
- \*CSA Certified, Class 6225-01, File 47235

## Dimensions- in (mm)



#### **Punched Mounting Hole**



# **Electrical Ratings**

Catalog Symbol		Lamp		Knob	Knob
	Amps	Volts AC	Туре	Color	Туре
HKL *	15	90-250	Neon	Clear	Octagon
HKL-X *	15	90-250	Neon	Clear	Flat Sided
HKR	20	22-30	Incandescent	Amber	Octagon
HKT	20	13-22	Incandescent	Amber	Octagon
HKU	20	4-6	Incandescent	Red	Octagon
HKX	20	22-33	Incandescent	Amber	Flat Sided

CE CE logo denotes compliance with European Union Low Voltage Directive (50-1000Vac, 75-1500Vdc). Refer to Data Sheet: 8002

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

#### Eaton Electronics Division

1000 Eaton Boulevard Cleveland, OH 44122 United States www.eaton.com/electronics

© 2017 Eaton All Rights Reserved Printed in USA Publication No. 2105 SB04184 June 2017

