



		1	
Part Number:		DRAWN	7/24/2010
NANAOO	2002 1	CJ	7/24/2018
	3802-1	CHECKED	8/16/2018
		C.H.	0/10/2010
Description:	IC Misusubsus	APPROVED	0/16/2010
Analog MEM	IS Microphone	C.E.	8/16/2018

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


## Top View



## Side View



## **Bottom View**



Pin 1	Pin 2	Pin 3	Pin 4
OUTPUT	GND	VDD	GND

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.

┑	Items	Specifications	Conditions				Ī	
Α	Directivity	Omnidirectional						
	Sensitivity	-38 ± 1	dB					
	Frequency Range	30 ~ 10,000	Hz					
	Rated Voltage	2	V					
	Voltage Range	1.6 ~ 3.6	V		REVISION HISTORY			
	Output Impedance	300	Ω	REV	DESCRIPTION	DATE	APPROVED	
	Max. Rated Current	0.1	mA		Released from Engineering	8/16/2018	C.E.	
	Power Supply Rejection	-90	dB		NOTES			
ſ	Storage Temperature	-40 ~ +105	°C		All dimensions are in mm unless otherwise noted			
Ī	Operating Temperature	-40 ~ +105	°C		2) All tolerances are ± 0.1 mm unless otherwise noted			
	Signal to Noise Ratio	65	dB		3) All parts meet RoHS			
	Mount Type	Surface Mount			4) Subject to change or redrawn without notice			
	Connection Method	Surface Mount Pads						
_			2	A .	2		4	