| TOP VIEWSIDE VIEWImage: Constraint of the second s | | | | | | | | | | | |
|---|-------------|-------|-----------------------------|------------------------|------------------|--------------------|--------------------|---------------------------|--------------------|--------------------|--|
| Sne | cifications | | | | | Revision History | | | | | |
| Description | | | Notes | | Version | Description | | | Date | Approved | |
| Resonant Frequency | 4,000 | (Hz) | 1) All dimensions are in mm | unless otherwise noted | 1 | Releas | ed from Eng | | 10/21/2013 | J.S | |
| Resonant Impedance (Max) | 1,000 | (Ohm) | 2) All parts meet RoHS | | | | 0 | 5 | | | |
| Max Input Voltage | 30 | (V) | 1 | | | | | | | | |
| Capacitance | 13,000 | (pF) |] | | | | | | | | |
| Plate Material | Brass | | | | | | | | | | |
| Operating Temperature | -20 ~ +60 | °C | | | | | | | | | |
| Storage Temperature | -20 ~ +70 | °C | | | Drawn by A.B. | Date 10/21/2013 | Checked by C.E. | Date 10/21/2013 | Approved by J.S | Date 10/21/2013 | |
| | | | | | P18040-1 | | | | | | |

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.