		TOF	P VIEW	SIDE V	ΊEW					
	<u>Ø20.0±0.4</u>		Ø27.0±0.1	-	20±0.01 42±0.03					
				_						
SI	pecifications						Revisio	on History		
Si Description	pecifications Value	Unit		Votes	Version		Revisic	-	Date	Approved
		Unit (Hz)	• • • • • • • • • • • • • • • • • • • •		Version 1	Release		-	Date 10/21/2013	Approved J.S
Description	Value					Release	Description	-		
Description Resonant Frequency	Value 4,000	(Hz)	1) All dimensions are in mm u			Release	Description	-		
Description Resonant Frequency Resonant Impedance (Max)	Value 4,000 500	(Hz) (Ohm)	1) All dimensions are in mm u			Releas	Description	-		
Description Resonant Frequency Resonant Impedance (Max) Max Input Voltage	Value 4,000 500 20	(Hz) (Ohm) (V)	1) All dimensions are in mm u			Release	Description	-		
Description Resonant Frequency Resonant Impedance (Max) Max Input Voltage Capacitance	Value 4,000 500 20 20,000	(Hz) (Ohm) (V)	1) All dimensions are in mm u			Release	Description	-		
Description Resonant Frequency Resonant Impedance (Max) Max Input Voltage Capacitance Plate Material	Value 4,000 500 20 20,000 Stainless Steel	(Hz) (Ohm) (V) (pF)	1) All dimensions are in mm u			Release	Description	-		
Description Resonant Frequency Resonant Impedance (Max) Max Input Voltage Capacitance Plate Material Operating Temperature	Value 4,000 500 20 20,000 Stainless Steel -20 ~ +60	(Hz) (Ohm) (V) (pF) °C	1) All dimensions are in mm u			Release	Description	-		

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.