


			1		
Part Number:	Part Number:		DRAWN	4/7/2016	
SC24		0908-1	CJ		
			CHECKED	4/11/2016	
			P.D.	7/11/2010	
Description:	Dumami	a Chanleau	APPROVED	4/11/2016	
	Dynamic Spea	с эреакег	J.S.	4/11/2010	

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com

Top View 14.90 Silk Screen Marking "16 D" 16=2016, D=Apr.



24.90		12.00
	24.90	

Bottom View

Items	Specifications	Conditions					
Sound Pressure Level	95	dB (@ 10cm)					
Resonant Frequency	900	Hz		REVISION HISTORY			
Frequency Range	900 ~ 20,000	Hz	REV	DESCRIPTION	DATE	APPROVED	
Nominal Power	0.5	W		Released from Engineering	10/21/2013	J.S.	
Max. Power	1	W	1	SPL Updated	2/11/2016	J.S.	
Impedance	8	Ω	NOTES				
Cone Material	Cloth			All dimensions are in mm unless otherwise noted			
Mount Type	Frame Mount			2) All tolerances are \pm 0.5 mm unless otherwise noted			
Storage Temperature	-20 ~ +50	℃	3) All parts meet RoHS				
Operating Temperature	-20 ~ +50	•€	4) Subject to change or redrawn without notice				
Matalah	•						