


			1		
	TE00220E 1		DRAWN	7/13/2015	
			CJ		
			CHECKED	11/23/2015	
			P.D		
	Pescription:	nical Transducer	APPROVED	11/23/2015	
	LIECTIO-MECHO		J.S	11/23/2013	

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com

Bottom View




Side View (2)

Top View

-8.50-

3 - 0.63

-Dummy Pad



Side View (1)

2 - Ø0).75−\	
Dummy Pad—	\ .	1.00
030	Ø1.00	Ø1.30

Weight

	Items	Specifications	Conditions					
	Sound Pressure Level	87	dB (@ 10cm)					
	Resonant Frequency	2,350	Hz					
ı	Rated Voltage	5	V	REVISION HISTORY				
	Voltage Range	3~7	V	REV	DESCRIPTION	DATE	APPROVED	
A	Coil Resistance	30	ohm		Released from Engineering	10/21/2013	J.S.	
,	Max. Rated Current	90	mA	1	Updated to new template	11/23/2015	J.S.	
A -	Storage Temperature	-30 ~ +70	°C		NOTES			
	Operating Temperature	-30 ~ +70	°C		All dimensions are in mm unless otherwise noted			
	Connection Method	Surface Mount Pads			2) All tolerances are ± 0.5 mm unless otherwise noted			
	Mount Type	Surface Mount			3) All parts meet RoHS			
	Housing Material	LCP		4) Subject to change or redrawn without notice				

Polarity Pad (+)-

Polarity Pad (-)