

Materials and Finish

Housing: PBT Thermoplastic
 UL 94V-0 Rated, Black Color
 Contact Material:
 Pin #1: Brass, Matte Tin Plated
 Pin #2 and Pin #4:
 Phosphor Bronze, Matte
 Tin Plated
 Pin #3 and Pin #5:
 Brass, Matte Tin Plated
 Switch Contacts:
 Brass, Matte Tin Plated

Electrical Characteristics

Insulation Resistance:
 100 Megohms at 500V DC
 Contact Resistance:
 50 milliohms Max.
 Dielectric Withstanding Voltage:
 500V AC RMS for 1 Minute

Mechanical Characteristics

Insertion Force: 0.3kg - 3.0kg
 Withdrawal Force: 0.3kg - 3.0kg
 Durability: 5000 Mating Cycles Min.
 Operating Temperature:
 -25°C to +85°C
 Torque : 1.5lb-in Max.

Tolerances
X.X ± 0.30
X.XX ± 0.15
Unless Stated Otherwise




REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	03/29/18	New Drawing	G. Serrato	C. Furumasu	G. Serrato	03/29/18
A1	11/07/18	Release Drawing DC18-009	D. Shehan	C. Kelleher		
A2	12/05/18	ECO #18-061	G. Serrato	D. Shehan		

STX-3150-5C-1

Stereo Jack, Straight Black Cover, 5 Pos

Thread w/ Nut, RoHS Compliant



UNITS
mm