



			1	
	Part Number:		DRAWN	
	TEAL	1003-6	CJ	3/20/2022
	1 054		CHECKED	3/21/2022
			P.D.	
	Description:	nical Transducer	APPROVED	3/21/2022
	Electro-Mechai		J.S.	

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


Top View



Side View



Bottom View



Items	Specifications	Conditions						
Min. Sound Pressure Level	83	dB (@ 10cm)						
Resonant Frequency	4,000	Hz						
Rated Voltage	3	V						
Voltage Range	2 ~ 4	V	REVISION HISTORY					
Coil Resistance	12 ± 3	Ω	REV	DESCRIPTION	DATE	APPROVED		
Max. Rated Current	110	mA		Released from Engineering	3/21/2022	J.S.		
Storage Temperature	-40 ~ +90	°C	NOTES					
Operating Temperature	-40 ~ +90	°C	All dimensions are in mm unless otherwise noted					
Connection Method	Surface Mount Pads			2) All tolerances are ± 0.3 mm unless otherwise noted				
Mount Type	Surface Mount			3) All parts meet RoHS				
Housing Material	LCP			4) Subject to change or redrawn without notice				
Weight	0.1	g						