## **COLOR CABLE TIES**





# COLOR CABLE TIES

Standard Colors and Outdoor Weatherable UV Colors

- High quality color concentrates and manufacturing processes produce color consistency time after time
- Ideal applications: Color Coding, Packaging Continuity, Identification, Bundling Aesthetics, etc.
- Custom colors are available

#### Color Cable Ties

ACT Part Number	Color	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	Mil-Spec	Per Bag	Per Case
AL-04-18-#-C	Ref. Chart	4.12/104.77	.095/2.413	.042/1.066	18 lb./80 n.	.875/22.2	MS3367-4*	100	10,000
AL-05-40-#-C	Ref. Chart	5.84/148.33	.140/3.556	.049/1.244	40 lb./178 n.	1.437/36.4	MS3367-5*	100	5,000
AL-08-40-#-C	Ref. Chart	8.87/225.42	.140/3.556	.049/1.244	40 lb./178 n.	2.375/60.3		100	5,000
AL-07-50-#-C	Ref. Chart	7.56/192.07	.180/4.572	.052/1.320	50 lb./222 n.	1.875/47.6	MS3367-1*	100	5,000
AL-11-50-#-C	Ref. Chart	11.25/285.75	.180/4.572	.052/1.320	50 lb./222 n.	3.062/77.7	MS3367-7*	100	5,000
AL-14-50-#-C	Ref. Chart	14.35/364.49	.180/4.572	.052/1.320	50 lb./222 n.	4.00/101.6	MS3367-2*	100	5,000
AL-14-120-#-C	Ref. Chart	14.82/376.63	.300/7.620	.076/1.930	120 lb./534 n.	4.06/103.1	MS3367-3*	100	2,000

<sup>14&</sup>quot; 120 lb. is not available in brown and fluorescent yellow, Sold in case quantities \*MIL-SPEC does not apply to fluorescent colors

#### **UV Color Cable Ties**

ACT Part Number	Color	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	Per Bag	Per Case
AL-04-18-#UV-C	Ref. Chart	4.12/104.77	.095/2.413	.042/1.066	18 lb./80 n.	.875/22.2	100	10,000
AL-05-40-#UV-C	Ref. Chart	5.84/148.33	.140/3.556	.049/1.244	40 lb./178 n.	1.437/36.4	100	5,000
AL-08-40-#UV-C	Ref. Chart	8.87/225.42	.140/3.556	.049/1.244	40 lb./178 n.	2.375/60.3	100	5,000
AL-07-50-#UV-C	Ref. Chart	7.56/192.07	.180/4.572	.052/1.320	50 lb./222 n.	1.875/47.6	100	5,000
AL-11-50-#UV-C	Ref. Chart	11.25/285.75	.180/4.572	.052/1.320	50 lb./222 n.	3.062/77.7	100	5,000
AL-14-50-#UV-C	Ref. Chart	14.35/364.49	.180/4.572	.052/1.320	50 lb./222 n.	4.00/101.6	100	5,000
AL-14-120-#UV-C	Ref. Chart	14.82/376.63	.300/7.620	.076/1.930	120 lb./534 n.	4.06/103.1	100	2,000

<sup>14&</sup>quot; 120 lb. is not available in brown and fluorescent yellow, Sold in case quantities; Minimum purchase required 
\*MIL-SPEC does not apply to fluorescent colors



1 = Brown	8 = Gray
_	11 = Fluorescent Green
2 = Red	i i = Fluorescent Green
3 = Orange	12 = Fluorescent Pink
4 = Yellow	13 = Fluorescent Yellow
5 = Green	14 = Fluorescent Orange
6 = Blue	15 = Fluorescent Blue
7 = Purple	18 = Pink

### OUTDOOR WEATHERABLE UV COLOR CODES

1UV = Brown	8UV = Gray
2UV = Red	11UV = Fluorescent Green
3UV = Orange	12UV = Fluorescent Pink
4UV = Yellow	13UV = Fluorescent Yellow
5UV = Green	14UV = Fluorescent Orange
6UV = Blue	15UV = Fluorescent Blue
7UV = Purple	18UV = Pink





245 Suffolk Lane, Gardner, MA 01440 Phone: 800.861.7228 - Fax: 978.630.3999 sales@actfs.com





