


PANEL CUT OUT

A 

inches		
	Maxi	mini
A	.198	.192
B	.183	.177

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	07/11/18	D.N.

NOTES:

MATERIALS:

1. INSULATORS = VIRGIN WHITE TEFLON PER ASTM D1710, GRADE 1, TYPE I, CLASS "B".
2. LOCKWASHER = PHOSPHOR BRONZE PER ASTM B139, COPPER ALLOY C53400, TEMPER H04.
3. ALL OTHER METAL PARTS = BRASS PER ASTM B16, ALLOY C36000, TEMPER H02.

FINISHES:


1. CONTACT = GOLD PLATE PER ASTM B488-11, TYPE II, 50µin MIN, GRADE C, OVER 100 TO 200µin STRESS FREE SULFAMATE NICKEL PER AMS-QQ-N-290.
2. ALL OTHER METAL PARTS = GOLD PLATE PER ASTM B488-11, TYPE II, 30µin MIN, GRADE C OVER 100 TO 200µin COPPER STRIKE PER AMS 2418.

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON

DECIMAL	ANGLE
---------	-------

DWN:	DATE
D.N.	07/11/18
CHKD:	DATE
C.E.	07/11/18
APVD:	DATE
J.M.	07/11/18

Property of Radiall
This document cannot be reproduced or
communicated to a third party without prior
written permission of RADIALL.




**RIGHT ANGLE CABLE TERMINATION
BULKHEAD MOUNTED CRIMP TYPE
FOR RG-316 & SIMILAR CABLES**

REFERENCE:

ORIGINATED: D.N.
DATE: 07/11/18

MATERIALS & FINISHES:

SEE NOTES

SIZE	FSCM NO.	DWG NO.	REV
A	19505	8144-1521-003	A
SCALE	THIRD ANGLE PROJECTION		SHEET 1 OF 1
5:1			

8144-1521-003