SAFETY DATA SHEET SRA #912 Rosin Flux, Type R

DATE REVISED: January 1, 2020

SECTION 1 -- IDENTIFICATION

Product Name/Part number: FLS912-1G, FLS912-4G

Recommended use: Solderability Testing Flux

Manufacturer:

SRA Soldering Products 24 Walpole Park S., STE 10 Walpole MA, 02081

Emergency Contact: INFOTREC Emergency Phone: 1-800-535-5353 For other info: (508) 668-6044

SECTION 2 – HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

GHS Classification in accordance with OSHA HCS (29 CFR 1910)

Flammable liquids (Category 2) H225

Eye irritation (Category 2A) H319

Specific target organ toxicity after single exposure - Central nervous system (Category 3) H336 See below for full text of H-Statements

GHS Label Elements, including precautionary statements

Pictogram(s):



S

Signal Word: Dang	er		
Hazard Stat	tement(s)		
H225 High	Highly flammable liquid and vapor		
H319 Caus	19 Causes serious eye irritation		
H336 May	cause drowsiness or dizziness		
Precautiona	ry statement(s)		
P210	Keep away from heat, sparks, hot surfaces, and open flames. No smoking.		
P233	Keep container tightly closed.		
P240	Ground container and receiving equipment.		
P241	Use explosion-proof electrical, lighting and ventilation equipment.		
P242	Use only non-sparking tools.		
P243	Take precautionary measures against static discharge		
P264	Wash skin thoroughly after handling		
P271	Use only outdoors or in a well-ventilated area		
P280	Wear protective clothing and face protection		
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P312	Call a POISON CENTER if you feel unwell.		
P337+P313	If eye irritation persists: Get medical advice.		
P370+P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction		
P403+P233	Store in a well-ventilated place. Keep container tightly closed.		

(precautionary statements, continued)		
P403+P235	Store in a well-ventilated place. Keep cool.	
P405	Store locked up	
P501	Dispose of contents to an approved waste disposal plant.	
Hazards not otherwise classified or not covered by GHS: None		

SECTION 3 – COMPOSITION INFORMATION

Components	CAS Number	%
Isopropanol	67-63-0	40-70
Rosin, polymerized	65997-05-9	20-50
Unlisted percentages are non-hazardous stabilizers, and water. None of the materials in this product are listed		
NTP, IARC, or OSHA as c	arcinogens.	

SECTION 4 – FIRST AID MEASURES

Description of first aid measures

- **General advice:** Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
- **Inhalation:** If breathed in, move to fresh air. If not breathing, give artificial respiration. Consult a physician.
- **Eyes:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.
- Skin: Wash off with soap and plenty of water. Consult a physician.
- **Ingestion:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Most Important Symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2 (labeling)

SECTION 5 – FIREFIGHTING MEASURES

Suitable Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special Hazards: No data available

Special protective actions for firefighters: Wear self-contained breathing apparatus for firefighting if necessary. Use water spray to cool unopened containers.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

- **Personal Precautions and Equipment and emergency procedures:** Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. *See section 8 for personal protection.*
- **Environmental Precautions:** Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
- In Case Material is spilled: Contain spillage, then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use explosion-proof equipment. Keep away from sources of ignition – No smoking. Take measures to prevent the build up for electrostatic charge.

For full precaution statements see Section 2

Storage Requirements: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION CONTROL PARAMETERS

OSHA Permissible Exposure Limit (PEL): 200 ppm **ACGIH Threshold Limit Value (TLV):** 200 ppm

- **Engineering Controls:** Use local exhaust ventilation to maintain air concentrations of vapors and fumes below occupational exposure standards.
- Special Engineering Control Needs: Explosion Proof, non-sparking equipment
- **Respiratory Protection:** Where risk assessment shows air-purifying respirators are appropriate, use a full-face respirator with multi-purpose combination (USA) or ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested an approved under appropriate government standards such as NIOSH (USA) or CEN (EU).
- **Protective Gloves:** Handle with gloves. (Nitrile Rubber recommended) Gloves must be inspected prior to use. Use proper glove removal techniques (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good lab practices. Wash and dry hands after handling.
- **Eye Protection:** Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (USA) or EN 166 (EU)

Body Protection: Impervious clothing, flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

SECTION 9 - PHYSICAL AND CHEMICAL CHARACTERISTICS

Appearance Odor Odor threshold pH Melting point/Freezing point Initial boiling point and boiling range Flash point Evaporation rate Flammability (Solid, gas) Upper flammability or explosive limits Lower flammability or explosive limits Vapor pressure

Vapor density Relative density Solubility(ies) Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature Viscosity Amber liquid Alcohol No data available No data available -89.5°C / -129°F 81-83°C / 177.8-181°F $12^{\circ}C / 53.5^{\circ}F$ (closed cup) No data available No data available Upper explosion limit: 12.7% (V) Lower explosion limit: 2% (V) 43 hPa (32.5 mmHg) at 20°C / 68°F 59 hPa (44.0 mmHg) at 25°C / 77°F No data available 0.842 (Water = 1) Slightly miscible in water log Pow: 0.05 425°C / 797°F No data available No data available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity: No data available Stability: Product is stable under recommended storage conditions Possibility of hazardous reactions: Vapors may form explosive mixture with air Conditions to Avoid: Heat, sparks and flames Incompatibility: Oxidizing agents, acid anhydrides, aluminum, halogenated compounds, acids Hazardous Decomposition Products Carbon oxides (Under fire conditions) In the event of fire: See Section 5

SECTION 11 - TOXICOLOGICAL INFORMATION

Likely Route(s) of Exposure: Inhalation, ingestion, skin and eye contact				
Acute toxicit	y	No data available		
Skin corrosio	on/irritation	No data available		
Serious eye d	amage/eye irritation	No data available		
Respiratory	or skin sensitization	No data available		
Germ cell mutagenicity		No data available		
Carcinogenicity				
This product is or contains a component that is not classifiable as to its carcinogenicity based on				
its IARC, ACGIH, NTP, or EPA classification.				
IARC	ARC No component of this product present at levels greater than or equal to 0.1% is			
	identified as probable	e, possible or confirmed human carcinogen by IARC.		

- NTP No component of this product present at levels greater than or equal to 0.1% is identified as known or anticipated carcinogen by NTP.
- OSHA No component of this product present at levels greater than or equal to 0.1% is identified as carcinogen or potential carcinogen by OSHA.

Reproductive toxicity No data available

Specific target organ toxicity – Single exposure

Inhalation, Oral – May cause drowsiness or dizziness

Specific target organ toxicity – Repeated exposure No data available

Aspiration hazard No data available

Additional information

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated

SECTION 12 - ECOLOGICAL INFORMATION TOXICITY

Persistence and degradability No data availableBioaccumulative potentialNo data availableMobility in soilNo data availableOther adverse effectsHazard to ozone layer: No data available

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste treatment methods

Product Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging Dispose of as unused product.

SECTION 14- TRANSPORTATION

D.O.T. (USA)Proper Shipping Name: IsopropanolIdentification Number: UN1219Hazard Class(es): 3Packing Group: IIReportable Quantity (RQ): 5,000 lbsSpecial Precautions to Note:Environmental HazardsPoison Inhalation Hazard? NoMarine Pollutant? No

SECTION 15 - REGULATORY INFORMATION

SARA 302 Components	No Chemicals in this material are subject to the reporting requirement of SARA Title III, Section 302.			
SARA 313 Components	The following components are subject to reporting levels established by SARA Title III, Section 313:			
Component	CAS No.	Revision Date		
2-Propanol	67-63-0	01-01-1987		
California Prop. 65 Components This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.				

SECTION 16 - OTHER INFORMATION

Further information:

Judgments as to the suitability of information herein or the purchaser's purposes are necessarily the purchaser's responsibility. The above information does not represent any guarantee of the properties of the product. It is believed to be correct, but does not purport to be all inclusive and should be used only as a guide. Reasonable care has been taken in the preparation of this material, and is based on the present state of our knowledge.

SRA Soldering shall not be held liable for any damage resulting from handling or from contact with the above product.

Version 2.1 Revision Date: 11/15/2017