## Thermocouple Assemblies with Flexible Fiberglass Insulated Leads


A8B Series

These thermocouples are available with either stainless steel or inconel sheaths. Fitted with a transition from the sheath to 36 inches of fiberglass insulated (insulation code 828) flexible leads. Available in thermocouple types E, J, K, and T as a standard assembly. Other thermocouple calibrations as well as various lead wire insulation materials are available upon request.

Maximum service temperature of the transition adaptor is 400 degrees Fahrenheit. Maximum use temperature of the thermocouple is determined by considering the sheath material being used and the thermocouple calibration. Standard units are 12 inches long, units can be made as short as 1-1/2 inches long without any special consideration.

## NOTES:

- When ordering, specify Part No. and Length "L" Example: A8B-1-12
- PFA Teflon® encapsulation good to 450°F, can be added to any probe.
- Duplex and multiple units also available.
- For high temperature (800 degrees) Fahrenheit) connectors and miniature plugs and jacks see our F2 and F3 Series.
- All assemblies use magnesia (Mg0) internal insulation. Contact factory if other types of insulation are required.



304 Stainless Steel Sheath - Specifications					Inconel 600 Sheath - Specifications				
Туре	Sheath Diameter (in.)	Exposed Junction	Grounded Junction	Ungrounded Junction	Туре	Sheath Diameter (in.)	Exposed Junction	Grounded Junction	Ungrounded Junction
		Part No.	Part No.	Part No.			Part No.	Part No.	Part No.
J J J	0.062 0.125 0.187 0.250	A8B-1 A8B-2 A8B-3 A8B-4	A8B-5 A8B-6 A8B-7 A8B-8	A8B-9 A8B-10 A8B-11 A8B-12	J J J	0.062 0.125 0.187 0.250	A8B-49 A8B-50 A8B-51 A8B-52	A8B-53 A8B-54 A8B-55 A8B-56	A8B-57 A8B-58 A8B-59 A8B-60
к к к	0.062 0.125 0.187 0.250	A8B-13 A8B-14 A8B-15 A8B-16	A8B-17 A8B-18 A8B-19 A8B-20	A8B-21 A8B-22 A8B-23 A8B-24	К К К К	0.062 0.125 0.187 0.250	A8B-61 A8B-62 A8B-63 A8B-64	A8B-65 A8B-66 A8B-67 A8B-68	A8B-69 A8B-70 A8B-71 A8B-72
E E E	0.062 0.125 0.187 0.250	A8B-25 A8B-26 A8B-27 A8B-28	A8B-29 A8B-30 A8B-31 A8B-32	A8B-33 A8B-34 A8B-35 A8B-36	E E E	0.062 0.125 0.187 0.250	A8B-73 A8B-74 A8B-75 A8B-76	A8B-77 A8B-78 A8B-79 A8B-80	A8B-81 A8B-82 A8B-83 A8B-84
T T T T	0.062 0.125 0.187 0.250	A8B-37 A8B-38 A8B-39 A8B-40	A8B-41 A8B-42 A8B-43 A8B-44	A8B-45 A8B-46 A8B-47 A8B-48	T T T T	0.062 0.125 0.187 0.250	A8B-85 A8B-86 A8B-87 A8B-88	A8B-89 A8B-90 A8B-91 A8B-92	A8B-93 A8B-94 A8B-95 A8B-96

## Thermocouple calibration type N is available in all sizes.

Nanmag

## Tel: 800.786.4669 | Int'l: 001.508.872.4811

12