

834FX- B

(PART B)

Safety Data Sheet

Section 1: Identification


Product Identifier and Other Means of Identification

Product Identifier: 834FX-B**Other Product Identifier:** Black Flexible Epoxy, Thermally Conductive – Flame Retardant, Encapsulating and Potting Compound**Related Part #** 834FX-450ML, 834FX-1.7L, 834FX-7.4L, 834FX-40L

Recommended Use and Restriction on Use

Use: Epoxy hardener for use with resins**Uses Advised Against:** Not applicable

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number




For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

Section 2: Hazard(s) Identification
Classification of the Chemical Material
GHS Categories

Criteria		Category	Signal Word	Pictograms
Serious Eye Damage		1	Danger	Corrosion
Skin Corrosion		1	Danger	Corrosion
Sensitization	Skin sensitizer	1	Warning	Exclamation
Acute Toxicity	Oral	4	Warning	Exclamation
Reproductive Toxicity		2	Warning	Health
Specific Target Organ Toxicity	Repeated Exposure	2	Warning	Health
Hazardous to the Aquatic Environment	Chronic	1	Warning	Environment


Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H314: Causes severe skin burns and eye damage
	H317: May cause an allergic skin reaction H302: Harmful if swallowed
	H361: Suspected of damaging fertility or the unborn child H373: May cause damage to liver and immune system through prolonged or repeated exposure

Section continued on the next page

834FX- B
(PART B)
Continued...

Pictograms	Hazard Statements
	H410: Very toxic to aquatic life with long lasting effects
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P201 + P202	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
P260	Do not breathe fumes/vapors.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
Response	Precautionary Statements
P310	For all routes of exposure: Immediately call a POISON CENTER/doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.

Section continued on the next page

834FX- B
(PART B)
Continued...

Storage	Precautionary Statements
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
21645-51-2	aluminum trihydrate	26%
9046-10-0	polyoxypropylenediamine	19%
68333-79-9	ammonium polyphosphate	19%
1344-28-1	aluminum oxide	16%
61788-44-1	phenol, styrenated	6%
138265-88-0	zinc borate	5%
61788-46-3	amines, coco alkyl	3%
25620-58-0	trimethylhexamethylenediamine	3%
1333-86-4	carbon black	0.5%

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305 + P351 + P338, P310
Immediate Symptoms	<i>redness, severe irritation, pain, burns</i>
Response	Rinse cautiously with water for 30 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
IF ON SKIN (or hair)	P303 + P361+ P353, P310, P363, P333 + P313
Immediate Symptoms	<i>redness, irritation, rash (allergic contact dermatitis), pain, chemical burns, blistering</i>
Response	Take off immediately all contaminated clothing. Wash with plenty of water/shower. Immediately call a POISON CENTRE/doctor. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
IF SWALLOWED	P301 + P330 + P331, P310
Immediate Symptoms	<i>irritation, abdominal pain, nausea, vomiting, burns to the digestive tract</i>
Response	Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER/doctor. If you feel unwell, get medical advice.
IF INHALED	P304 + P340, P310
Immediate Symptoms	<i>cough, irritation of the respiratory track, burning sensation</i>
Response	Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

Advice to Physicians

In case of exposure to combustion products during a fire, the symptoms of overexposure to nitrogen oxides (NO_x) may be delayed. For significant exposures, the exposed person should be kept under medical surveillance for 48 hours.

834FX- B**(PART B)****Section 5: Fire-Fighting Measures**

Extinguishing Media	In case of fire: Use extinguishing media suitable for surrounding materials.
Specific Hazards	Not flammable or combustible, but burns if involved in a fire. Produces irritating and toxic fumes in fires or in contact with hot surfaces. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO, CO ₂), nitrogen oxides (NO _x), and other toxic fumes.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	Use personal protection recommended in Section 8.
Precautions for Response	Do not breathe fumes/vapors.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways. Do not flush to sewer.
Containment Methods	Contain with inert absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Sprinkle inert absorbent compound onto spill, then sweep into the container. Wipe residue with a paper towel wetted with a suitable organic solvent such as alcohol or ethyl lactate, and place dirty towels in container. Wash spill area with soap and water to remove the last traces of residue. Collect spill waste in a sealable container.
Disposal Methods	Dispose spill waste according to Section 13.

Section 7: Handling and Storage
Prevention

Keep out of reach of children.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Do not breathe fumes/vapors.

Contaminated work clothing should not be allowed out of the workplace.

Do not eat, drink, or smoke when using this product.

Avoid release to the environment.

Handling

Collect spillage.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash hands thoroughly after handling.

Wash contaminated clothing before reuse.

Storage

Store locked up.

Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum metal and insoluble compounds ^{a)}	ACGIH	1 mg/m ³	Not established
	U.S.A. OSHA PEL	15 mg/m ³	Not established
	Canada AB	10 mg/m ³	Not established
	Canada BC	1 mg/m ³	Not established
	Canada ON	1 mg/m ³	Not established
	Canada QC	10 mg/m ³	Not established
aluminum oxide	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	5 mg/m ³	Not established
	Canada AB	10 mg/m ³	Not established
	Canada BC	Not established	Not established
	Canada ON	Not established	Not established
	Canada QC	10 mg/m ³	Not established

Section continued on the next page

834FX- B
(PART B)
Continued...

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
carbon black ^{a)}	ACGIH	3.5 mg/m ³	Not established
	U.S.A. OSHA PEL	3.5 mg/m ³	Not established
	Canada AB	3.5 mg/m ³	Not established
	Canada BC	3 mg/m ³	Not established
	Canada ON	3.5 mg/m ³	Not established
	Canada QC	3.5 mg/m ³	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS² database and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles

Engineering Controls
Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Due to low vapor pressure of the product, general ventilation should be adequate for normal use. If the product is heated at high temperatures or worker is allergic, use local ventilation and consider using a full mask breathing apparatus.

Because carbon black is bound to the liquid mixture, it does not present an airborne hazard under normal use.

Personal Protective Equipment
Eye protection

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Skin Protection

For likely contacts, use of protective butyl rubber, neoprene, or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Section continued on the next page

834FX- B**(PART B)**

Respiratory Protection For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

834FX- B
(PART B)
Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Black	Upper Flammability Limit	Not available
Odor	Mild	Vapor Pressure @20 °C	1 hPa [0.75 mmHg]
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	1.62
Freezing/Melting Point	Not available	Solubility in Water	Slightly soluble
Initial Boiling Point ^{a)}	>200 °C [>392 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	>124 °C [>255 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Non Flammable	Viscosity @25 °C	2 820 mm ² /s [4 670 cP]

a) Component with the lowest literature value polyoxypropylenediamine

Section 10: Stability and Reactivity

Reactivity	Reacts exothermically with epoxides.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid excessive heat and incompatible substances. Do not use in a way that forms a mist or aerosolize the product.
Incompatibilities	Strong oxidizing agents, strong acids, strong bases
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information
Summary of Effects and Symptoms by Routes of Exposure

Eyes	May cause redness, severe eye irritation, pain, and/or burns.
Skin	May cause redness, serious skin irritation, allergic contact dermatitis, pain, chemical burns, or blistering.
Inhalation	Inhalation of vapors or mist may cause irritation to the nose, throat and lung (upper respiratory tract).
Ingestion	May cause irritation, abdominal pain, nausea, vomiting, burns to the digestive tract. May cause allergic reactions (see inhalation symptoms).
Chronic	Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization. It may also lead to reproductive effects and damage to the liver and central nervous system.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
aluminum trihydrate	>10 000 mg/kg Rat	>10 000 mg/kg Rabbit ^{a)}	Not available
polyoxypropylenediamine	>480 mg/kg Rat	2 090 mg/kg Rabbit	Not available
ammonium polyphosphate	>300 mg/kg Rat	Not available	Not available
aluminium oxide	>2 000 mg/kg Rat	Not available	Not available
phenol, styrenated	3 700 mg/kg Rat ^{a)}	>5 010 mg/kg Rabbit ^{a)}	>4.9 mg/L (mist) Rat ^{a)}
zinc borate	>10 000 mg/kg Rat	>10 000 mg/kg Rat	>5.0 mg/L 4 h Rat ^{a)}
amines, coco alkyl	1 300 mg/kg Rat ^{a)}	>2 000 mg/kg Rat ^{a)}	Not available

Section continued on the next page

834FX- B
(PART B)
Continued...

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
trimethylhexamethylenediamine	Not available	Not available	Not available
carbon black	15 400 mg/kg Rat	3 000 mg/kg Rat	Not available

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDSs were also consulted.

a) Supplier MSDS

Other Toxicological Effects
Skin corrosion/irritation

The hardener system causes skin burns.

Serious eye damage/irritation

The hardener system causes severe eye damage.

Respiratory and skin sensitization (allergic reactions)

Phenol, trimethylhexamethylenediamine and 2,4,6-tris(dimethylaminomethyl)phenol may cause skin sensitization according to animal studies.

Carcinogenicity
(risk of cancer)

The carbon black [1333-86-4] is possibly carcinogenic by airborne routes of exposures.

Because the carbon black is bound in the epoxy liquid mixture, it is not available as an airborne hazard (dust, mist, or spray) under normal use.

Carbon Black [1333-86-4]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A4: Not classified as a human carcinogen

CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size)

NTP: Not listed

Mutagenicity
(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

Reproductive Toxicity
(risk to sex functions)

Animal ingestion studies show that high doses of zinc borate cause reproductive and developmental effects.

Teratogenicity
(risk of fetus malformation)

Based on available data, the classification criteria are not met.

Section continued on the next page

834FX- B**(PART B)****STOT-single exposure**

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Long term or repeated exposure to "amines, coco alkyl" are believed to lead to liver damage and immune system deficiencies.

Aspiration hazard

Based on available data, the classification criteria are not met. Contains <10% category 1 components, and the kinematic viscosity is >20.5 mm²/s at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The coco alkyl amines is classified as a chronic category 1 environmental toxicant with an M-factor of 10.

The phenol, styrenated compound is classified as chronic category 2 environmental toxicants.

The trimethylhexamethylenediamine and 2,4,6-tris(dimethylaminomethyl)phenol compounds are classified as chronic category 3 environmental toxicants.

The zinc borate is classified as a chronic category 1 environmental toxicant with a M-Factor of 1 (with minimal LC50 96 h of 2.4 mg/L for *Oncorhynchus mykiss* (rainbow trout); LC50 48 h of 76 mg/L *Daphnia magna* (water flea); and transformation/dissolution endpoint for zinc borate powder that release of 0.452 mg/L of zinc ion, which is higher than zinc's NOEC limit).

Based on available data, carbon black, aluminum trihydrate, aluminum oxide, polyoxypropylenediamine, ammonium polyphosphate, 1-decene, homopolymer, hydrogenated, and polyphosphoric acids are not classified as environmental hazards according to GHS criteria.

Acute Ecotoxicity

Category 1

Very toxic to aquatic life

Section continued on the next page

834FX- B

(PART B)

Chronic Ecotoxicity

Category 1

Very toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not readily biodegradable

Bioaccumulation

Not available

Other Effects



Not available

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

<p>Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); USA DOT 49 CFR (Parts 100 to 185) Regulations.</p>	
<p>Sizes 1 L and under <i>Part B of 834FX-450ML, 834FX-1.7L kits</i></p> <p>Limited Quantity Note: The 834FX-450ML and 834FX-1.7L kits are composed of separate containers which meet this inner packaging limit.</p>	<p>Sizes greater than 1 L (Cargo only) <i>Part B of 834FX-7.4L kit</i></p> <p>UN number: UN2735 Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. * (trimethylhexamethylenediamines, polyoxypropylene diamine, amines coco alkyl) Class: 8 Packing Group: II Marine Pollutant: Yes</p>
	

Section continued on the next page

834FX- B

(PART B)

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 0.5 L and under

Part B of 834FX-450ML kit

Limited Quantity



Sizes greater than 0.5 L up to 1 L (Passenger), 5 L (Cargo)

Part B of 834FX-1.7L kit

UN number: UN2735

Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. *
(trimethylhexamethylenediamines, polyoxypropylene diamine, amines coco alkyl)

Class: 8

Packing Group: II

Marine Pollutant: Yes



Sea

Refer to IMDG regulations.

Sizes 1 L and under

Part B of 834FX-450ML, 834FX-1.7L kits

Limited Quantity

Note: The 834FX-450ML and 834FX-1.7L kits are composed of separate containers which meet this inner packaging limit.



Sizes greater than 1 L

Part B of 834FX-7.4L kit

UN number: UN2735

Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. *
(trimethylhexamethylenediamines, polyoxypropylene diamine, amines coco alkyl)

Class: 8

Packing Group: II

Marine Pollutant: Yes



Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information**Canada****Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)**


All hazardous ingredients are listed on the DSL/NDSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA**Other Classifications****HMIS® RATING**

HEALTH:	* 3
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain zinc borate (CAS# 138265-88-0), which have a 1 000 lb reporting quantity requirements in section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product contains carbon black, but it is bound and exposures during normal conditions of uses are below the Safe Harbor Threshold.

834FX- B**(PART B)****Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by	MG Chemicals' Regulatory Department
Date of Revision	20 April 2022
Supersedes	02 March 2020
Reason for Changes:	Company address change

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

834FX- B**(PART B)****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Disclaimer This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.