

838AR-P

CARBON CONDUCTIVE PEN

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 838AR-P**Other Means of Identification:** Carbon Conductive Pen**Related Part #** 838AR-P, 838AR-PCA

Recommended Use and Restriction on Use

Use: Electrically conductive paint and EMI/RFI shield**Uses Advised Against:** Not applicable

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

Phone +1-800-340-0772**Fax** +1-800-340-0773**E-mail** support@mgchemicals.com**Web** www.mgchemicals.com**Phone** +1-905-331-1396**Fax** +1-905-331-2682**E-mail** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)




For emergencies involving the transport of dangerous goods; 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

838AR-P
CARBON CONDUCTIVE PEN
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquids	2	Danger	Flame
Eye Damage	1	Danger	Corrosive
Carcinogenicity	2	Warning	Health
Sensitization	1	Warning	Exclamation
Specific Target Organ Toxicity	3	Warning	Exclamation


Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
	H318: Causes serious eye damage
	H351: Suspected of causing cancer by inhalation

Section continued on the next page

838AR-P
CARBON CONDUCTIVE PEN
Continued...

Pictograms	Hazard Statements
	H317: May cause an allergic skin reaction H336: May cause drowsiness or dizziness
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P203	Obtain, read and follow all safety instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharge.
P280	Wear protective gloves, protective clothing, and eye protection.
P261	Avoid breathing mist, vapors, and spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P361 + P352	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash skin with plenty of water.
P333 + P317	If skin irritation or rash occurs: Get medical help.
P363	Wash contaminated clothing before reuse.
P305 + P351 + P338, P317	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help.
P304 + P340, P319	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.
P318	IF exposed or concerned, get medical advice.

Section continued on the next page

838AR-P
CARBON CONDUCTIVE PEN
Continued...

Storage	Precautionary Statements
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of container in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
67-64-1	acetone	36%
110-19-0	isobutyl acetate	30%
71-36-3	1-butanol	10%
1333-86-4	carbon black	6%
108-65-6	1-methoxy-2-propyl acetate	4%
25619-56-1	barium bis(dinonylnaphthalenesulphonate)	0.5%

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF IN EYES	P305 + P351 + P338, P317
Immediate Symptoms	<i>redness, pain, blurred vision, eye damage</i>
Response	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help.
IF ON SKIN (or hair)	P303 + P361, P363, P352, P333 + P317
Immediate Symptoms	<i>dry skin, redness, rash, allergic dermatitis</i>
Response	Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Wash with plenty of water. If skin irritation or rash occurs: Get medical help.
IF INHALED	P304 + P340, P319, P318
Immediate Symptoms	<i>cough, sore throat, vomiting, headache, dizziness, drowsiness, shortness of breath</i>
Response	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell. IF exposed or concerned, get medical advice.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	<i>abdominal pain, nausea, diarrhea, drowsiness, dizziness, vomiting, shortness of breath</i>
Response	Rinse mouth. Do NOT induce vomiting.

838AR-P

CARBON CONDUCTIVE PEN

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
Specific Hazards	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion. Produces irritating and toxic fumes in fires or in contact with hot surfaces. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO, CO ₂), and other toxic fumes.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing the mist, spray, and vapors. Remove or keep away all sources of ignition or extreme heat.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert and nonflammable absorbent (such as soil, sand, or vermiculite).
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue. RECOMMENDATION: Use a grounded stainless steel or carbon steel container.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage
Prevention

Keep out of reach of children.

Obtain, read and follow all safety instructions before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Take action to prevent static discharge.

Avoid breathing mist, vapors, and spray. Use only outdoors or in a well-ventilated area. Keep container tightly closed.

Handling

Wear protective gloves, protective clothing, and eye protection.

Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash it before reuse.

Storage

Store in a well-ventilated place. Keep cool.

Store locked up.

Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
acetone	ACGIH	500 ppm	750 ppm
	U.S.A. OSHA PEL	1 000 ppm	Not established
	Canada AB	500 ppm	750 ppm
	Canada BC	250 ppm	500 ppm
	Canada ON	500 ppm	750 ppm
	Canada QC	750 ppm	1 000 ppm
isobutyl acetate	ACGIH	150 ppm	Not established
	U.S.A. OSHA PEL	150 ppm	Not established
	Canada AB	150 ppm	Not established
	Canada BC	150 ppm	Not established
	Canada ON	150 ppm	Not established
	Canada QC	150 ppm	Not established

Section continued on the next page

838AR-P
CARBON CONDUCTIVE PEN
Continued...

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
1-butanol	ACGIH	20 ppm	Not established
	U.S.A. OSHA PEL	100 ppm	Not established
	Canada AB	20 ppm	Not established
	Canada BC	15 ppm	30 ppm (Ceiling)
	Canada ON	20 ppm	Not established
	Canada QC	50 ppm (Ceiling)	Not established
carbon black ^{a)}	ACGIH	3.5 mg/m ³	Not established
	U.S.A. OSHA PEL	3.5 mg/m ³	Not established
	Canada AB	3.5 mg/m ³	Not established
	Canada BC	3 mg/m ³	Not established
	Canada ON	3.5 mg/m ³	Not established
	Canada QC	3.5 mg/m ³	Not established
1-methoxy-2-propyl acetate	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	50 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	50 ppm	75 ppm
	Canada ON	50 ppm	Not established
	Canada QC	Not established	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database² and from suppliers' SDSs were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles

Engineering Controls
Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment
Eye protection

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Ensure that glasses have side shields for lateral protection.

Skin Protection

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

838AR-P
CARBON CONDUCTIVE PEN

Section continued on the next page

Respiratory Protection For over-exposures up to 10 x OEL of mist, vapors, and spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit ^{b)}	2%
Appearance	Black	Upper Flammability Limit ^{b)}	12%
Odor	Solvent like	Vapor Pressure @20 °C	Not available
Odor Threshold	Not available	Vapor Density	≥2
pH	Not available	Relative Density @25 °C	0.89
Freezing/Melting Point	Not available	Solubility in Water	Partly miscible
Initial Boiling Point ^{a)}	56 °C [132 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	-17 °C [1.4 °F]	Auto-ignition Temperature ^{a)}	465 °C [869 °F]
Evaporation Rate	<1 (ButAc = 1)	Decomposition Temperature	Not available
Flammability	Highly flammable	Viscosity @25 °C	114 cP

a) Values based on acetone.

b) Values based on Raoult's Law and LeChatelier principle.

838AR-P
CARBON CONDUCTIVE PEN
Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures.
Conditions to Avoid	Ignition sources, open flames, excessive heat, and incompatible substances
Incompatibilities	Strong oxidizing agents, strong bases, strong reducing agents, acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information
Summary of Effects and Symptoms by Routes of Exposure

Eyes	Causes redness, pain, blurred vision and eye damage.
Skin	May cause dry skin, redness, rash, and allergic dermatitis.
Inhalation	May cause coughing, sore throat, vomiting, headache, dizziness, drowsiness, and shortness of breath.
Ingestion	May cause abdominal pain, nausea, diarrhea, drowsiness, dizziness, vomiting, and shortness of breath.
Chronic	Prolonged or repeated exposure may cause skin may cause skin dryness and cracking.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
acetone	5 800 mg/kg Rat	20 mL/kg Rabbit ^{a)}	16 000 ppm 4 h Rat ^{a)}
isobutyl acetate	13 413 mg/kg Rat	>17 400 mg/kg Rabbit	Not available

Section continued on the next page

838AR-P
CARBON CONDUCTIVE PEN
Continued...

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
1-butanol	2 292 mL/kg Rat	3 434 mL/kg Rabbit	>17.76 mg/L 4 h Rat
carbon black	>15 g/kg Rat	>3 g/kg Rabbit	Not available
1-methoxy-2-propanol acetate	8 532 mg/kg Rat	>5 g/kg Rabbit	Not available
barium bis(dinonylnaphthalenesulphonate)	>15 800 mg/kg Rat	>7 940 mg/kg Rabbit	Not available

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDSs were also consulted.

Other Toxicological Effects
Skin Corrosion/Irritation

Based on available data, the classification criteria are not met.

Serious Eye Damage/Irritation

1-butanol causes serious eye damage.

Sensitization

(allergic reactions)

Barium bis(dinonylnaphthalenesulphonate) can cause an allergic skin reaction.

Carcinogenicity

(risk of cancer)

The carbon black [CAS# 1333-86-4] is possibly carcinogenic by airborne routes of exposures under WHMIS 2015 and HCS 2012.

Carbon Black [CAS# 1333-86-4]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A4: Not classified as a human carcinogen

CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size)

NTP: Not listed

Mutagenicity

(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

Reproductive Toxicity

(risk to sex functions)

Based on available data, the classification criteria are not met.

Teratogenicity (risk of fetus malformation)

Based on available data, the classification criteria are not met.

Section continued on the next page

838AR-P**CARBON CONDUCTIVE PEN****STOT-Single Exposure**

Acetone, isobutyl acetate and 1-butanol can affect the central nervous system by inhalation causing drowsiness or dizziness.

STOT-Repeated Exposure

Based on available data, the classification criteria are not met.

Aspiration Hazard

Based on available data, the classification criteria are not met.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

None of the ingredients are classified as an environmental hazard according to GHS criteria.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

Other Effects

Regulated Volatile Organic Compounds (VOC) content according to the US (EPA) and Canadian (CEPA) authorities.

Actual VOC = 58% (519 g/L)

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

838AR-P**CARBON CONDUCTIVE PEN****Section 14: Transport Information****Ground**

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Sizes 30 mL and under

838AR-P, 838AR-PCA

Excepted QuantityCode **E2****Air**

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 30 mL and under

838AR-P, 838AR-PCA

Excepted QuantityCode **E2**On air waybill, write:
"Dangerous Goods in Excepted
Quantities".*FOR REFERENCE ONLY***UN number:** UN1263**Shipping Name:** PAINT**Class:** 3**Packing Group:** II**Marine Pollutant:** No**Sea**

Refer to IMDG regulations.

Sizes 30 mL and under

838AR-P, 838AR-PCA

Excepted QuantityCode **E2**In transport document, write:
"Dangerous Goods in Excepted
Quantities".*FOR REFERENCE ONLY***UN number:** UN1263**Shipping Name:** PAINT**Class:** 3**Packing Group:** II**Marine Pollutant:** No

Note: **Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

838AR-P

CARBON CONDUCTIVE PEN

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


USA

Other Classifications

HMIS® RATING

HEALTH:	* 2
FLAMMABILITY:	3
PHYSICAL HAZARD:	1
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains acetone (CAS# 67-64-1) and isobutyl acetate (CAS# 110-19-0), which is subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

Section continued on the next page

838AR-P**CARBON CONDUCTIVE PEN**

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product contains carbon black (airborne, unbound particles of respirable size), which is listed as a carcinogen.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by MG Chemicals' Regulatory Department

Date of Creation 05 November 2020

Supersedes 03 March 2020

Reason for Changes: Added new part number.

Reference

1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

838AR-P**CARBON CONDUCTIVE PEN****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content
Wt	Weight

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses	Manufacturing & Support	Head Office
	1210 Corporate Drive	9347-193rd Street
	Burlington, Ontario, Canada	Surrey, British Columbia, Canada
	L7L 5R6	V4N 4E7

Disclaimer This safety data sheet is provided as an information resource only. M.G. Chemicals, Ltd. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.