

860

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: 860**Other Means of Identification:** Silicone Heat Transfer Compound**Related Part #** 860-4G, 860-60G, 860-150G, 860-1P, 860-3.78L, 860-1G, 860-5GPSW

Recommended Use and Restriction on Use

Use: heat transfer compound**Uses Advised Against:** Not available

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

☎ +1-800-340-0772**Fax** +1-800-340-0773**E-mail** support@mgchemicals.com**Web** www.mgchemicals.com**☎** +1-905-331-1396**Fax** +1-905-331-2682**E-mail** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)USA or CANADA— Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**

(Service access code: 335388)


For emergencies involving the transport of dangerous goods; 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

860
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Hazardous to the Aquatic Environment Chronic	1	Warning	Environment

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H410: Very toxic to aquatic life with long lasting effects
Prevention	Precautionary Statements
P273	Avoid release to the environment.
Response	Precautionary Statements
P391	Collect Spillage.
Disposal	Precautionary Statements
P501	Dispose of contents and container in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Specified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

860
Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
1314-13-2	zinc oxide	70%
112945-52-5	amorphous silica	3%

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305 + P351+ P338
Immediate Symptoms	<i>redness, mild irritation</i>
Response	Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF ON SKIN	P302 + P352
Immediate Symptoms	<i>mild irritation</i>
Response	Wash with plenty of water.
IF INHALED	P304 + P340
Immediate Symptoms	<i>coughing, irritation of the respiratory tract</i>
Delayed Symptoms	If exposed to metal fumes, chills and fever-like symptoms may occur 4-12 hours after exposure.
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	<i>low toxicity: abdominal pain, diarrhea, nausea, vomiting</i>
Response	Rinse mouth. Do NOT induce vomiting.

860

Section 5: Fire Fighting Measures

Extinguishing Media	In case of fire: Use extinguishing media suitable for surrounding materials. Not flammable or combustible, but burns if involved in a fire.
Specific Hazards	When the product is exposed to very high heat such as welding, this may cause harmful zinc oxide fumes. Inhalation of fumes may cause metal fever and irritate the respiratory tract. The flu-like symptoms of metal fume fever may be delayed, occurring 4–12 hours after exposure. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO, CO ₂), metal fumes, zinc oxide (ZnO), and formaldehyde.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing fumes or dust. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment	Not applicable—not readily flowable
Cleaning	Collect waste in a waste container. Wash spill area with soap and water to remove the last traces of residue.
Disposal	Dispose of spill waste according to Section 13.

860
Section 7: Handling and Storage

Prevention	Keep out of reach of children. Avoid breathing dust and fumes. Avoid release to the environment.
Handling	Wear protective gloves, protective clothing, and eye protection. Wash hands thoroughly after handling. Collect spillage.
Storage	Not applicable

Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
zinc oxide (dust/mist)	ACGIH	2 mg/m ³	Not established
	U.S.A. OSHA PEL	2 mg/m ³	10 mg/m ³
	Canada AB	2 mg/m ³	10 mg/m ³
	Canada BC	2 mg/m ³	10 mg/m ³
	Canada ON	2 mg/m ³	10 mg/m ³
	Canada QC	2 mg/m ³	10 mg/m ³
fumes dust	Canada QC	2 mg/m ³	10 mg/m ³
	Canada QC	10 mg/m ³	Not established
amorphous silica	ACGIH	Not established	Not established
	U.S.A. NIOSH	6 mg/m ³	Not established
mineral dust	U.S.A. OSHA PEL	20 mppcf ^{a)}	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH1, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from RTECS2 database and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

(mppcf) Millions of particles per cubic foot air, based on impinge samples counted by light-field technique.

Section continued on the next page

860**Engineering Controls****Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

The zinc oxide and silica dust are bound in the grease matrix and are not available as a respiration hazard under normal conditions.

Personal Protective Equipment**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Ensure that glasses have side shields for lateral protection.

Skin Protection

For likely contacts, use of protective nitrile gloves or other chemically resistant gloves.

Respiratory Protection

For over-exposures up to 10 x OEL of dust and fumes, wear a an approved respirator with particulate filter that meets local, regional, and national standards.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

860
Section 9: Physical and Chemical Properties

Physical State	Solid	Lower Flammability Limit	Not applicable
Appearance	White paste	Upper Flammability Limit	Not applicable
Odor	None	Vapor Pressure @20 °C	Not available
Odor Threshold	Not applicable	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	2.40
Freezing/Melting Point	Not available	Solubility in Water	Insoluble ^{a)}
Initial Boiling Point	>300 °C [>572 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point	260 °C [500 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Not flammable	Viscosity @40 °C	Not applicable

a) Inorganic components are sparingly soluble.

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Ignition sources, excessive heat, and incompatible substances.
Incompatibilities	Strong oxidizing agents, strong acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

860**Section 11: Toxicological Information****Summary of Effects and Symptoms by Routes of Exposure**

Eyes	May cause redness and mild irritation.
Skin	May cause mild skin irritation.
Inhalation	May cause coughing and irritation of the respiratory tract. Inhalation of fumes may cause metal fever and irritate the respiratory tract. The flu-like symptoms of metal fume fever may be delayed, occurring 4-12 hours after exposure.
Ingestion	Low toxicity: abdominal pain, diarrhea, nausea, vomiting
Chronic	Not available

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
zinc oxide	7 950 mg/kg Rat	Not available	2 500 mg/m ³ Mouse 4 h
amorphous silica	3 160 mg/kg Rat	Not available	Not available

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier SDSs were also consulted.

Section continued on the next page

860**Other Toxicological Effects**

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Based on available data, the classification criteria are not met.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Not applicable. There are no category 1 components and the kinematic viscosity of the mixture is >20.5 mm ² /s at 40 °C.

860**Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Contains zinc oxide which is a chronic category 1 solid (non-biodegradable, minimal EC50 of 0.042 mg/L *Pseudokrichneriella subcapita*) that is harmful to the environment.

Based on available data, the polydimethyl siloxane fluid and amorphous silica are not classifiable as ecotoxic hazards according to GHS criteria.

Acute Ecotoxicity

See chronic ecotoxicity

Chronic Ecotoxicity

Category 1

Very toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not readily biodegradable

Other Effects

Exempted volatile organic compounds (VOC) by EPA and CEPA regulations.

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

860

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Sizes under 450 kg
 860-4G, 860-60G, 860-150G,
 860-1P, 860-3.78L, 860-1G

NOT REGULATED in TDG
 per Special Provisions 99

Sizes 5 kg and under

NOT REGULATED in 49 CFR
 per exception 171.4 (c)(2)

Sizes greater than 5 kg (USA)
 860-5GPSW


UN number: UN3077

Shipping Name: ENVIRONMENTALLY
 HAZARDOUS SUBSTANCE, SOLID,
 N.O.S. (zinc oxide)

Class: 9

Packing Group: III

Marine Pollutant: Yes



Special Provision 99 (2): These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

860

Air

Refer to ICAO-IATA regulations.

Sizes 5 kg and under

860-4G, 860-60G, 860-150G,
860-1P, 860-3.78L, 860-1G

NOT REGULATED

On the air waybill, write
"Not Restricted, as per
Special Provisions A197"

Sizes greater than 5 kg

860-5GPSW


UN number: UN3077

Shipping Name: ENVIRONMENTALLY
HAZARDOUS SUBSTANCE, SOLID,
N.O.S. (zinc oxide)

Class: 9

Packing Group: III

Marine Pollutant: Yes



Special Provision A197: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Section continued on the next page

860

Sea


Refer to IMDG regulations.

Sizes 5 kg and under
 860-4G, 860-60G, 860-150G,
 860-1P, 860-3.78L, 860-1G

NOT REGULATED
 per 2.10.2.7

Sizes greater than 5 kg
 860-5GPSW

UN number: UN3077
Shipping Name: ENVIRONMENTALLY
 HAZARDOUS SUBSTANCE, SOLID,
 N.O.S.
 (zinc oxide)
Class: 9
Packing Group: III
Marine Pollutant: Yes



2.10.2.7: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.


Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

Section continued on the next page

860**USA****Other Classifications****HMIS® RATING**

HEALTH:	1
FLAMMABILITY:	0
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains zinc compounds which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity)

This product does not contain any of the listed substances.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

860**Section 16: Other Information**

SDS Prepared by Regulatory Department
Date of Issue 26 February 2020
Supersedes 09 January 2020
Reason for Changes: Amended transport section and emergency response contact.

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content
Wt	Weight

Section continued on the next page

860

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses	Manufacturing & Support	Head Office
	1210 Corporate Drive	9347-193rd Street
	Burlington, Ontario, Canada	Surrey, British Columbia, Canada
	L7L 5R6	V4N 4E7

Disclaimer This safety data sheet is provided as an information resource only. M.G. Chemicals, Ltd. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.