


THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO RF INDUSTRIES,
 ANY UNAUTHORIZED USE OF THIS DRAWING IS EXPRESSLY PROHIBITED
 WITHOUT WRITTEN PERMISSION FROM RF INDUSTRIES.
 ANY VIOLATION IS PUNISHABLE UNDER U.S. COPYRIGHT LAWS.

ALL DIMENSIONS ARE REFERENCE ONLY


PART NO.

RFE-6050-C2




REV	DESCRIPTION	DWN	DATE	APPROVED
-	ENGINEERING RELEASE	DM	9/7/17	JDMc



RECOMMENDED CRIMP DIE: .068



RECOMMENDED CRIMP DIE: .213



RECOMMENDED STRIPPING DIMS

SPECIFICATIONS:

IMPEDANCE: 50 OHMS
 FREQUENCY RANGE: 0-2 GHz
 WORKING VOLTAGE RATING: 335 VRMS
 TEMPERATURE RANGE: -65°C TO 165°C
 FOR: LMR-200, BELDEN 7807A, COMMSCOPE WBC-200

1	BODY	1	BRASS	NICKEL, 100μ"
2	INSULATOR	1	DELTRIN	---
3	BACK NUT	1	BRASS	GOLD, 30μ"
4	PIN	1	BRASS	NICKEL, 100μ"
5	FERRULE	1	BRASS	NICKEL, 100μ"
6				
7				
8				
9				
10				
11				
12				
13				
14				

DRAWN	JDM	3/5/18
CHECKED		
ORJ DRAWN	C. ZUNIGA	4/24/00

UNLESS OTHERWISE SPECIFIED:
 1. REMOVE ALL BURRS
 2. BREAK ALL CORNERS & EDGES .005 R. MAX.
 3. CHAMFER 1ST & LAST THREADS 45°
 4. SURFACE ROUGHNESS 63 FINISH MIL-STD-10
 5. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN .002 T.I.R.
 6. ALL DIMENSIONS ARE AFTER PLATING.

DIMENSIONS ARE IN INCHES AND [MILLIMETERS]
 UNLESS OTHERWISE NOTED TOLERANCES ARE:
 DECIMALS .XXX±.003 [.08]
 .XX±.005 [.13]
 DIAMETER .XXX±.001 [.03]
 .XX±.003 [.08]

RFconnectors
 DIVISION OF RF INDUSTRIES, LTD.

7610 MIRAMAR RD
 SAN DIEGO, CA 92126
 (858) 549-6340
 (858) 549-6345 FAX

FME JACK CRIMP

SIZE	CABLE GROUP	DWG NO.	REV
A	C2	RFE-6050-C2	-
SCALE:	NTS	CAD FILE	OUTLINE
SHEET			1 OF 1