08-	unting Option #4-40 Unified Threaded Inserts	Contact Detail 500-Wire Hole .087x.013(2.21x0.33) - Tail LG.=.282(7.16) .156 [3.96] Contact Spacing x .140 [3.56] Row Spacing	THIS IS A C.A.D. GENERATEI DO NOT MAKE MANUAL REVI	D DRAWING SIONS TO MAS	STER.	ISSUE NUM ORIGINA	
	Card Slot Accepts054 (1.37) to .070 (1.78) Thick P.C. Board						
\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\							
	0.156[3.96]	6.248[158.70]					
		6.394[162.41] ————————————————————————————————————	-				
						8.38] d Slot	
						0.330 [8.38] Card Slot	
	A						
1					<u> </u>	_'	
				Ī			
460[11.68]	-	6.990[177.55]	-		0.125[3.18]	SECTION	۱ A-A
0.46			305 / 315 / 355 Card Edge Connector Part Number: 305-078-500-508		ACAD REFERENCE DRAWN: J.LEE CHECKED:	DATE: SEI	PT. 21/09
	See Accompanying Page for: Mounting Options	EDAC TORONTO, CANA	ONTARIO ARE THE PROPERTY OF EDA SHALL NOT BE REPRODUCE	AC INC.,AND D,OR COPIED OR THE	SCALE: NTS DRAWING NUMBER	SHEET	1 OF 2
		YOUR CONNECTION TO QUALITY &	SERVICE WITHOUT WRITTEN PERMISSI		305 Assemb	У	

