Contact Dimensions: 520-P.C. Tail .030x.018(0.76x0.46) - Tail LG=.175(4.45) .100 (2.54) Contact Spacing x .200 (5.08) Row Spacing 1 -2x Ø.156[3.96] CARD SLOT ACCEPTS .054" [1.37] TO .070"[1.78] THICK PCB -6.100 [154.94] -6.260[159]--6.575 [167.01] 160 [4.06] POINT OF CONTACT 330[8.38] CARD SLOT .175 4.45 **SECTION A-A** 600 [15.24]

INSULATOR MATERIAL: THERMOPLASTIC PBT BLACK, UL 94V-0 CONTACT MATERIAL; COPPER TIN ALLOY

CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING ON THE CONTACT TAILS, NICKEL UNDERPLATE

345/395 SE	RIES CARD EDGE CONNECT	TOR
PART NUM	3FR: 395-120-520-278	

YOUR CONNECTION TO QUALITY & SERVICE

-6.835[173.61]

ACAD REFERENCE NO. 345-ENG-MASTER				
DRAWN: R.STA.MONICA	DATE:MAY.16/2017			
CHECKED:	DATE:			
SCALE: 1:1	SHEET '	OF 2		
DRAWING NUMBER	•	ISSUE		
345-ENG-MASTER	1			









**Contact Code 558** 

Contact Code 559

**Contact Code 560** 

INSULATOR MATERIAL: THERMOPLASTIC POLYESTER, UL 94V-0

DAP MATERIAL AVAILABLE UPON REQUEST

CONTACT MATERIAL; COPPER ALLOY CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING ON THE CONTACT TAILS, NICKEL UNDERPLATE

345/395 SERIES CARD EDGE CONNECTOR CONTACT CODE 555,556,558,559,560 DIMENSIONS

YOUR CONNECTION TO QUALITY & SERVICE

ACAD REFERENCE NO. 345-ENG-MASTER DATE:MAY.16/2017 DRAWN: R.STA.MONICA 1:1 SHEET 2 OF 2

345-ENG-MASTER