
2 CONTACTS WHITE FEMALE HOUSING FOR WIRE INSULATION Ø1.30 TO Ø1.70


UNLESS O	UNLESS OTHERWISE SPECIFIED		
.X	±0.38		
.XX	±0.25		
.XXX	±0.13		

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER
ORIGINAL 1





ISO 1:1





15.00

NOTE:

ELECTRICAL SPECIFICATIONS:

VOLTAGE RATING: 250V MAX. CURRENT RATING: 3A per CONTACT CONTACT RESISTANCE: $15m\Omega$ MAX. INSULATOR RESISTANCE: $1000M\Omega$ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC(RMS) OPERATING TEMPERATURE: -40 °C ~ 105 °C

MATERIAL & FINISH:

HOUSING: PBT, UL94V-0

CONTACTS: PHOSPHOR BRONZE, TIN PLATED

SEALS: SILICONE RUBBER

			ACAD REFERENCE NO.: 560 Assembly			
560 SERIES WATERPROOF CONNECTOR		DRAWN: C.B	DATE: July 23, 20	20		
			DATE:			
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: 2:1	SHEET 1 OF	1		
CANADA OR USED AS THE BASIS FOR TI MANUFACTURE OR SALE OF A	SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 560 Asse	embly	ISSUE		
	MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER: 560-002-	000-211	1		



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.