

SECTION X-X

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL (1)

MATERIALS:

HOUSING: PBT, UL94V-0

2. TERMINAL: PHÖSPHOR BRONZE TIN PLATED

SPECIFICATIONS

1. PITCH: 5.8MM

2. RATED VOLTAGE: 300V

3. RATED CURRENT: 10A MAX

4. WITHSTAND VOLTAGE: AC1700V R.M.S.


5. CONTACT RESISTANCE: 10 MOHMS MAX INSULATION RESISTANCE:

1000 MOHMS MIN/DC 500V

7. TEMPERATURE RANGE: -40°C ~ +105°C

B. WATERPROOF GRADE: TESTED AND

CERTIFIED TO IP67



RECOMMENDED PCB HOLE LAYOUT

ITEM NO.	DESCRIPTION	QTY.
1	570-003-420-101_Housing	1
2	570-003-420-101_Pin	3

Waterproof Connector, Plug, 3 Pin, Board Mount 570-003-420-101

ACAD REFERENCE NO. 570-003-420-101

DRAWN:R.STA.MONICA DATE: OCT.15/10

CHECKED: DATE:

SCALE: NOT TO SCALE SHEET 1 OF 1

DRAWING NUMBER ISSUE

EDNG

EDAC INC TORONTO, ONTARIO

CANADA

YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

RAWING NUMBER IS 570-003-420-101



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2002/95/EC AND 2002/96/EC FOR RoHS COMPLIANCY