

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

STEEL, NICKEL PLATED SHELL:

CONTACT: COPPER ALLOY, 30µ GOLD PLATING

OPERATING TEMPERATURE: -55°C TO +125°C

CURRENT RATING: 3A PER CONTACT

CONTACT RESISTANCE: $25m\Omega$ MAX. **INSULATOR RESISTANCE:** 5000MΩ min.

DIELECTRIC

WITHSTANDING VOLTAGE: 1000V AC rms

$\begin{bmatrix} 0.100 \pm 0.010 \\ 2.54 \pm 0.25 \end{bmatrix}$ $[0.100 \pm 0.010]$ 11.43 ± 0.25 54 0.045 1.14 [0.090]2.29

634 SERIES D-SUB CONNECTOR

YOUR CONNECTION TO QUALITY & SERVICE

EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

SW REFERENCE NO.: 634 ASSEMBLY	
DRAWN: C.B	DATE: AUG. 01/2018
CHECKED:	DATE:
SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 1
DRAWING NUMBER: 634-026-6	663-512 ISSUE

PART NUMBER: 634-026-663-512

ISSUE NUMBER

ORIGINAL

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.