



# PRODUCT SPECIFICATION

## TITLE

### Cellular Quad Band Flex Antenna

#### TABLE OF CONTENTS

- 1.0 SCOPE
- 2.0 PRODUCT DESCRIPTION
- 3.0 APPLICABLE DOCUMENTS AND SPECIFICATIONS
- 4.0 RATINGS
- 5.0 PERFORMANCE
- 6.0 TEST GROUPINGS
- 7.0 PACKING
- 8.0 CHANGE HISTORY

|  |   |  |                            |
|--|---|--|----------------------------|
| REVISION:<br><b>B</b>                    | ECR/ECN INFORMATION:<br>EC No: 726689<br>DATE: 2022/10/31 | TITLE:<br><b>Cellular Quad Band Flex Antenna</b> | SHEET No.<br><b>1 of 8</b> |
| DOCUMENT NUMBER:<br><b>PS-146185-100</b> | CREATED / REVISED BY:<br>Colin. Xu                        | CHECKED BY:<br>Stary.Song                        | APPROVED BY:<br>Welson Tan |



# PRODUCT SPECIFICATION

## Cellular Quad Band Flex Antenna

### 1.0 SCOPE

This Product Specification covers the mechanical, electrical and environmental performances requirements and test methods for Cellular Quad Band Flex Antenna with solder cable.

### 2.0 PRODUCT DESCRIPTION

#### 2.1 PRODUCT NAME AND SERIES NUMBER (S)

Product name: Cellular Quad Band Flex Antenna-1461850100

#### 2.2 Design and Construction

Antenna construction and physical dimensions specified on the applicable sales drawing.

#### 2.3 Materials

- a) Flex: Refer to sales drawing of 1461850100
- b) Cable Line: Refer to sales drawing of 1461850100
- c) Connector : Refer to sales drawing of 1461850100

### 3.0 APPLICABLE DOCUMENTS AND SPECIFICATIONS

See drawings and other sections of this specification for the relevant reference documents. In cases where the specification differs from the drawings, the drawings take precedence.

### 4.0 RATINGS

#### 4.1 RF POWER

2 WATTS MAX

#### 4.2 TEMPERATURE

Operating: - 30°C to 85°C  
 Storage : - 40°C to 95°C

#### 4.3 HUMIDITY

Operating: -30°C to 85°C  
 -30°C to 50°C, 85%RH or less  
 50°C to 85°C, 60%RH or less

Storage : -40°C to 95°C  
 -40°C to 50°C, 85%RH or less  
 50°C to 95°C, 60%RH or less

|  |   |  |                            |
|--|---|--|----------------------------|
| REVISION:<br><b>B</b>                    | ECR/ECN INFORMATION:<br>EC No: 726689<br>DATE: 2022/10/31 | TITLE:<br><b>Cellular Quad Band Flex Antenna</b> | SHEET No.<br><b>2 of 8</b> |
| DOCUMENT NUMBER:<br><b>PS-146185-100</b> | CREATED / REVISED BY:<br>Colin. Xu                        | CHECKED BY:<br>Stary.Song                        | APPROVED BY:<br>Welson Tan |



# PRODUCT SPECIFICATION

## 5.0 PERFORMANCE

### 5.1 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 50mm (1461850050)

| DESCRIPTION      | TEST CONDITION  | REQUIREMENTS  |                |
|------------------|---|---------------|----------------|
|                  |   | 824MHz~960MHz | 1.71GHz~2.7GHz |
| Frequency Range  | 0.824GHz~2.7GHz   | 824MHz~960MHz | 1.71GHz~2.7GHz |
| Return Loss      | Antenna loaded on PC/ABS housing (thickness 1mm) with 100mm 1.13mm diameter micro coaxial cable<br>Measured by VNA5071C | < -4 dB       | < -4 dB        |
| Peak Gain        | Measure antenna on recommended PC/ABS housing through OTA chamber   | 1.5dBi        | 3.2dBi         |
| Total Efficiency | Measure antenna on recommended PC/ABS housing through OTA chamber   | >61%          | >67%           |
| Polarization     | Measure antenna on recommended PC/ABS housing through OTA chamber   | Linear        |                |
| Input Impedance  | Measure antenna on recommended PC/ABS housing through VNA E5071C  | 50 Ohms       |                |

### 5.2 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 100mm (1461850100)

| DESCRIPTION      | TEST CONDITION  | REQUIREMENTS  |                |
|------------------|---|---------------|----------------|
|                  |   | 824MHz~960MHz | 1.71GHz~2.7GHz |
| Frequency Range  | 0.824GHz~2.7GHz   | 824MHz~960MHz | 1.71GHz~2.7GHz |
| Return Loss      | Antenna loaded on PC/ABS housing (thickness 1mm) with 100mm 1.13mm diameter micro coaxial cable<br>Measured by VNA5071C | < -4 dB       | < -4 dB        |
| Peak Gain        | Measure antenna on recommended PC/ABS housing through OTA chamber   | 1.4 dBi       | 3 dBi          |
| Total Efficiency | Measure antenna on recommended PC/ABS housing through OTA chamber   | >60%          | >65%           |
| Polarization     | Measure antenna on recommended PC/ABS housing through OTA chamber   | Linear        |                |
| Input Impedance  | Measure antenna on recommended PC/ABS housing through VNA E5071C  | 50 Ohms       |                |

|                      |                                   |  |                   |
|----------------------|-----------------------------------|--|-------------------|
| REVISION:            | ECR/ECN INFORMATION:              | TITLE:                                 | SHEET No.         |
| <b>B</b>             | EC No: 726689<br>DATE: 2022/10/31 | <b>Cellular Quad Band Flex Antenna</b> | <b>3 of 8</b>     |
| DOCUMENT NUMBER:     | CREATED / REVISED BY:             | CHECKED BY:                            | APPROVED BY:      |
| <b>PS-146185-100</b> | <b>Colin. Xu</b>                  | <b>Stary.Song</b>                      | <b>Welson Tan</b> |



# PRODUCT SPECIFICATION

## 5.3 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 150mm (1461850150)

| DESCRIPTION      | TEST CONDITION  | REQUIREMENTS  |                |
|------------------|---|---------------|----------------|
| Frequency Range  | 0.824GHz~2.7GHz   | 824MHz~960MHz | 1.71GHz~2.7GHz |
| Return Loss      | Antenna loaded on PC/ABS housing (thickness 1mm) with 100mm 1.13mm diameter micro coaxial cable<br>Measured by VNA5071C | < -4 dB       | < -4 dB        |
| Peak Gain        | Measure antenna on recommended PC/ABS housing through OTA chamber   | 1.3 dBi       | 2.8 dBi        |
| Total Efficiency | Measure antenna on recommended PC/ABS housing through OTA chamber   | >58%          | >62%           |
| Polarization     | Measure antenna on recommended PC/ABS housing through OTA chamber   | Linear        |                |
| Input Impedance  | Measure antenna on recommended PC/ABS housing through VNA E5071C  | 50 Ohms       |                |

## 5.4 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 200mm (1461850200)

| DESCRIPTION      | TEST CONDITION  | REQUIREMENTS  |                |
|------------------|---|---------------|----------------|
| Frequency Range  | 0.824GHz~2.7GHz   | 824MHz~960MHz | 1.71GHz~2.7GHz |
| Return Loss      | Antenna loaded on PC/ABS housing (thickness 1mm) with 100mm 1.13mm diameter micro coaxial cable<br>Measured by VNA5071C | < -4 dB       | < -4 dB        |
| Peak Gain        | Measure antenna on recommended PC/ABS housing through OTA chamber   | 1.2dBi        | 2.7dBi         |
| Total Efficiency | Measure antenna on recommended PC/ABS housing through OTA chamber   | >57%          | >60%           |
| Polarization     | Measure antenna on recommended PC/ABS housing through OTA chamber   | Linear        |                |
| Input Impedance  | Measure antenna on recommended PC/ABS housing through VNA E5071C  | 50 Ohms       |                |

|                      |                                   |  |                   |
|----------------------|-----------------------------------|--|-------------------|
| REVISION:            | ECR/ECN INFORMATION:              | TITLE:                                 | SHEET No.         |
| <b>B</b>             | EC No: 726689<br>DATE: 2022/10/31 | <b>Cellular Quad Band Flex Antenna</b> | <b>4 of 8</b>     |
| DOCUMENT NUMBER:     | CREATED / REVISED BY:             | CHECKED BY:                            | APPROVED BY:      |
| <b>PS-146185-100</b> | <b>Colin. Xu</b>                  | <b>Stary.Song</b>                      | <b>Welson Tan</b> |



# PRODUCT SPECIFICATION

## 5.5 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 250mm (1461850250)

| DESCRIPTION      | TEST CONDITION  | REQUIREMENTS  |                |
|------------------|---|---------------|----------------|
|                  |   | 824MHz~960MHz | 1.71GHz~2.7GHz |
| Frequency Range  | 0.824GHz~2.7GHz   | 824MHz~960MHz | 1.71GHz~2.7GHz |
| Return Loss      | Antenna loaded on PC/ABS housing (thickness 1mm) with 100mm 1.13mm diameter micro coaxial cable<br>Measured by VNA5071C | < -4 dB       | < -4 dB        |
| Peak Gain        | Measure antenna on recommended PC/ABS housing through OTA chamber   | 1dBi          | 2.5dBi         |
| Total Efficiency | Measure antenna on recommended PC/ABS housing through OTA chamber   | >56%          | >58%           |
| Polarization     | Measure antenna on recommended PC/ABS housing through OTA chamber   | Linear        |                |
| Input Impedance  | Measure antenna on recommended PC/ABS housing through VNA E5071C  | 50 Ohms       |                |

## 5.6 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 300mm (1461850300)

| DESCRIPTION      | TEST CONDITION  | REQUIREMENTS  |                |
|------------------|---|---------------|----------------|
|                  |   | 824MHz~960MHz | 1.71GHz~2.7GHz |
| Frequency Range  | 0.824GHz~2.7GHz   | 824MHz~960MHz | 1.71GHz~2.7GHz |
| Return Loss      | Antenna loaded on PC/ABS housing (thickness 1mm) with 100mm 1.13mm diameter micro coaxial cable<br>Measured by VNA5071C | < -4 dB       | < -4 dB        |
| Peak Gain        | Measure antenna on recommended PC/ABS housing through OTA chamber   | 0.9dBi        | 2.3dBi         |
| Total Efficiency | Measure antenna on recommended PC/ABS housing through OTA chamber   | >55%          | >56%           |
| Polarization     | Measure antenna on recommended PC/ABS housing through OTA chamber   | Linear        |                |
| Input Impedance  | Measure antenna on recommended PC/ABS housing through VNA E5071C  | 50 Ohms       |                |

|                      |                                   |  |                   |
|----------------------|-----------------------------------|--|-------------------|
| REVISION:            | ECR/ECN INFORMATION:              | TITLE:                                 | SHEET No.         |
| <b>B</b>             | EC No: 726689<br>DATE: 2022/10/31 | <b>Cellular Quad Band Flex Antenna</b> | <b>5 of 8</b>     |
| DOCUMENT NUMBER:     | CREATED / REVISED BY:             | CHECKED BY:                            | APPROVED BY:      |
| <b>PS-146185-100</b> | <b>Colin. Xu</b>                  | <b>Stary.Song</b>                      | <b>Welson Tan</b> |



# PRODUCT SPECIFICATION

## 5.7 CABLE LOSS

| ITEM  | DESCRIPTION     | TEST CONDITION                | REQUIREMENT    |                |           |           |
|-------|-----------------|-------------------------------|----------------|----------------|-----------|-----------|
| 5.7.1 | Frequency Range | 824MHz~6GHz                   | 824MHz~960 MHz | 1.7GHz~2.7 GHz | 3GHz~5GHz | 5GHz~6GHz |
| 5.7.2 | Attenuation     | 1m cable measured by VNA5071C | ≤1.8dB/m       | ≤3.5dB/m       | ≤4dB/m    | ≤5dB/m    |

## 5.8 CABLE LENGTH AFFECT THE ANTENNA PERFORMANCE

Balance antenna resonance is insensitive by cable's length, but the cable's loss will affect the total Efficiency. Refer to 5.7

## 5.9 MECHANICAL REQUIREMENTS

| ITEM  | DESCRIPTION | TEST CONDITION   | REQUIREMENT     |
|-------|-------------|--|-----------------|
| 5.9.1 | Pull test   | Test machine : Max intelligent load tester<br>Stick the flex antenna in a PC block, pull cable in horizontal direction | Pull force >8 N |

## 5.10 ENVIRONMENTAL REQUIREMENTS

| ITEM   | DESCRIPTION                   | TEST CONDITION  | REQUIREMENT   |
|--------|-------------------------------|---|---|
| 5.10.1 | Temperature /Humidity cycling | Test condition:<br>1) The device under test is kept for 30 mins in an environment with a temperature of -40 °C.<br>2) Kept for 4 Hours in an environment with a temperature of 85 degrees and a relative humidity of 95%.<br>3) Kept for 2 Hours in an environment with a temperature of 125 degrees and a relative humidity of 95%.<br>4) The cycle is repeated until a total of 40 cycles have been completed. Hereafter the conditions are stabilized at room temperature. | 1) Parts should meet RF spec before and after test.<br>2) No cosmetic problem |
| 5.10.2 | Temperature Shock             | Test condition:<br>The device under test at -40 °C ↔ 125 °C by 100 cycles, Dwell of 30 mins, transition time between Dwell 30 secs (~ 61 mins / cycle ) and each item should be measured after exposing them in normal temperature and humidity for 24 h.   | 1) Parts should meet RF spec before and after test.<br>2) No cosmetic problem |

|                      |                                   |  |                   |
|----------------------|-----------------------------------|--|-------------------|
| REVISION:            | ECR/ECN INFORMATION:              | TITLE:                                 | SHEET No.         |
| <b>B</b>             | EC No: 726689<br>DATE: 2022/10/31 | <b>Cellular Quad Band Flex Antenna</b> | <b>6 of 8</b>     |
| DOCUMENT NUMBER:     | CREATED / REVISED BY:             | CHECKED BY:                            | APPROVED BY:      |
| <b>PS-146185-100</b> | <b>Colin. Xu</b>                  | <b>Stary.Song</b>                      | <b>Welson Tan</b> |



# PRODUCT SPECIFICATION

|        |                  |  |   |
|--------|------------------|--|---|
| 5.10.3 | High Temperature | Test condition:<br>1) Temperature:125°C, time:1008hours<br>2) There is no substantial obstruction to air flow across and around the samples, and the samples are not touching each other   | 1) Parts should meet RF spec before and after test.<br>2) No cosmetic problem                         |
| 5.10.4 | Salt mist test   | 1. Test condition:<br>The device under test is exposed to a spray of a 5% (by volume) resolution of NaCL in water for 2 hours. Thereafter the device under test is left for 1 week in room temperature at a relative humidity of 95%. The cycle is repeated until a total of 2 cycles have been completed. Here after the conditions are stabilized at room temperature. | 1) Parts should meet RF spec before and after test.<br>2) No visible corrosion, discoloration accept. |

The meaning of text “No Cosmetic Problem” in the table above is:

- a. No soldering problem
- b. No adhesion problem of glue
- c. Cable & connector assembly orientation rotates 20°Max

## 6.0 TEST GROUPINGS

| Test Item       | Description                   | Group1 | Group2 | Group3 | Group4 | Group5 |
|-----------------|-------------------------------|--------|--------|--------|--------|--------|
| 5.9.1           | Pull test                     | X      |        |        |        |        |
| 5.10.1          | Temperature /Humidity cycling |        | X      |        |        |        |
| 5.10.2          | Temperature Shock             |        |        | X      |        |        |
| 5.10.3          | High Temperature              |        |        |        | X      |        |
| 5.10.4          | Salt mist test                |        |        |        |        | X      |
| Sample Quantity |                               | 5      | 5      | 5      | 5      | 5      |

## 7.0 PACKAGING

Refer to Molex packaging drawing of 1461850100

|  |   |  |                                   |
|--|---|--|-----------------------------------|
| REVISION:<br><br><b>B</b>                | ECR/ECN INFORMATION:<br>EC No: 726689<br>DATE: 2022/10/31 | TITLE:<br><br><b>Cellular Quad Band Flex Antenna</b> | SHEET No.<br><br><b>7 of 8</b>    |
| DOCUMENT NUMBER:<br><b>PS-146185-100</b> | CREATED / REVISED BY:<br><b>Colin. Xu</b>                 | CHECKED BY:<br><b>Stary.Song</b>                     | APPROVED BY:<br><b>Welson Tan</b> |



# PRODUCT SPECIFICATION

## 8.0 CHANGE HISTORY

| REV | DATA       | DESCRIPTION   |
|-----|------------|---|
| B   | 2022/10/31 | Update the efficiency and gain values of Part 5 to be consistent with AS. |

|   |  |   |                                   |
|---|--|---|-----------------------------------|
| <b>REVISION:</b><br><b>B</b>                    | <b>ECR/ECN INFORMATION:</b><br>EC No: 726689<br>DATE: 2022/10/31 | <b>TITLE:</b><br><b>Cellular Quad Band Flex Antenna</b> | <b>SHEET No.</b><br><b>8 of 8</b> |
| <b>DOCUMENT NUMBER:</b><br><b>PS-146185-100</b> | <b>CREATED / REVISED BY:</b><br>Colin. Xu                        | <b>CHECKED BY:</b><br>Stary.Song                        | <b>APPROVED BY:</b><br>Welson Tan |