	13	12		11		10	9	8	7	6
	MATERIAL NUMBER				NUMBER FINIS		ISHED LENGTH			
J	12000868524		40	)3007K05	K05M010 1M +55.6		6mm -0 [3.3FT. +2.2IN -0]			
	12000868525		4(	)3007K05	5M02	O 2M +55.	6mm -0 [6.6F	T. +2.2IN -0]		
	12000868526 403007			)3007K05	K05M050 5M +55.6mm -0 [16.4FT. +2.2IN -0]					
	12000868527		4(	)3007K05	<pre>&lt;05M100 10M +55.6mm -0 [32.8FT. +2.2IN -0]</pre>					
I										
•									- FINISHED LE	NGTH –
						4	_ 4.0" REF		-	
Н	[102mm]									
	.9" REF.									
	[22mm]									
G				4						
	.9" REF.									
F										
	Ø.4" REF M8 x 1									
Е	[10mm]									
D										
	SPECIFICATI	1								
С	COMPONENT MATERIAL						_			cable typ
	LABEL MYLAR COUPLER BRASS					K/YELLOW	_		:	#22/3C /
	COUPLER BRASS CONTACT COPPER ALLOY					OVER Ni	-			TPE YE
	INSERT PUR					NCK	_			
В	OVERMOLD TPE				YEL	LOW				
	CABLE	ABLE TPE			YEL	LOW			ଞ୍ଚାର QUALITY	GENEF (UNLI
	VOLTAGE RATING:				60VA	C/75VAC			2013/10/09 SAMBOT	,
	AMPERAGE RATING:				4A			3E 557		4 PLACES 3 PLACES
A	PROTECTION CLASS:				P 67			RELEASE PG2014-0657		2 PLACES 1 PLACE
	OPERATING TEMPERATURE:				20°C	/ 80°C			: GGL	Al
	UL CERTIFICATION:				FILE	NO. E152210		ÖN ()	DRWN: ( CH'KD: APPR: I	DR A
	CSA CERTIFICATIONS:				FILE	NO. LR6837				A ML WITHI
	13	12		11		10	9	8	7	6

