



- NOTES:
1. MATERIALS: HOUSING - LIQUID CRYSTAL POLYMER (LCP), GLASS-FILLED, UL94V-0  
TERMINALS - HIGH PERFORMANCE COPPER ALLOY
  2. FINISH: 30μIN MIN GOLD IN CONTACT AREA, SELECTIVE TIN ON PCB TAILS, NICKEL OVERALL.
  3. REFER TO MOLEX PRODUCT SPEC PS-76060-999 FOR PERFORMANCE SPECIFICATIONS AND ADDITIONAL PCB INFORMATION.
  4. EACH SIGNAL WAFER CONTAINS 2 COLUMNS OF TERMINALS.
  5. PRODUCT IS PACKAGED PER PK-70873-589.
  6. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPEC PS-45499-002.
  7. REFER TO MOLEX SALES DRAWING SD-76145-002 FOR THE MATING HEADERS AND SD-76560-002 FOR THE MATING RAM CONNECTORS.
  8. REFER TO MOLEX ROUTING GUIDE AS-76060-990 FOR ANTIPAD AND ROUTING RECOMMENDATIONS.
  9. PART NUMBER 76150-3020 SHOWN ON DRAWING. KEYING FEATURES WILL CHANGE WITH COLUMN SIZE.
  10. MINIMUM BOARD THICKNESS IS 1.00 mm FOR COMPLIANT PIN FUNCTIONALITY.
  11. WHEN USING MOLEX SUPPLIED #2-32 SCREW 73726-0000 (9.50mm ±0.38 THREADABLE SCREW LENGTH), THE MAXIMUM BOARD THICKNESS IS 4.4mm.
  12. MARKING: LOCATED APPROXIMATELY AS SHOWN. PART NUMBER AND DATE CODE.

DAUGHTERCARD HOLE PATTERN (CONNECTOR SIDE)

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
DIMENSION UNITS	SCALE	CURRENT REV DESC: MIGRATED TO NX	
mm	NTS		
GENERAL TOLERANCES (UNLESS SPECIFIED)			
ANGULAR TOL	± 0.5°	EC NO: 622829	
4 PLACES	±	DRWN: PKH	2019/08/22
3 PLACES	±	CHK'D: BOKOK	2019/08/29
2 PLACES	± 0.13	APPR: SHONG	2019/08/30
1 PLACE	± 0.25	INITIAL REVISION:	
0 PLACES	±	DRWN: MCARRANZA	2007/06/11
		APPR: JLAURX	2008/04/24
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIRD ANGLE PROJECTION	DRAWING	SERIES
		C-SIZE	76150
		MATERIAL NUMBER	CUSTOMER
		SEE CHART	GENERAL MARKET
		DOCUMENT NUMBER	DOC TYPE   DOC PART   REVISION
		SD-76150-002	PSD   001   H3
		SHEET NUMBER	1 OF 2

MATERIAL NUMBER	# OF COLUMNS	# OF DIFF PAIR	DIM "A" MAX	DIM "B"	PTH $\phi$
76150-**10	10	60	26.60	17.10	0.46 $\pm 0.05$
76150-**14	14	84	34.20	24.70	
76150-**16	16	96	38.00	28.50	
76150-**20	10	60	26.60	17.10	0.39 $\pm 0.05$
76150-**24	14	84	34.20	24.70	
76150-**26	16	96	38.00	28.50	

76150-\*\*\*\*

3 = LEFT GUIDED LEAD-FREE

POLARIZATION KEY ORIENTATION

0 = NO KEY

1 = A      5 = E  
 2 = B      6 = F  
 3 = C      7 = G  
 4 = D      8 = H

# OF COLUMNS

10 = 10 COL 0.46 PTH  
 14 = 14 COL 0.46 PTH  
 16 = 16 COL 0.46 PTH  
 20 = 10 COL 0.39 PTH  
 24 = 14 COL 0.39 PTH  
 26 = 16 COL 0.39 PTH

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS		SCALE		CURRENT REV DESC: MIGRATED TO NX		<b>molex</b>			
mm		NTS							
GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 622829		IMPACT 100 OHM DC 6 PAIR SIGNAL MODULE GUIDE LEFT SALES DWG			
ANGULAR TOL $\pm 0.5^\circ$				DRWN: PKH 2019/08/22					
4 PLACES $\pm$				CHK'D: BOKOK 2019/08/29		PRODUCT CUSTOMER DRAWING			
3 PLACES $\pm$				APPR: SHONG 2019/08/30					
2 PLACES $\pm 0.13$				INITIAL REVISION:		DOCUMENT NUMBER			
1 PLACE $\pm 0.25$				DRWN: MCARRANZA 2007/06/11					
0 PLACES $\pm$				APPR: JLAURX 2008/04/24		DOC TYPE			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION					
				DRAWING		REVISION			
				SERIES					
				C-SIZE		CUSTOMER			
				76150					
						SEE CHART			
						2 OF 2			

DOCUMENT STATUS	P1	RELEASE DATE	2019/08/30	15:04:20
-----------------	----	--------------	------------	----------