

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0622018790](#)
Status: **Active**
Overview: [Application Tooling](#)
Description: Backplane Press-In Tool

Documents:

[RoHS Certificate of Compliance \(PDF\)](#)


General

Product Family	Application Tooling
Series	207123
Comments	See Tooling Specification (PDF) Above
Function	Insertion
Geographic Area	Global
Level of Automation	Manual
More Detailed Tech Information	applicationtooling@molex.com
Overview	Application Tooling
Product Name	Impact
Tool Type	Press-Fit Insertion Tool
UPC	884982515550
Warranty Disclaimer	CAUTION: Molex tooling crimp specifications are valid only when used with Molex terminals and tooling manufactured by Molex and sold by Molex or authorized distributors ("Molex Tooling"). When using tooling other than Molex Tooling with Molex specific connector systems listed in our ATS documents, the Molex tooling qualification does not apply and the responsibility for full qualification of the connector system is that of the customer. Molex accepts no liability for connector performance or tooling support where tooling other than Molex Tooling is used or where Molex Tooling is modified.

Material Info

Reference - Drawing Numbers
Application Tooling Documents

ATS-622018790, TM-622018799



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Not Reviewed

REACH SVHC

Not Contained Per
-ED/01/2018 (15
January 2018)

Halogen-Free

Status

Not Relevant

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Not Relevant

Not Relevant

Not Contained

Search Parts in this Series

[207123 Series](#)

Use With

[170335](#) Impact Backplane Signal Module Assembly, 4-Pair by 10 Column 85 Ohm Assemblies

Application Tooling

Description

FAQ

Product #

Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Open End Walls, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	1703351105
Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Open End Walls, 10 Columns, 120	1703351106

Circuits, Pin Length
4.50mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact 85 Ohm 1703351107
Plus 4 Pair Vertical
Header, Unguided,
Open End Walls,
10 Columns, 120

Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact 85 Ohm 1703351108
Plus 4 Pair Vertical
Header, Unguided,
Open End Walls,
10 Columns, 120

Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact 85 Ohm 1703351127
Plus 4 Pair Vertical
Header, Unguided,
Dual End Walls,
10 Columns, 120

Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact 85 Ohm 1703353106
Plus 4 Pair Vertical
Header, Left Guide,
Open End Walls,
10 Columns, 120

Circuits, Pin Length
4.50mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact 85 Ohm 1703353107
Plus 4 Pair Vertical
Header, Left Guide,
Open End Walls,
10 Columns, 120

Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact 85 Ohm 1703353127
Plus 4 Pair Vertical
Header, Left Guide,
Open End Walls,
10 Columns, 120

Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,

Keying Orientation B,
Lead-Free
Impact 85 Ohm 1703355104
Plus 4 Pair Vertical
Header, Right
Guide, Open End
Walls, 10 Columns,
120 Circuits, Pin
Length 4.90mm,
Plated Through Hole
Dimension 0.46mm,
Lead-Free
Impact 85 Ohm 1703355106
Plus 4 Pair Vertical
Header, Right
Guide, Open End
Walls, 10 Columns,
120 Circuits, Pin
Length 4.50mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 85 Ohm 1703355107
Plus 4 Pair Vertical
Header, Right
Guided, Left Endwall,
10 Columns, 120
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Lead Free
Impact 85 Ohm 1703357107
Plus 4 Pair Vertical
Header, Left Guide,
Right End Wall,
10 Columns, 120
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact 85 Ohm 1703357157
Plus 4 Pair Vertical
Header, Left Guide,
Right End Wall,
10 Columns, 120
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Keying Orientation E,
Lead-Free
Impact 85 Ohm 1703359107
Plus 4 Pair Vertical
Header, Right
Guide, Left End
Wall, 10 Columns,
120 Circuits, Pin
Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 4X10 85ohm 1703359108
GR BP Endwall 0.46

This document was generated on 02/27/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION