

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** **0750030105**  
**Status:** **Active**  
**Overview:** Plateau HS Mezz™  
**Description:** 1.20mm Pitch Plateau HS Mezz™ Plug, 48 Circuits, 5.50mm Unmated Height

**Documents:**

<a href="#">3D Model</a>	<a href="#">Application Specification AS-75005-001-001 (PDF)</a>
<a href="#">Drawing (PDF)</a>	<a href="#">Packaging Specification PK-75003-002 (PDF)</a>
<a href="#">Product Specification PS-75005-001-001 (PDF)</a>	<a href="#">Test Summary TS-75005-001-001 (PDF)</a>
<a href="#">Product Specification PS-75005-002-001 (PDF)</a>	<a href="#">RoHS Certificate of Compliance (PDF)</a>

**Agency Certification**

CSA	LR19980
UL	E29179


**General**

Product Family	PCB Headers
Series	75003
Application	Board-to-Board, Signal
Overview	Plateau HS Mezz™
Product Name	Plateau HS Mezz™
UPC	756054569931

**Physical**

Breakaway	No
Circuits (Loaded)	48
Circuits (maximum)	48
Color - Resin	Black
Durability (mating cycles max)	25
First Mate / Last Break	No
Flammability	94V-0
Glow-Wire Compliant	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	3.396/g
Number of Rows	2
Orientation	Vertical
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm
Packaging Type	Tube
Pitch - Mating Interface	2.35mm
Plating min - Mating	0.762µm
Plating min - Termination	3.810µm
Robotic Placement	Metal Cap
Shrouded	Fully
Stackable	No
Temperature Range - Operating	-20°C to +85°C
Termination Interface: Style	Surface Mount
Unmated Height	5.50mm

**Electrical**



Series image - Reference only

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
ED/21/2016 (20 June  
2016)

**Halogen-Free**

**Status**

**Low-Halogen**

**Need more information on product  
environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any  
non-product compliance questions.

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

**Search Parts in this Series**

75003 Series

**Mates With**

75005 1.20mm Pitch Plateau HS Mezz™  
Receptacle

Current - Maximum per Contact  
Voltage - Maximum

1.5A  
30V

**Solder Process Data**

Lead-free Process Capability  
Process Temperature max. C

REFLOW  
260

**Material Info**

**Reference - Drawing Numbers**

Application Specification  
Packaging Specification  
Product Specification  
Sales Drawing  
Test Summary

AS-75005-001-001  
PK-75003-002  
PS-75005-001-001, PS-75005-002-001  
SD-75003-001  
TS-75005-001-001

This document was generated on 11/18/2016

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**