

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1054311207](#)
Status: **Active**
Overview: [Nano-Fit Power Connectors](#)
Description: Nano-Fit Vertical Header, Surface Mount, 2.50mm Pitch, Single Row, 7 Circuits, 0.38µm Gold (Au) Plating, Black, Glow-Wire Capable

Documents:

| | |
|--|---|
| 3D Model | Product Specification PS-105405-001-001 (PDF) |
| 3D Model (PDF) | Application Specification AS-105405-001-001 (PDF) |
| Drawing (PDF) | Packaging Specification 1054311000-PK-000 (PDF) |
| Product Specification 1054051000-PS-CH-000 (PDF) | Test Summary 1054050000-TS-000 (PDF) |
| Product Specification 1054051000-PS-ES-000 (PDF) | Datasheet (PDF) |
| Product Specification 1054051000-PS-SK-000 (PDF) | RoHS Certificate of Compliance (PDF) |

General

| | |
|----------------|---|
| Product Family | PCB Headers |
| Series | 105431 |
| Application | Power, Wire-to-Board |
| Component Type | PCB Header |
| Overview | Nano-Fit Power Connectors |
| Product Name | Nano-Fit |
| Taxonomy | PCB Headers and Receptacles |
| UPC | 191128978774 |


Physical

| | |
|--------------------------------|------------------------|
| Breakaway | No |
| Circuits (Loaded) | 7 |
| Circuits (maximum) | 7 |
| Color - Resin | Black |
| Durability (mating cycles max) | 50 |
| Glow-Wire Capable | Yes |
| Keying to Mating Part | Yes |
| Lock to Mating Part | Yes |
| Material - Metal | Brass |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Tin |
| Material - Resin | Liquid Crystal Polymer |
| Net Weight | 1.170/g |
| Number of Rows | 1 |
| Orientation | Vertical |
| PCB Locator | No |
| PCB Thickness - Recommended | 1.60mm |
| Packaging Type | Embossed Tape on Reel |
| Pitch - Mating Interface | 2.50mm |
| Pitch - Termination Interface | 2.50mm |
| Plating min - Mating | 0.380µm |
| Plating min - Termination | 0.762µm |
| Polarized to Mating Part | Yes |
| Polarized to PCB | No |
| Temperature Range - Operating | -40° to +115°C |
| Termination Interface: Style | Surface Mount |

Electrical

| | |
|-------------------------------|------------------|
| Current - Maximum per Contact | 6.5A |
| Voltage - Maximum | 250V AC (RMS)/DC |

Material Info



EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2022)4187-DC (10
June 2022)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[105431](#) Series

Mates With

Nano-Fit Receptacle Housing [1053071207](#)

Reference - Drawing Numbers

| | |
|---------------------------|--|
| Application Specification | AS-105405-001-001 |
| Packaging Specification | 1054311000-PK-000 |
| Product Specification | 1054051000-PS-CH-000, 1054051000-PS-ES-000, 1054051000-PS-SK-000, PS-105405-001-001 |
| Sales Drawing | 1054311000-PK-000, SD-105431-001-000 |
| Test Summary | 1054050000-TS-000 |

This document was generated on 02/27/2023

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION