


Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092

Series: The Blue Dot



Features:

- Chip Antenna
- Frequency:2400MHz ~ 2483MHz
- Low profile
 2.0mm(Length) x 1.2mm(Width)
 x 0.55mm(Thickness)

Applications:

- WLAN
- 802.11b/g
- Bluetooth
- Zigbee, ISM 2.4GHz

All dimensions are in mm / inches

Issue: 2049

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:

Pulse Worldwide Headquarters 12220 World Trade Drive San Diego, CA 92128 USA Tel:1-858-674-8100 Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092

Series: The Blue Dot

ELECTRICAL SPECIFICATIONS

Frequency	2400-2483	MHz
Nominal Impedance	50	Ω
VSWR	3	max
Gain (Typ.)	0.89	dBi
Efficiency(Typ.)	50	%
Polarization	Lir	near



Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092

Series: The Blue Dot

MECHANICAL SPECIFICATIONS

Weight 0.005 g

Size 2.0x1.2x0.55 mm

MSL Level 1

ENVIRONMENTAL SPECIFICATIONS

Operating temperature -40/+105 ° C

High temperature resistance 150 ° C, 1000 hours

Low temperature resistance -40 ° C, 1000 hours

Humidity 85%R.H. 85±5 ° C, 1000 cycles

Soldering heat resistance 260 ° C 10s

Thermal shock -40/+105 ° C

Storage condition

At warehouse 0-30 °C, <60%R.H., shoule be used<1 year

On board -40 ~85 ° C, <85%R.H




Description: Bluetooth, WiFi Antenna


PART NUMBER: W3092


Series: The Blue Dot

MECHANICAL DRAWING

Pad for SMT process









Description: Bluetooth, WiFi Antenna


PART NUMBER: W3092

Series: The Blue Dot

OTHER SPECIFICATIONS

Recommended PCB layout(Unit:mm)

PCB size(L X W X T): 110 X 55 X 1mm








Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092

Series: The Blue Dot

OTHER SPECIFICATIONS

PCB top side layout



Issue: 2049

ROHS




Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092

Series: The Blue Dot


OTHER SPECIFICATIONS

PCB bottom side layout



*Clearance 8mm × 2.7mm : All metallization should be removed from all PCB layers.

Recommended matching circuit








Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092

Series: The Blue Dot

OTHER SPECIFICATIONS

Recommended reflow soldering



Time

Α	1 st rising temperature	The normal to Preheating temperature	30s to 60s
В	Preheating	140°C to 160°C	60s to 120s
С	2 nd rising temperature	Preheating to 200°C	20s to 40s
D Main he		if 220°C	50s∼60s
		if 230°C	40s∼50s
	Main heating	if 240°C	30s∼40s
		if 250℃	20s~40s
		if 260°C	20s~40s
Е	Regular cooling	200°C to 100°C	1℃/s ~ 4℃/s

^{*}reference: J-STD-020C

(1) Soldering gun procedure

Note the follows, in case of using solder gun for replacement.

- (a) The tip temperature must be less than 350°C for the period within 3 seconds by using soldering gun under 30 W.
- (b) The soldering gun tip shall not touch this product directly.

(2) Soldering volume

Note that excess of soldering volume will easily get crack the body of this product.

Issue: 2049

ROHS




Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092

Series: The Blue Dot

CHARTS

VSWR







Description: Bluetooth, WiFi Antenna


PART NUMBER: W3092

Series: The Blue Dot

CHARTS

Efficiency

Efficiency vs Frequency measured with demo board





Description: Bluetooth, WiFi Antenna


PART NUMBER: W3092

Series: The Blue Dot

CHARTS

Peak Gain

Peak Gain vs Frequency measured with demo board



—-W3092






Description: Bluetooth, WiFi Antenna


PART NUMBER: W3092

Series: The Blue Dot

CHARTS



Radiation pattern XY Plane



2400MHz

Avg (dBi) = -4.07Peak (dBi) = -2.05Avg -3 (deg) = 285

2450MHz

Avg (dBi) = -3.89 Peak (dBi) = -1.39 Avg -3 (deg) = 265

2480MHz

Avg (dBi) = -3.32 Peak (dBi) = -1.32 Avg -3 (deg) = 265

— 2400MHz —— 2450MHz —— 2500MHz

Phi Angle (°)

Power (dBm)




Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092


Series: The Blue Dot

CHARTS



Radiation pattern

ZX Plane








Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092


Series: The Blue Dot

CHARTS



Radiation pattern









Description: Bluetooth, WiFi Antenna

PART NUMBER: W3092


Series: The Blue Dot

PACKAGING

Taping Package and Label Marking: (unit: mm)


(1) Quantity/Reel: 5000pcs/Reel

(2) Carrier tape dimensions



Type	Α	В	С	D	Е	F	L	W
ACA2012	8.00±	3.50±	1.75±	2.00±	4.00±	1.50±	2.30±	1.55±
	0.30	0.05	0.10	0.05	0.10	0.10	0.10	0.10

(3) Taping reel dimensions



Α	178.0±2.0
В	2.0±0.5
С	13.0±0.5
D	21.0±0.8
Ε	62.0±1.5
F	9.0±0.5
G	13.0±1.0