

SMH-110-02-L-D SMH-112-02-L-S SMH-120-02-G-S **SMH SERIES**

(2.54 mm) .100"

SMT HORIZONTAL SOCKET

Mates With:

TSW, MTSW, MTLW, EW, ZW, TSS, ZSS, TSM

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?SMH

Insulator Material: Black LCP

Contact Material:

Contact Material:
Phosphor Bronze
Plating:
Au or Sn over
50 µ" (1.27 µm) Ni
Operating Temp Range:
-55 °C to +125 °C with Gold
-55 °C to +105 °C with Tin

Insertion Depth:

(3.68 mm) .145" to (6.35 mm) .250"

Max Cycles: 100 with 10 μ" (0.25 μm) Au RoHS Compliant:

PROCESSING

Lead-Free Solderable:

SMT Lead Coplanarity: (0.15 mm) .006" max (02-24) (0.20 mm) .008" max (25-36)* *(.004" stencil solution may be available; contact IPG@samtec.com)

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



ALSO AVAILABLE (MOQ Required)

Other platings

Important Note: SMH mated to TSM-DH/-SH not coplanar, SSM-DH/-SH recommended for coplanar applications.

Some lengths, styles and options are non-standard, non-returnable.

