



AERODYNAMIC BEARINGS

MICRO BLOWERS

NIDEC COPAL ELECTRONICS CORP.

AERODYNAMIC BEARINGS

MICRO BLOWERS

Our unique Aerodynamic Bearings technology generates a non-contact rotational motion to provide ultra-high speed rotation.
(Max.50,000 rpm)

Compact
Light weight

Actual size ratio



Dime
Coin diameter
φ 0.705 inch (φ 17.9 mm)



TF029B-1000-F
Impeller diameter
φ 1.142 inch (φ 29 mm)



TF037F-2000-F
Impeller diameter
φ 1.457 inch (φ 37 mm)



TF037C-2000-F
Impeller diameter
φ 1.457 inch (φ 37 mm)



TF037C-2100-F
Impeller diameter
φ 1.457 inch (φ 37 mm)



TF037E-2000-F
Impeller diameter
φ 1.457 inch (φ 37 mm)

High static
Pressure



Ultra high-speed rotation



Low vibration
Long life





No wear on shaft and sleeve



Aerodynamic bearings

Non-contact bearing structure

balancing optimization



*The above is the deformed image.


Please watch the high performance of our Micro Blowers with the video on YouTube.
<https://youtu.be/UWwYQcCXtk>

Applications

Compact and high power microblowers are ideal for the following applications.



CPAP
(Medical Devices)



Fuel Cell System




Server



Air Cleaner



Ionizer



3D Printer

Quick Reference Table

Item	Part No.	TF037C-2100-F / TF037C-2000-F	TF037E-2000-F	TF037F-2000-F	TF029B-1000-F
Rated Voltage		24 VDC ±10%	24 VDC ±10%	12~24 VDC	12~27 VDC
Rated Power Supply Current		1.2 A Max.	0.86 A Max.	0.67 A Max.	0.62 A Max.
Rated Power Consumption		29 W Max.	22.7 W Max.	16.1 W Max.	14.9 W Max.
Rated Rotation Speed		40,000 r/min	35,500 r/min	31,000 r/min	36,000 r/min
Rated Air Flow		100 l/min	100 l/min	100 l/min	100 l/min
Rated Pressure		4 kPa	3 kPa	2 kPa	2 kPa
Maximum Rotation Speed		45,000 r/min	45,000 r/min	45,000 r/min	50,000 r/min
Maximum Pressure		4.5 kPa	4.5 kPa	4.5 kPa	3.5 kPa
Acoustic Audible Noise		67.0 dB (A) Max.	65.0 dB (A) Max.	65.0 dB (A) Max.	65.0 dB (A) Max.
Weight		2100-F: 94 g / 2000-F: 90 g	165 g	72 g	55 g
Material in Resin		Full compliance with UL94 V0		Full compliance with FDA standards	

AERODYNAMIC BEARINGS
MICRO BLOWERS

NIDEC COPAL ELECTRONICS CORP. (Head Office)

7-5-25 Nishi-Shinjuku, Shinjuku-ku, Tokyo 160-0023 JAPAN
Phone:+81-3-3364-7055 Fax:+81-3-3364-7098

NIDEC COPAL ELECTRONICS, INC.

367 Van Ness Way, Suite 601
Torrance, CA 90501 U.S.A
Phone:+1-310-618-0225 Fax:+1-310-618-9984

NIDEC COPAL ELECTRONICS GmbH

Mergenthalerallee 79-81
65760 Eschborn GERMANY
Phone:+49-6196-92775-0 Fax:+49-6196-92775-75

NIDEC COPAL ELECTRONICS SINGAPORE PTE. LTD.

180B Bencoolen Street #07-05 The Bencoolen Singapore 189648
Phone +65-6535-0056 Fax:+65-6535-0087

NIDEC COPAL ELECTRONICS (SHANGHAI) CO.,LTD.

Unit A, 4/F, No.4 Bldg., No.253, Ai Du Rd., Wai Gao Qiao
Free Trade Zone, Shanghai 200131, CHINA
Phone:+86-21-5046-3009 Fax:+86-21-5046-3115

NIDEC COPAL ELECTRONICS (TAIWAN) CO., LTD.

18F-1, No.57, Sec.2, Tun Hwa S.Rd., Taipei 106, TAIWAN
Phone:+886-2-27030577 Fax:+886-2-27010577

NIDEC COPAL ELECTRONICS KOREA CORP.

Woolim Lion's Valley, C- 406, 371-28, Gasan-dong,
Geumcheon-gu, Seoul, 153-786, KOREA
Phone:+82-2-3482-5861 Fax:+82-2-3482-5860

<https://www.nidec-copal-electronics.com>

Sales agent: