THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.														PANDUIT CORP.	
				CUT-THRU FOR #	LO TRUS	S HEAD S	SCREW.								
.3	00 REF Typ					E REF.									
								A							
				PANDUIT Part no.	in	E DIA. Max. (mm)	A in (mm) in (mm	n) in	(mm)	D in (r	nm) in (mm)	MIN. LOOF TENSILE IN		
			HLT2I		.25 (6.4)	1.91 .100 (48.5) (2.5		0.50		.50 38.1)	1.00 (25.4)			INTERMEDIATE	
			H	LT3I	.25 (6.4)	3.18 (80.6)	.100 (2.5			1.50 38.1)	1.((25,		40 (178)	INTERMEDIATE	
NOTES: 1) SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE AND PART COLOR. * 2) MINIMUM 2" OVERLAP REQUIRED TO ACHIEVE LOOP TENSILE RATING. CAD FILENAME/LAYERS DIMENSIONS IN PARENTHESIS ARE IN METRIC UNITS SS_26938_07 CORP. TINLEY PARK, ILLINOIS															
										ТАК-ТҮ ™	CABLE TIES				
													ESS OTHERWISE		UNLESS OTHERWISE SPECIFIED,
07	01/14/19	SAT	DWW B. UPDATED MATERIAL. A. REMOVED APPROXIMATE WEIGHT COLUMN.					26938	7	ML		(.×	IENSIONAL TOLE () <u>+</u> ((X) ± .125 A	.XXX) ± .030	ALL DIMENSIONS ARE GIVEN
6	1/16/06	ERW	ADDED APPROX. WEIGHT PER 100 PIECES					26938	6			drawn by KET	MAT'L:		scale NONE
5	5/3/05	ERW	W JVL REMOVED OVAL SLOT DIMENSION TO BE CONSISTENT WITH OTHER CUSTOMER DRAWINGS					26938	5	JVL		DATE 11/28	3/94 HOOKS:	O-BACK HOOK AND LOOF POLYETHYLENE OR NYLON	Dwg
REV	DATE BY CHK DESCRIPTION							ECN -	R	CUST	SUP	снк о Н		NYLON	SS-26938 A size