	T D	т п		0			
4	Z M M M M M M M M M M M M M	ØF F F F F F F F F F F F F F F F F F F					
ယ				LAYOUT SHOWN AS EXAMPLE	3		
		Keying Shown as example					
	CHARACTERISTICS	Connector dimension	-				
	-Standard : Based on MIL-DTL-38999 Series III	DimNominalF19.05 Max	-				
	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy	Z 31.5 Max VV THREAD M15x1-6g		SOURIAU shall not be liable for any non-conform due to a use of the Products which does not the Specifications issued by either of the Parties of (professional recommendation, technica	comply with or by a third party		
$\sim$	-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories			Country Jurisdiction & Control List   FR Not Listed			
				PN: 8D111F99PA			
	-Temperature Range <sub>:</sub> -65°C to +200°C -Salt Spray : 48 hours		A 26-09-2016	A 26-09-2016 First Release			
			ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING		
				TITLE Aluminium Inline plug 8D series			
	BASIC SERIES: 8D 1 - 11 F	99 P A	SCALE	General linear Tolerances:	NPRDS / PROJECT		
<b></b>	SHELL TYPE : In line Receptacle     CONTACT TYPE : Standard Crimp Contact     SHELL SIZE : 11     CONTACT TYPE : PIN(500 Matings)				859 This document is the property of SOURIAU		
				SOURIAU WWW.SOURIAU.COM it must not be re communicated with			
	PLATING : F = Nickel	CONTACT LAY		SOURIAU DRG N	• SHEET		
			A3	8D111F99PA-C	1/2		
	H I G I	F I E	D	C I B	I A		

	±	G	н т	m	D	C
		Contact Layout				
4	-×	$ \begin{array}{c} & & & \\ & & & \\ & & & \\ & & $				
	Conta positio ID A B C D E F F G Shell Arrangement Numbe size no. conta	X-axis (mm)     Y-axis (mm)       +.065 (1.65)     +.113 (2.87)       +.130 (3.30)     +.000 (0.00)       +.065 (1.65)    113 (2.87)      065 (1.65)    113 (2.87)      065 (1.65)     +.113 (2.87)      065 (1.65)     +.100 (0.00)      065 (1.65)     +.113 (2.87)      065 (1.65)     +.113 (2.87)       +.000 (0.00)     +.000 (0.00)      065 (1.65)     rulia (2.87)      065 (1.65)     rulia (2.87)      065 (1.65)     rulia (2.87)      000 (0.00)     +.000 (0.00)				
ယ	11 -99 7	20 I Ali MS20050-99				
	_					
						SOURIAU shal due to a us the Specification (profes
2						
					ISS DATE	
					Designed By:	Date
1					SCALE NA	
					FORMAT A3	JWWW
	Н	G	F	E	D	С

