T G	m		C B	A	_	
A M Thread	ØF				4	
ω 			LAYOUT SHOWN AS EXAMPLE		3	
	Keying Shown as example					
CHARACTERISTICSStandard : Based on MIL-DTL-38999 Series III	Connector dimensionDimNominal					
-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	F         19.05 Max           Z         31.5 Max           VV THREAD         M15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet: Silicon ElastomerN-Contact Plating: Gold over copper Alloy 0.8µm minimum			CountryJurisdiction & Control ListFRNot Listed			
<ul><li>-Durability : 500 Mating cycles</li><li>-Delivered with Souriau contacts and Accessories</li></ul>			PN: 8D111W04PN			
-Temperature Range <sub>:</sub> -65°C to +175°C -Salt Spray : 500 hours		A 26-09-2016 ISS DATE Designed By:	First Release Latest modification - by Date:	MOD N CUSTOMER DRAWING	• •	
		TITLE	Aluminium Inline	e plug 8D series		
BASIC SERIES: 8D 1 - 11 W SHELL TYPE : In line Receptacle	04 P N	SCALE - NA	General linear Tolerances:	NPRDS / PROJECT <b>859</b>	1	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORIENT		SOURIAU         This document is the property of SOURIAU           it must not be reproduced or communicated without permission			
PLATING : W = Olive drab Cadmium	CONTACT TYPE : PIN(SOC		SOURIAU DRG	N° SHEET	-	
H G	F E	D	8D111W04PN	-C 1/2		

ſ	т	۵	г	п	D	0	Φ	A		-
		Contact Layout								
		*+Y								
4	-x	↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔ ↔								4
	Contac positio ID	n X-axis Y-axis								
	A B C D	+.065 (1.65) +.065 (1.65) 065 (1.65)								
	Shell sizeArrangement no.Number conta11-44	cts contacts rating location								
ω										3
										3
	<u> </u>									
						SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
N								tion & Control List Not Listed		2
						PN: 8D111W04PN				
					A 26-09-201	6 First Release				-
					ISS DATE Designed By:	Latest modification - by Date:		CUSTOMER DRAWING	MOD N°	-
					TITLE	Aluminium Inline plug 8D series				_
					SCALE	General lin Tolerance		NPRDS / PROJECT		-
<b>_</b>					NA			859 This document is the pro	perty of	1
					SOURIAU	WWW.SOURIA	U.COM	SOURIAU it must not be reproduc communicated without pe		
					FORMAT A3		AU DRG N°		SHEET	
L		<u>^</u>	F	_			LW04PN-C	•	2/2	
	Н	G			D I	C	В	A		