The set of	4
CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal F 22.25 Max	
-Shell Material : Aluminium I Z2.25 Max -Shell Plating : Olive drab Cadmium Z 31.5 Max -Shell Plating : Olive drab Cadmium VV THREAD M18x1-6g -Insulator : Thermoplastic VV THREAD M18x1-6g -Contacts : Copper Alloy : Copper Alloy : Copper Alloy	
-Seals & Grommet: Silicon ElastomerCountryJurisdiction & Control ListContact Plating: Gold over copper Alloy 0.8μm minimum	2
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours	
	OD N°
TITLE Aluminium Inline plug 8D series	
BASIC SERIES: 8D 1 - 13 W 04 A N SHELL TYPE In line Receptacle SHELL TYPE In line Receptacle Odd A N	
SHELL TYPE : In line Receptacle NA ± USS CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SOURIAU SHELL SIZE : 13 CONTACT TYPE : PIN(500 Matings) WWW.SOURIAU.COM	
	HEET 1/2
H G F E D 8D113W04AN-C H G F A	L/ Z

		Q	г	т	D	C	σ	A		-
4	-X.	(1111) (1111)								4
 ა	B C D Shell Arrangement Nur size no. co	+.146 (3.71) +.035 (0.89) +.000 (0.00) 083 (2.11) 146 (3.71) +.035 (0.89)								3
	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)									
2					A 27-09-201	Country Jurisdiction & Control List FR Not Listed PN: 8D113W04AN 7-09-2016 First Release				2
		ISSDATELatest modification - byDesigned By:Date:CUSTOMER DRAWINGTITLEAluminium Inline plug 8D series							MOD N°	-
1		SCALE General linear NPRDS / PROJECT NA Tolerances: 859 ± This document is the pro SOURIAU WWW.SOURIAU.COM This document is the production of the reproduction of the						859 his document is the propo SOURIAU it must not be reproduce	ed or	- 1
	Н	G	F	E	A3		13W04AN-C B	A	2/2	