	E G	т (Г			0	Φ	A			
4	Z Pearly M Parly M	ØF						4		
ယ					LAYOUT SHO	WN AS EXAMPLE		3		
		Keying Shown as example								
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal								
	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	F 22.25 Max Z 31.5 Max VV THREAD M18x1-6g			mage ith rd party					
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum				k Control List isted	2				
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D113W98PB						
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours			A 27-09-2016 ISS DATE Designed By:	First Release Latest modification - by Date:	CUST	MOD OMER DRAWING	 N°		
				TITLE	Alun	ninium Inline plug 8D	series			
_	BASIC SERIES: 8D 1 - 13 W SHELL TYPE : In line Receptacle I	98 P B		SCALE -	Genera Tolera ±	inces:	PRDS / PROJECT 859	1		
	CONTACT TYPE : Standard Crimp Contact		SOURIAU	his document is the property of SOURIAU it must not be reproduced or						
	SHELL SIZE : 13 PLATING : W = Olive drab Cadmium	CONTACT TYPE : PI	N(500 Matings) LAYOUT : 13-98	FORMAT		RIAU DRG N°	mmunicated without permission			
	H G	F E		A3	8D1 C	13W98PB-C B	1/2			
		_	\vee							

-	Т	D	ш	П	п	C	כ	0		Φ		A		
		Contact Layout												
4		$\begin{array}{c} & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ &$												4
		Contacts (Insert arrangement 13-98) Location Contact position ID Location X-axis (mm) Y-axis (mm) A +.000 (0.00) +.195 (4.95) B +.125 (3.18) +.150 (3.81) C +.193 (4.90) +.030 (0.76) D 104 (4.17) 105 (2.67) E +.000 (0.00) 135 (3.43) F 164 (4.17) 105 (2.67) G 193 (4.90) +.030 (0.76) H 125 (3.18) +.150 (3.81)												
دی ا	size	H 125 (3.18) +.150 (3.81) J +.065 (1.65) 015 (0.38) K 065 (1.65) 015 (0.38) Ingement Number of contacts Size contacts Service rating -98 10 20 I												3
										le for any non-confor				
								the Specificat	ions issued by	ducts which does not either of the Parties nmendation, technica	or by a third			
N										FR	risdiction & Not Lis	Control List ted]	2
							A 27-09-2	016 First Release	PN: 8D	113W98PB				_
						_	ISS DATE						MOD N°	
						_	Designed By: TITLE	D	ate: Alur	ninium Inline p		MER DRAWING eries		_
_						_	SCALE			al linear ances:	NPR	DS / PROJECT 859		- 1
						-	SOURIA	U ww	W.SOUR	IAU.COM	it	s document is the pro SOURIAU must not be reprodu municated without p	ced or	
						-	FORMAT			RIAU DRG N			SHEET	
			 	 	-		A3	^	8D1	13W98PB-0		٨	2/2	
	Н	l G	F	E		[J	C		В	I	А		