⊥ G		m (0			
	ØS						
	I			LAYOUT	SHOWN AS EXAMPLE		
	Keying Shown as example						
CHARACTERISTICS	Connec	ctor dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim ØS	Nominal 25 Max					
-Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	Z' VV THREAD	31.5 Max M15x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer					Country Jurisdic	tion & Control List]]
-Contact Plating : Gold over copper Alloy 0.8µm minimum			[Not Listed	
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D511M22SDL				
-Temperature Range : -65°C to +200°C		Г					
-Salt Spray : 2000 hours			A 16-10-20	016 First Release			
Mass : 12.8 g ± 10%		-	ISS DATE Designed By:	Latest modification - b Date:	y	CUSTOMER DRAWING	MOD N°
		-	TITLE Composite Plug 8D series				
BASIC SERIES: 8D 5 - 11 M	22 S D L	-	SCALE		eneral linear	NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding		Delivered W/O Contacts	NA	$\forall \forall $	Tolerances: ±	859	
CONTACT TYPE : Standard Crimp Contact		ORIENTATION : D				This document is the pro SOURIAU	perty of
SHELL SIZE : 11	CON	TACT TYPE : SOCKET(500 Matings)	SOURIA	U WWW.SO	URIAU.COM	it must not be reprodu communicated without pe	
PLATING : M = Nickel		CONTACT LAYOUT : 11-22	FORMAT	<u> </u>	DURIAU DRG N°		SHEET
		1	A3		D511M22SDL-C		1/2
				0			

_	Ŧ	۵	н г	m	D	0
4		Contact Layout 22*				
 	Ctc A B C D	4#22D 11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905				
	_					SOURIAU shall not be liable for a due to a use of the Products w the Specifications issued by either (professional recommenda
2						Coun FR PN: 8D511
_					A 16-10-201 ISS DATE Designed By:	6 First Release Latest modification - by Date:
_ _					TITLE SCALE NA SOURIAU	
					FORMAT	SOURIAL

G

Н

F

Е

A3

D

С

