Σ <u></u>	т (п		0	₿ >		
					-	
	And		LAYOUT SHOWN AS EXAMP	LE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension Dim Nominal					
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
 Contact Plating : Gold over copper Alloy 0.8μm minimum 			Country FR	Jurisdiction & Control List Not Listed		
-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories			PN: 8D513F03BB			
-Temperature Range : -65°C to +200°C -Salt Spray : 48 hours		A 17-10-2016	First Release			
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	<u>) N°</u>	
		TITLE	TITLE Aluminium Plug 8D series			
→ BASIC SERIES: 8D 5 - 13 F C)3 B B	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIEN CONTACT TYPE : SOCKET(50	TATION : B 0 Matings)	WWW.SOURIAU.COM	This document is the property of SOURIAU it must not be reproduced or communicated without permission		
PLATING : F = Nickel	CONTACT LAYO	OUT : 13-03	SOURIAU DR			
		A3	8D513F03E	B-C 1/2	•	

	T	۵	н П	m	D	0	
		Contact Layout					
4							
	Ctc A B	3#16 13-03 X Y 2.39 1.47 0 -2.79 2.20 1.47					
ယ	С	-2.39 1.47					
						SOURIAU shall no due to a use of the Specifications is (profession	the Products v
N							Cour
						19	N: 8D513
					ISS D	D-2016 First Release	- by
					Designed By:	Date:	Alumi
_					SCALE NA		General linear Tolerances: ±
					SOUR	AU WWW.S	OURIAU.
					FORMAT A3		SOURIAI 8D513F

G

Н

F

Е

D

С

