ב בר				0	σ		
ØS~							
				LAYOUT SHOWN A			
				LATOOT SHOWIN A			
	Keying Shown as example						
CHARACTERISTICS  -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal	]					
Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum						ion & Control List Not Listed	
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				PN: 8D51			
-Temperature Range : -65°C to +200°C		A	14-10-2016 Firs	st Release			
-Salt Spray : 48 hours		ISS Design		Latest modification - by Date:		CUSTOMER DRAWING	MOD N°
			TITLE		Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 17 F SHELL TYPE : Plug with RFI Shielding	20 S E	SCA N		General linea Tolerances:		NPRDS / PROJECT <b>859</b>	
CONTACT TYPE : Standard Crimp Contact			SOURIAU WWW.SOURIAU.COM This document is the propert SOURIAU it must not be reproduced communicated without permit		iced or		
SHELL SIZE : 17	CUNTACT TYPE : SUCKETT:					in the second product	
SHELL SIZE : 17 PLATING : F = Nickel	CONTACT TYPE : SOCKET(			SOURIA	U DRG N°		SHEET

ſ	т	۵	<u>п</u>	m		0
4		Contact Layout <b>20*</b> <b>4#</b> 12 16#22D				
ω	Ctc A B C D 1 2 3 4 5 6	17-20           X         Y           0         5.51           3.17         0           0         -5.51           -3.17         0           4.16         7.06           4.29         4.29           7.11         4.03           8.05         1.4           8.05         -1.4           7.11         -4.03				
N	7 8 9 10 11 12 13 14 15 16	4.29       -4.29         4.16       -7.06         -4.16       -7.06         -4.29       -4.29         -7.11       -4.03         -8.05       -1.4         -8.05       1.4         -7.11       4.03         -4.29       4.29         -4.16       7.06			A 14-10-20	SOURIAU shall not be liable for a due to a use of the Products w the Specifications issued by either (professional recommend Coun FR PN: 8D517 16 First Release
					ISS DATE Designed By: TITLE SCALE NA SOURIA FORMAT A3	Date: Alumi General linear Tolerances: ±
l	Н	G	F	E	D	C

