T Q	m m	D	0	ω	A	
A						4
CHARACTERISTICS	Keying Shown as example		LAYOUT SHOWN	N AS EXAMPLE		3
-Standard : Based on NIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	DimNominalØS35.7 MaxZ31 MaxVV THREADM25x1-6g		the Specifications issued by eit (professional recomm	cts which does not comply w	ith rd party & Control List	2
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 40.26 g ± 10%		A 18-10-2016 ISS DATE Designed By:		17Z26SN	MOD N OMER DRAWING	J°
BASIC SERIES: 8D 5 - 17 Z 26	S N	SCALE	General lir Tolerance		ies PRDS / PROJECT 859	
SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 PLATING : Z = Black Zinc Nickel	ORIENTATIO CONTACT TYPE : SOCKET(500 Ma CONTACT LAYOUT :	atings)	SOURI	AU DRG N°	This document is the property of SOURIAU it must not be reproduced or ommunicated without permission SHEET	1
H G	F E	D A3	8D51	.7Z26SN-C B	1/2	

